TRAFFIC PLANNING AND DESIGN, INC.



www.TrafficPD.com

610.326.3100

TPD@TrafficPD.com

October 17, 2014


Access Improvements Associated with Ardrossan Farm Radnor Township, Delaware County Newtown Road (SR 1021) TPD Job # ESII.A.00001

DRAINAGE NARRATIVE

Analyses have been performed for the spread of flow across Road B and Road C, two proposed accesses to Newtown Road (SR 1021). The enclosed drainage calculations indicate that the spread of flow at Road B meets PennDOT allowable criteria in accordance with Publication 13M Design Manual 2. The post-development spread at Road C represents a 27% reduction compared to pre-development conditions.

Attached are the calculations for the peak flow and spread of flow for the 10-year frequency storm with a 5-minute time of concentration as required by PennDOT. The drainage areas used for the computations can be found in attached plan sheets.

Gutter Spread Points of Interest	Pre-Dev. Spread	Post-Dev. Spread	Difference	Percent Change
P.O.I. #1 – Road C across from	(ft)	(ft)	(ft)	
Abrahams Road STA 150+00.00 RT	21.60	15.75	-5.85	-27.08%



	@	loh No:	ESII.A.00001
$\overline{}$		JOD 110I	E311.A.0000 I
		Description:	Ardrossan Farm
	Tra	ffic Planning & De	sian

Computed By:	BF	Date:	10-21-14
Checked By:		Date:	

Pre-Development Weighted Runoff Factor and Peak Discharge Computation

Peak Discharge Q = (C) x (I) x (A)

	Rur	noff Factor "C"	
Concrete	0.95	Light Growth	0.30
Asphalt	0.90	Woods/Heavy Growth	0.25
Residential	0.55		

Design Storm = 10

						Woods/H							
Area	Total				Light	eavy	Weighted			PA	Rainfall	Peak	
Number	Area	Concrete	Asphalt	Residential	Growth	Growth	"C" Value	Tc	Мар	Region	Intensity	Discharge	Remarks
	(Ac.)	(Ac.)	(Ac.)	(Ac.)	(Ac.)	(Ac.)		minutes			(Inches/Hr.)	(cfs)	
DA Road C Spread	12.243	0.000	0.425	0.000	11.818	0.000	0.32	5.0	С	4.0	6.60	25.924	STA 150+00.00 RT

Overall	12.24	0.00	0.43	0.00	11.82	0.00			25.92
Total	12.24	0.00	0.43	0.00	11.02	0.00			25.52

_		Job No:	ESII.A.00001
		Description:	Ardrossan Farm
	Tra	ffic Planning & De	esign

Computed By:	BF	Date:	10-21-14
Checked By:		Date:	

Post-Development Weighted Runoff Factor and Peak Discharge Computation

Peak Discharge Q = (C) x (I) x (A)

	Ru	noff Factor "C"	
Concrete	0.95	Light Growth	0.30
Asphalt	0.90	Woods/Heavy Growth	0.25
Residential	0.55		

Design Storm = 10

Area Number	Total Area	Concrete	Asphalt	Residential	Light	Woods/H eavy Growth	Weighted "C" Value	Тс	Мар	PA Region	Rainfall Intensity	Peak Discharge	Remarks
	(Ac.)	(Ac.)	(Ac.)	(Ac.)	(Ac.)	(Ac.)		minutes			(Inches/Hr.)	(cfs)	
DA Road B Spread	0.003	0.000	0.003	0.000	0.000	0.000	0.90	5.0	С	4.0	6.60	0.018	STA 163+40.01 RT
DA Road C Spread	3.052	0.000	0.399	0.000	2.653	0.000	0.38	5.0	С	4.0	6.60	7.623	STA 150+00.00 RT

Overall	2.06	0.00	0.40	0.00	2.65	0.00			7.64
Total	3.06	0.00	0.40	0.00	2.65	0.00			7.04

Channel Report

Hydraflow Express by Intelisolve

Tuesday, Oct 21 2014

ESII.A.1 Road B Spread

 User-defined

 Invert Elev (ft)
 = 429.72

 Slope (%)
 = 0.10

 N-Value
 = 0.015


Calculations

Compute by: Known Q Known Q (cfs) = 0.02 Highlighted

Depth (ft) = 0.04Q (cfs) = 0.020Area (sqft) = 0.13Velocity (ft/s) = 0.15Wetted Perim (ft) = 6.51Crit Depth, Yc (ft) = 0.03Top Width (ft) = 6.51EGL (ft) = 0.04

(Sta, El, n)-(Sta, El, n)...

(0.00, 429.89)-(8.49, 429.75, 0.015)-(10.46, 429.72, 0.015)-(20.28, 429.82, 0.015)-(50.00, 430.41, 0.015)



Channel Report

Hydraflow Express by Intelisolve

Tuesday, Oct 21 2014

ESII.A.1 Existing Road C Spread


User-defined Highlighted = 386.44Invert Elev (ft) Depth (ft) = 0.41Slope (%) = 1.46Q (cfs) = 25.92N-Value = 0.015= 5.59 Area (sqft) Velocity (ft/s) = 4.64**Calculations** Wetted Perim (ft) = 21.61Crit Depth, Yc (ft) Compute by: Known Q = 0.52Known Q (cfs) = 25.92Top Width (ft) = 21.60

EGL (ft)

= 0.74

(Sta, El, n)-(Sta, El, n)...

(0.00, 386.62)-(11.93, 386.46, 0.015)-(12.10, 386.44, 0.015)-(12.46, 386.45, 0.015)-(14.20, 386.56, 0.015)-(26.19, 387.03, 0.015)



Channel Report

Hydraflow Express by Intelisolve

Tuesday, Oct 21 2014

ESII.A.1 Road C Spread

User-defined

Invert Elev (ft) = 386.47 Slope (%) = 1.82 N-Value = 0.015

Calculations

Compute by: Known Q Known Q (cfs) = 7.61

(Sta, El, n)-(Sta, El, n)...

(0.00, 386.62)-(8.32, 386.50, 0.015)-(10.65, 386.47, 0.015)-(51.91, 388.33, 0.015)

Highlighted

Depth (ft) = 0.23Q (cfs) = 7.610= 2.25Area (sqft) Velocity (ft/s) = 3.38Wetted Perim (ft) = 15.76Crit Depth, Yc (ft) = 0.29Top Width (ft) = 15.75EGL (ft) = 0.41

