


**STORMWATER MANAGEMENT REPORT AND
SITE DRAINAGE CALCULATIONS**

LANCASTER AVENUE HOUSING

**VILLANOVA UNIVERSITY
RADNOR TOWNSHIP
DELAWARE COUNTY, PENNSYLVANIA**

VILLANOVA UNIVERSITY



**Issued: December 5, 2014
Nave Newell No.: 2011-005.00**

**STORMWATER MANAGEMENT REPORT AND SITE DRAINAGE CALCULATIONS
SUMMARY OF CONTENTS**

**WALDEN
LANCASTER COUNTY, LANCASTER, PA**

Section	Title	Page
I.	Stormwater Management Narrative Introduction Existing Conditions Stormwater Management Criteria	1
II.	USGS Norristown Quadrangle	5
III.	USDA NRCS Soil Survey	7
IV.	Radnor Township Exhibits	12
V.	Volume Calculations POI 2A Summary for Volume Management Rain Garden, Infiltration and Cistern Supporting Calculations NPDES Worksheets POI 2A Worksheet 4	19
VI.	Peak Rate Summary	26
VII.	Peak Rate Analysis HydroCAD Routing Diagram POI 2 Pre-Development Information Summary for Sub-catchment 11S (Total Flow to POI 2A) Summary for Link 15L (Total Flow to POI 2A) Post-Development Information (Controlled) Summary for Sub-catchment 20S (Captured Infil-1) Summary for Sub-catchment 17S (From Rain Gardens) Summary for Pond 19P (Infiltration Basin-1) Summary for Sub-catchment 16S (Route 30 Bio-swales) Summary for Pond 28P (Detention-1) Summary for Sub-catchment 30S (From Rain Gardens) Summary for Link 27L (Link to Infiltration-2) Summary for Sub-catchment 22S (Captured Infil-2) Summary for Pond 21P (Infiltration-2) Summary for Link 28S (Captured Infil-3) Summary for Pond 27P (Infiltration-3) Summary for Sub-catchment 13S (Cistern-1) Summary for Pond 14P (Cistern-1) Summary for Sub-catchment 29S (Cistern-2) Summary for Pond 21P (Cistern-2) Summary for Sub-catchment 31S (From Rain Garden-11) Summary for Sub-catchment 12S (Ithan and Uncap) Summary for Link 15L (Total Flow to POI 2A)	28

Section	Title	Page
VIII.	StormCAD Output Inlet Drainage Area Calculations StormCAD Analysis 25 Year Storm StormCAD Analysis 100 Year Storm Storm Drain Profiles Rip-Rap Design	232
IX.	Infiltration Test Report and Test Logs	267
Appendix	Pre-Development Drainage Area Plan Post-Development Drainage Area Plan – Peak Rate Detention Post-Development Drainage Area Plan – Volume Management Inlet Drainage Area Plan	Pocket

l.

STORMWATER MANAGEMENT NARRATIVE – LANCASTER AVENUE HOUSING (LAH)

INTRODUCTION

Villanova University proposes to re-develop the existing parking lot on the southerly side of Lancaster Avenue (U.S. Route 30) ("Main Lot") to provide for six (6) dormitory buildings and associated retail uses, while reducing the impervious coverage.

The proposed plan for re-development of the "Main Lot" includes six proposed dormitory buildings that will accommodate on-campus housing as well as associated retail uses, at grade parking comprising 62 parking spaces, pedestrian pathways throughout the re-developed area that will ultimately provide a pedestrian link to the remaining areas of the campus, and a comprehensive storm water management system.

EXISTING CONDITIONS

The "Main Lot" is located on the southwesterly corner of Lancaster Avenue (Route 30) and Ithan Avenue, this site is almost entirely paved with at-grade parking. The property in question is Zoned 'Pi' – Planned Institutional. The entire parking lot currently drains overland to a drainage swale adjacent to the SEPTA Route 100 Line that discharges to the storm drainage system in Ithan Avenue. The site is located in the Darby Creek watershed (PA Chapter 93 Designation is "CWF, MF" – Coldwater Fish, Migratory Fish). Soils for this area of the campus are mapped as "Me" – Made Land Schist and Gneiss Materials and the hydrologic soils group is "B".

The following soils are mapped in the Re-Development Areas per the NRCS Web Soil Survey:

Me Made Land, Schist and Gneiss Materials HSG 'B'

STORM WATER MANAGEMENT CRITERIA

Storm water Management Design shall meet the following criteria:

Peak Rate Control – The Villanova University Re-Development is subject to the provisions of the Darby – Cobbs Creek Watershed criteria and Radnor Township Storm Water Management Ordinance (Chapter 245 of the Township's Municipal Code). The site in question is located in the Release Rate District designated B-2 and are subject to the following release rate criteria:

Predevelopment	Reduce to	Post-Development
2 year		1 year
5 year		2 year
10 year		5 year
25 year		5 year
50 year		10 year
100 year		100 year

The following values will be utilized for the 24 hour rainfall depths in accordance with Table F-1 from Ordinance Appendix 'F':

Year	24 Hour Rainfall Depth (in)
1	2.64
2	3.36
5	4.32
10	5.28
25	6.24
50	7.20
100	8.40

The ground cover condition for a Redevelopment Site for the Pre-Development Condition shall be based on actual land cover conditions, except that for NPDES Permitting 20% of existing impervious must be considered meadow for volume control calculations.

Storm Drainage Conveyance System – Storm Drains are designed in accordance with the Ordinance such that the pipes have adequate capacity to convey the 25 year storm. In addition, the storm drainage system is designed to accommodate the 100 year storm such that there would be no surcharging of storm inlets (this is done to insure all storm water is directed to the intended storm water management facilities). Storm drain design calculations are based on the Rational Method and on the PennDOT Region 5 IDF Curves per Figure 'F-4' of Ordinance Appendix 'F'.

Groundwater Recharge – The total volume of runoff retained corresponds with the approach designated the "One inch from Impervious Surface" per the Radnor Township Code. Since this project will be subject to a General NPDES Permit, calculations for estimating the required net 2 year volume will be prepared based on the NPDES Permit requirements and the Pennsylvania Best Management Practices Manual (2006) (PA BMP Manual) utilizing the Standard Worksheets – particularly Worksheet No. 4.

Calculations to estimate the net two year volume of runoff to be infiltrated from pre-development to post-development condition will be based on the criteria in the PA BMP Manual, Section 3.3.3 – Volume Control Guideline 1 (CG-1):

- a. Do not increase the post-development total runoff volume for all storms equal to or less than the 2 year / 24 hour event.
- b. Existing (pre-development) non-forested pervious areas must be considered meadow (good condition) or its equivalent.
- c. Twenty (20) percent of existing impervious area, when present, shall be considered meadow (good condition) in the model for existing conditions for re-development (This is more conservative than the Township requirement).

In addition to the Net Two Year Volume of Runoff, the targeted Recharge Volume (Rev) will be evaluated utilizing the criteria of Section 245-22 of the Radnor Township Storm Water Management Ordinance as follows:

$Rev = I * Impervious\ Area\ (Square\ Feet) / 12\ inches = Rev\ in\ Cubic\ Feet$ (This value will be calculated for 1.0 inch of runoff for comparison to the NPDES required volume per CG-1).

In this case, there is a decrease in the impervious coverage from pre-development to post-development condition and as such, there will be no requirement to manage runoff volume

based on the NPDES Worksheet 4. The design calculations are therefore configured to show that the project will voluntarily comply with the Radnor Township Storm water Management Ordinance Section 245-22 indicating storm water Best Management Practices shall treat the one inch (1 inch) runoff event.

Water Quality Requirements

This project is required to meet the criteria of Section 245-23 of the Radnor Township Stormwater Management Ordinance. The required Water Quality Volume (WQv) will be calculated as follows:

$$WQv = [(P)(Rv)(A)] / 12$$

Where

WQv – Water Quality Volume (acre feet)

P = 1 inch

Rv = $0.05 + 0.009 * I$ where I = Percent Impervious Surface Area

A = Area of project contributing to water quality BMP in acres

Infiltration Testing

Infiltration testing was conducted in the area of the proposed infiltration BMP's in September 2014. Test logs indicate fill material to a depth ranging from 1.5 feet to 7 feet. Due to the presences of fill and variable infiltration rates (some outside the acceptable range), the proposed infiltration systems interface is set at depths greater than 7 feet in order to be located within native soil. Per the geotechnical engineer, the native soil is expected to provide favorable infiltration rates. It should be noted that for the purpose of this study, no infiltration rate has been applied to the peak rate routing calculations.

Proposed Green Infrastructure/BMP's - Best Management Practices (POI 2A)

The Lancaster Avenue Housing Development is designed to meet the Peak Rate, Groundwater Recharge, and Water Quality Requirements of the Radnor Township Code (Chapter 245 Storm water Management Ordinance) as follows:


1. Ten rain gardens will be spaced around the site that will cumulatively treat approximately 1.25 inches of runoff.
2. Three subsurface combination detention/infiltration beds are proposed near the southeast corner of the "Main Lot" that will treat approximately 2.40 inches of runoff from the contributing area in addition to contributing to meeting the peak rate release requirements.
3. Two underground cisterns are proposed that will retain approximately 1.86 inches of runoff from a majority of roof areas of the proposed dormitory buildings. All of this collected runoff will be conveyed to the proposed cooling tower system to service heating / cooling needs of the proposed buildings.
4. One additional underground detention system will contribute to meeting the peak rate release requirements.


The average runoff treated by BMP's is 1.7 inches.

PADOT Lancaster Avenue (Route 30) (POI 2B)

Lancaster Avenue is proposed to be widened to accommodate a left turn lane onto North Ithan Avenue and a left turn lane from Lancaster Avenue onto Church Walk. The proposed additional impervious area generated by the widening is 3000 square feet. Existing run-off from Lancaster Avenue is collected via an existing inlet and pipe network that bypass the main lot and outfalls south of the Septa Route 100 rail line into the existing stream channel through the Aldwyn triangle. In order to mitigate the additional runoff from the widening, a city inlet is proposed to accept runoff from an equivalent 3000 square foot area which will drain to the onsite BMP's within POI 2A. Drainage Area 2B is proposed to maintain an equivalent square footage of impervious between pre and post development.


||.



 <p>Where Ideas Get Down to Earth</p> <p>900 West Valley Road • Suite 1100 Wayne, PA 19087-1830 p: 610.265.8323 f: 610.265.4299 www.navenewell.com</p>	DRAWING NAME: USGS MAP - "NORRISTOWN" QUADRANGLE		<h1>1 of 1</h1>
	PROJECT NAME: VILLANOVA UNIVERSITY CICD DEVELOPMENT		
	SCALE: 1" = 2000'	DRAWN BY: MMB	
CHK'D BY: DAT	APPROV. BY: GCN	DATE: 11/26/14	

|||.

Hydrologic Soil Group—Delaware County, Pennsylvania



MAP LEGEND

Area of Interest (AOI)
 Area of Interest (AOI)

Soils
 Soil Map Units

Soil Ratings

- A
- A/D
- B
- B/D
- C
- C/D
- D

Not rated or not available

Political Features

Cities

Water Features

Streams and Canals

Transportation

- Rails
- Interstate Highways
- US Routes
- Major Roads
- Local Roads

MAP INFORMATION

Map Scale: 1:6,050 if printed on A size (8.5" x 11") sheet.
 The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.
 Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for accurate map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL: <http://websoilsurvey.nrcs.usda.gov>
 Coordinate System: UTM Zone 18N NAD83

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Delaware County, Pennsylvania
 Survey Area Data: Version 6, Feb 24, 2009

Date(s) aerial images were photographed: Data not available.

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Hydrologic Soil Group

Hydrologic Soil Group-- Summary by Map Unit -- Delaware County, Pennsylvania (PA045)				
Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
GeB2	Glennville channery silt loam, 3 to 8 percent slopes, moderately eroded	B	1.0	1.5%
GnB2	Glennville silt loam, 3 to 8 percent slopes, moderately eroded	C	26.2	40.5%
Me	Made land, schist and gneiss materials	B	37.5	57.9%
UnB	Urban land-Gladstone complex, 0 to 8 percent slopes		0.1	0.2%
Totals for Area of Interest			64.8	100.0%

Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

Rating Options

Aggregation Method: Dominant Condition
Component Percent Cutoff: None Specified
Tie-break Rule: Higher

IV.

TABLE F-1

DESIGN STORM RAINFALL AMOUNT (INCHES)

The design storm rainfall amount chosen for design should be obtained from the PennDOT region in which the site is located according to Figure F-2.

Duration	Region 5						
	Precipitation Depth (in)						
	1 Yr	2 Yr	5 Yr	10 Yr	25 Yr	50 Yr	100 Yr
5 min	0.33	0.38	0.45	0.50	0.56	0.63	0.68
15 min	0.64	0.75	0.90	1.00	1.15	1.35	1.50
1 hr	1.10	1.35	1.61	1.85	2.15	2.60	2.98
2 hrs	1.34	1.66	2.00	2.34	2.70	3.26	3.76
3 hrs	1.50	1.86	2.28	2.67	3.09	3.69	4.29
6 hrs	1.86	2.28	2.82	3.36	3.90	4.62	5.40
12 hrs	2.28	2.76	3.48	4.20	4.92	5.76	6.72
24 hrs	2.64	3.36	4.32	5.28	6.24	7.20	8.40

Source: "Field Manual of Pennsylvania Department of Transportation," Storm Intensity-Duration-Frequency Charts, PDT- IDF, May 1986.

TABLE F-2
RUNOFF CURVE NUMBERS

LAND USE DESCRIPTION	Hydrologic Condition	HYDROLOGIC SOIL GROUP			
		A	B	C	D
Open Space					
Grass cover < 50%	Poor	68	79	86	89
Grass cover 50% to 75%	Fair	49	69	79	84
Grass cover > 75%	Good	39	61	74	80
Meadow		30	58	71	78
Agricultural					
Pasture, grassland, or range – Continuous forage for grazing	Poor	68	79	86	89
Pasture, grassland, or range – Continuous forage for grazing	Fair	49	69	79	84
Pasture, grassland, or range – Continuous forage for grazing	Good	39	61	74	80
Brush—brush-weed-grass mixture with brush the major element	Poor	48	67	77	83
Brush—brush-weed-grass mixture with brush the major element	Fair	35	56	70	77
Brush—brush-weed-grass mixture with brush the major element	Good	30	48	65	73
Fallow Bare soil	-----	77	86	91	94
Crop residue cover (CR)	Poor	76	85	90	93
	Good	74	83	88	90
Woods – grass combination (orchard or tree farm)	Poor	57	73	82	86
	Fair	43	65	76	82
	Good	32	58	72	79
Woods	Poor	45	66	77	83
	Fair	36	60	73	79
	Good	30	55	70	77

F-7

Commercial	(85% impervious)	89	92	94	95
Industrial	(72% impervious)	81	88	91	93
Institutional	(50% impervious)	71	82	88	90

Residential districts by average lot size:

	% Impervious				
1/8 acre or less * (townhouses)	65	77	85	90	92
1/4 acre	38	61	75	83	87
1/3 acre	30	57	72	81	86
1/2 acre	25	54	70	80	85
1 acre	20	51	68	79	84
2 acres	12	46	65	77	82
Farmstead		59	74	82	86
Smooth surfaces (concrete, asphalt, gravel, or bare compacted soil)		98	98	98	98
Water		98	98	98	98
Mining/newly graded areas (pervious areas only)		77	86	91	94

* Includes multi-family housing unless justified lower density can be provided.

Note: Existing site conditions of bare earth or fallow ground shall be considered as meadow when choosing a CN value.

Source: NRCS (SCS) TR-55


TABLE F-3

RATIONAL RUNOFF COEFFICIENTS

LAND USE DESCRIPTION	HYDROLOGIC SOIL GROUP			
	A	B	C	D
Cultivated land : without conservation treatment	.49	.67	.81	.88
: with conservation treatment	.27	.43	.61	.67
Pasture or range land: poor condition	.38	.63	.78	.84
: good condition	---*	.25	.51	.65
Meadow: good condition	---*	---*	.44	.61
Woods: thin stand, poor cover, no mulch	---*	.34	.59	.70
: good cover	---*	---*	.45	.59
Open spaces, lawns, parks, golf courses, cemeteries				
Good condition: grass cover on 75% or more of the area	---*	.25	.51	.65
Fair condition: grass cover on 50% to 75% of the area	---*	.45	.63	.74
Commercial and business areas (85% impervious)	.84	.90	.93	.96
Industrial districts (72% impervious)	.67	.81	.88	.92
Residential:				
Average lot size Average % impervious				
1/8 acre or less 65	.59	.76	.86	.90
1/4 acre 38	.25	.49	.67	.78
1/3 acre 30	---*	.49	.67	.78
1/2 acre 25	---*	.45	.65	.76
1 acre 20	---*	.41	.63	.74
Paved parking lots, roofs, driveways, etc.	.99	.99	.99	.99
Streets and roads:				
Paved with curbs and storm sewers	.99	.99	.99	.99
Gravel	.57	.76	.84	.88
Dirt	.49	.69	.80	.84

FIGURE F-4

PENNDOT REGION 5 STORM INTENSITY-DURATION-FREQUENCY CURVE



Source: "Field Manual of Pennsylvania Department of Transportation,"
Storm Intensity-Duration-Frequency Charts, PDT- IDF, May 1986.

EROSION AND SEDIMENT CONTROL; STORMWATER MANAGEMENT

TABLE F-4

MANNING'S ROUGHNESS COEFFICIENTS

Roughness Coefficients (Manning's "n") for Overland Flow

Surface Description	n
Dense growth	0.4 to 0.5
Pasture	0.3 to 0.4
Lawns	0.2 to 0.3
Bluegrass sod	0.2 to 0.5
Short grass prairie	0.1 to 0.2
Sparse vegetation	0.05 to 0.13
Bare clay-loam soil (eroded)	0.01 to 0.03
Concrete/asphalt:	
very shallow depths (less than 1/4 inch)	0.10 to 0.15
small depths (1/4 inch to several inches)	0.05 to 0.10

Roughness Coefficients (Manning's "n") for Channel Flow

Reach Description	n
Natural stream, clean, straight, no rifts or pools	0.03
Natural stream, clean, winding, some pools or shoals	0.04
Natural stream, winding, pools, shoals, stony with some weeds	0.05
Natural stream, sluggish deep pools and weeds	0.07
Natural stream or swale, very weedy or with timber underbrush	0.10
Concrete pipe, culvert, or channel	0.012
Corrugated metal pipe	0.012-0.027 ⁽¹⁾
High density polyethylene (HDPE) pipe	
Corrugated	0.021-0.029 ⁽²⁾
Smooth lined	0.012-0.020 ⁽²⁾

⁽¹⁾ Depending upon type, coating, and diameter

⁽²⁾ Values recommended by the American Concrete Pipe Association, check manufacturer's recommended value./

Source: U.S. Army Corps of Engineers, HEC-1 Users Manual

V.

Volume Calculations for Section 245-22 and 245-23 of the Radnor Township Storm Water Management Ordinance

POI No. 2A – Main Lot – Lancaster Avenue Housing (LAH)

1. Calculation of Net Two Year Runoff Volume – Calculated utilizing Worksheet 4 from the PaDEP's BMP Manual = -4960 CF (decreased impervious area results in a volume credit).

2. Calculation of the Retention (Infiltration) Volume based on a Runoff Depth of 1.0 inch for all Impervious Surfaces:

$$Rev = I \times \text{Impervious Area (S.F.)} / 12 \text{ inches} = \text{Volume (CF)}$$

$$\text{Impervious Area} = 212,810 \text{ SF}$$

$$I = 1.0 \text{ inches}$$

$$Rev = \mathbf{17,727 \text{ CF}}$$
 (Greater of Rev and WQV)

3. Water Quality Volume per Section 245-23 :

$$WQv = [(P)(Rv)(A)]/12$$

$$P = 1.0 \text{ Inch}$$

$$Rv = 0.05 + 0.009(I) \text{ where } I = \% \text{ Impervious Coverage}$$

$$A = \text{Project Area} = 412,470 \text{ SF or } 9.469 \text{ Acres}$$

$$\text{Impervious Surface Area} = 212,810 \text{ SF or } 51.6\% \text{ Impervious Coverage}$$

$$Rv = 0.05 + 0.009(51.6) = 0.5144$$

$$WQv = [(1.0)(0.5144)(9.469)]/12 = 0.406 \text{ Acre Feet or } \mathbf{17,681 \text{ CF}}$$

4. Water Quality Volume Treated

Rain Gardens 1 through 10	6,950 CF
Infiltration Systems 1 through 3	11,761 CF
<u>Subtotal Volume Treated</u>	<u>18,711 CF > 17,727 CF</u>

Cisterns 1 and 2 11,539 CF

Total Volume treated 30,250 CF

Equivalent Runoff Depth treated: $30,250/17,727 = 1.71 \text{ inches}$

Villanova University – CICD Development

Volume Summary

Rain Garden No. 1 (RG-1)

Impervious Surface Area	=	9247	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	771	CF
Storage Volume	=	687	CF
Equivalent Runoff Depth Treated	=	0.89	in.*

Rain Garden No. 2 (RG-2)

Impervious Surface Area	=	3307	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	276	CF
Storage Volume	=	285	CF
Equivalent Runoff Depth Treated	=	1.03	in.

Rain Garden No. 3 (RG-3)

Impervious Surface Area	=	8867	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	739	CF
Storage Volume	=	856	CF
Equivalent Runoff Depth Treated	=	1.16	in.

Rain Garden No. 4 (RG-4)

Impervious Surface Area	=	5065	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	422	CF
Storage Volume	=	487	CF
Equivalent Runoff Depth Treated	=	1.15	in.

Rain Garden No. 5 (RG-5)

Impervious Surface Area	=	7319	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	610	CF
Storage Volume	=	696	CF
Equivalent Runoff Depth Treated	=	1.14	in.

Rain Garden No. 6 (RG-6)

Impervious Surface Area	=	6626	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	552	CF
Storage Volume	=	558	CF
Equivalent Runoff Depth Treated	=	1.01	in.

Rain Garden No. 7 (RG-7)

Impervious Surface Area	=	5047	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	421	CF
Storage Volume	=	760	CF
Equivalent Runoff Depth Treated	=	1.81	in.

Rain Garden No. 8 (RG-8)

Impervious Surface Area	=	7183	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	599	CF
Storage Volume	=	950	CF
Equivalent Runoff Depth Treated	=	1.59	in.

Rain Garden No. 9 (RG-9)

Impervious Surface Area	=	4385	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	365	CF
Storage Volume	=	813	CF
Equivalent Runoff Depth Treated	=	2.22	in.

Rain Garden No. 10 (RG-10)

Impervious Surface Area	=	9215	SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	768	CF
Storage Volume	=	858	CF
Equivalent Runoff Depth Treated	=	1.12	in.

Cistern No. 1

Impervious Surface Area	=	55818 SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	4652 CF
Storage Volume	=	10336 CF
Equivalent Runoff Depth Treated	=	2.22 in.

Cistern No. 2

Impervious Surface Area	=	8839 SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	737 CF
Storage Volume	=	1203 CF
Equivalent Runoff Depth Treated	=	1.63 in.

Infiltration System No. 1

Impervious Surface Area	=	42610 SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	3551 CF
Storage Volume	=	6361 CF
Equivalent Runoff Depth Treated	=	1.79 in.

Infiltration System No. 2

Impervious Surface Area	=	25785 SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	2149 CF
Storage Volume	=	4446 CF
Equivalent Runoff Depth Treated	=	2.07 in.

Infiltration System No. 3

Impervious Surface Area	=	7411 SF
Runoff Volume - Impervious Surface Area (1.0 inch runoff)	=	618 CF
Storage Volume	=	954 CF
Equivalent Runoff Depth Treated	=	1.54 in.

*RG-1 outfall is contributing to Infiltration System No. 1 which accommodates the remaining 0.1" of runoff

Cooling Tower Seasonal Demand and Cistern Capacities

Cistern 1 & 2				
Storage =		11073 cubic feet	82837 gallons*	
Cooling Tower Usage	Season	Demand gal/min.**	Demand gal/day***	Duration (cooling tower supply) days
	Summer	72	103,680	0.80
	Winter	10	14,400	5.75
<p>* 7.481 x cubic feet = gallons ** Seasonal demand provided by MEP Engineer *** gal/day = gal/minute * 1440 minutes/day</p>				

WORKSHEET 4. CHANGE IN RUNOFF VOLUME FOR 2-YR STORM EVENT

PROJECT: Villanova University - Lancaster Ave. Housing
 Drainage Area: POI 2A
 2-Year Rainfall: 3.36 inches

Total Site Area: 9.469 acres
 Protected Site Area: 0.000 acres
 Managed Area: 9.469 acres

Existing Conditions:

Cover Type/Condition	Soil Type	Area (sf)	Area (ac)	CN	S	I _a (0.2 x S)	Q Runoff ¹ (in)	Runoff Volume ² (ft ³)
Woodland	B		0.000	55	8.18	1.64	0.30	0
Woodland	C		0.000	70	4.29	0.86	0.92	0
Woodland	D		0.000	77	2.99	0.60	1.33	0
Meadow	B	87966	2.019	58	7.24	1.45	0.40	2927
Meadow	C		0.000	71	4.08	0.82	0.98	0
Meadow	D		0.000	78	2.82	0.56	1.39	0
Meadow (20% from Imperv.)	B	61408	1.410	58	7.24	1.45	0.40	2043
Meadow (20% from lthan.)	B	2996	0.069	58	7.24	1.45	0.40	100
Meadow (20% from Imperv.)	D		0.000	78	2.82	0.56	1.39	0
Impervious	B	245634	5.639	98	0.20	0.04	3.13	64007
Impervious (lthan Road)	C	11983	0.275	98	0.20	0.04	3.13	3122
Impervious	D		0.000	98	0.20	0.04	3.13	0
TOTAL:		409987	9.412					72199

Developed Conditions:

Cover Type/Condition	Soil Type	Area (sf)	Area (ac)	CN	S	I _a (0.2 x S)	Q Runoff ¹ (in)	Runoff Volume ² (ft ³)
Woodland	B		0.000	55	8.18	1.64	0.30	0
Woodland	C		0.000	70	4.29	0.86	0.92	0
Woodland	D		0.000	77	2.99	0.60	1.33	0
Meadow	B		0.000	58	7.24	1.45	0.40	0
Meadow	C		0.000	71	4.08	0.82	0.98	0
Meadow	D		0.000	78	2.82	0.56	1.39	0
Lawn	B	185040	4.248	61	6.39	1.28	0.51	7882
Lawn	C		0.000	74	3.51	0.70	1.14	0
Lawn	D		0.000	80	2.50	0.50	1.53	0
Impervious	B	212810	4.885	98	0.20	0.04	3.13	55453
Impervious (lthan Road)	B	14979	0.344	98	0.20	0.04	3.13	3903
Impervious	D		0.000	98	0.20	0.04	3.13	0
TOTAL:		412829	9.477					67238

2-Year Volume Increase (ft³)	-4960 ft³
--	-----------------------------

2-Year Volume Increase = Developed Conditions Runoff Volume - Existing Conditions Runoff Volume

1. Runoff (in) = $Q = (P - 0.2S)^2 / (P + 0.8S) = (P - I_a)^2 / ((P - I_a) + S)$

P = 2-Year Rainfall (in)

S = $(1000 / CN) - 10$

2. Runoff Volume (CF) = $Q \times \text{Area} \times 1/12$

Q = Runoff (in)

Area = Land use area (sq. ft)

Note: Runoff Volume must be calculated for EACH land use type/condition and HSGI. The use of a weighted CN value for volume calculations is not acceptable.

VI.

POI 2A SUMMARY OF FLOWS
Pre-Development/Post Development

STORM	Pre-Development (CFS)	Allowable Flow (CFS)	Post Development Flow (CFS)	% of Allowable (CFS)
1	22.70		8.29	36.52
2	31.67	22.70	11.68	51.45
5	43.69	31.67	16.44	51.91
10	55.70	43.69	21.99	50.33
25	67.65	43.69	30.23	69.19
50	79.53	55.70	39.99	71.80
100	94.31	94.31	51.21	54.30

No Detention Credit taken for Volume detained in Cisterns, Infiltration Systems, and Rain Gardens



900 West Valley Road
 Suite 1100
 Wayne, PA 19087

PROJECT:

Villanova



JOB NO. 2011-005.00

BY: LRL


DATE: 12/5/2014

CHK'D: DAT


VII.



Routing Diagram for LAH SWM Report
 Prepared by Nave Newell Inc., Printed 12/4/2014
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC



PRE - MAIN LOT



POI -2A PRE



Routing Diagram for LAH SWM Report_No Cistern Credit
Prepared by Nave Newell Inc., Printed 12/4/2014
HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Events for Link 24L: POI -2A PRE

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)
1-yr	22.70	22.70	0.00
2-yr	31.67	31.67	0.00
5-yr	43.69	43.69	0.00
10-yr	55.70	55.70	0.00
25-yr	67.65	67.65	0.00
50-yr	79.53	79.53	0.00
100-yr	94.31	94.31	0.00

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT

Runoff = 22.70 cfs @ 12.01 hrs, Volume= 53,775 cf, Depth> 1.57"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 1-yr Rainfall=2.64"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 2-yr Rainfall=3.36"
 Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT

Runoff = 31.67 cfs @ 12.01 hrs, Volume= 75,951 cf, Depth> 2.22"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 2-yr Rainfall=3.36"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT

Runoff = 43.69 cfs @ 12.01 hrs, Volume= 106,523 cf, Depth> 3.12"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT

Runoff = 55.70 cfs @ 12.01 hrs, Volume= 137,761 cf, Depth> 4.03"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT


Runoff = 67.65 cfs @ 12.01 hrs, Volume= 169,399 cf, Depth> 4.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT

Runoff = 79.53 cfs @ 12.01 hrs, Volume= 201,296 cf, Depth> 5.89"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 11S: PRE - MAIN LOT


Runoff = 94.31 cfs @ 12.01 hrs, Volume= 241,411 cf, Depth> 7.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (sf)	CN	Description
87,966	58	Meadow, non-grazed, HSG B
322,021	98	Paved parking, HSG B
409,987	89	Weighted Average
87,966		21.46% Pervious Area
322,021		78.54% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 11S: PRE - MAIN LOT



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 1.57" for 1-yr event
Inflow = 22.70 cfs @ 12.01 hrs, Volume= 53,775 cf
Primary = 22.70 cfs @ 12.01 hrs, Volume= 53,775 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 2.22" for 2-yr event
Inflow = 31.67 cfs @ 12.01 hrs, Volume= 75,951 cf
Primary = 31.67 cfs @ 12.01 hrs, Volume= 75,951 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 3.12" for 5-yr event
Inflow = 43.69 cfs @ 12.01 hrs, Volume= 106,523 cf
Primary = 43.69 cfs @ 12.01 hrs, Volume= 106,523 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 4.03" for 10-yr event
Inflow = 55.70 cfs @ 12.01 hrs, Volume= 137,761 cf
Primary = 55.70 cfs @ 12.01 hrs, Volume= 137,761 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 4.96" for 25-yr event
Inflow = 67.65 cfs @ 12.01 hrs, Volume= 169,399 cf
Primary = 67.65 cfs @ 12.01 hrs, Volume= 169,399 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE

Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 5.89" for 50-yr event
Inflow = 79.53 cfs @ 12.01 hrs, Volume= 201,296 cf
Primary = 79.53 cfs @ 12.01 hrs, Volume= 201,296 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014


Summary for Link 24L: POI -2A PRE


Inflow Area = 409,987 sf, 78.54% Impervious, Inflow Depth > 7.07" for 100-yr event
Inflow = 94.31 cfs @ 12.01 hrs, Volume= 241,411 cf
Primary = 94.31 cfs @ 12.01 hrs, Volume= 241,411 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 24L: POI -2A PRE

Hydrograph





Routing Diagram for LAH SWM Report - NO CISTERN CREDIT - DIAGRAM ONLY
 Prepared by Nave Newell Inc., Printed 12/2/2014
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM Report_No Cistern Credit

Type II 24-hr 100-yr Rainfall=8.40"

Prepared by Nave Newell Inc.

Printed 12/4/2014

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Events for Link 15L: POI 2A - POST

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)
1-yr	8.29	8.29	0.00
2-yr	11.68	11.68	0.00
5-yr	16.44	16.44	0.00
10-yr	21.99	21.99	0.00
25-yr	30.23	30.23	0.00
50-yr	39.99	39.99	0.00
100-yr	51.21	51.21	0.00

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1

Runoff = 2.54 cfs @ 12.08 hrs, Volume= 7,084 cf, Depth> 1.29"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 2-yr Rainfall=3.36"
 Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1


Runoff = 3.72 cfs @ 12.07 hrs, Volume= 10,402 cf, Depth> 1.89"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1


Runoff = 5.36 cfs @ 12.07 hrs, Volume= 15,075 cf, Depth> 2.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1

Runoff = 7.01 cfs @ 12.07 hrs, Volume= 19,922 cf, Depth> 3.62"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 25-yr Rainfall=6.24"
 Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1


Runoff = 8.68 cfs @ 12.07 hrs, Volume= 24,876 cf, Depth> 4.51"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1


Runoff = 10.34 cfs @ 12.07 hrs, Volume= 29,903 cf, Depth> 5.43"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 20S: INFIL-1

Runoff = 12.40 cfs @ 12.06 hrs, Volume= 36,254 cf, Depth> 6.58"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
0.619	98	Paved parking, HSG B
0.268	61	>75% Grass cover, Good, HSG B
* 0.359	98	Roof (Rear Courtyard)
* 0.272	61	Lawn (Rear Courtyard)
1.518	85	Weighted Average
0.540		35.57% Pervious Area
0.978		64.43% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.0					Direct Entry,

Subcatchment 20S: INFIL-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens

Runoff = 0.71 cfs @ 12.41 hrs, Volume= 3,992 cf, Depth> 0.68"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens

Runoff = 1.27 cfs @ 12.37 hrs, Volume= 6,646 cf, Depth> 1.13"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens

Runoff = 2.12 cfs @ 12.34 hrs, Volume= 10,671 cf, Depth> 1.81"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens

Runoff = 3.05 cfs @ 12.34 hrs, Volume= 15,072 cf, Depth> 2.56"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens


Runoff = 4.03 cfs @ 12.33 hrs, Volume= 19,729 cf, Depth> 3.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens

Runoff = 5.03 cfs @ 12.33 hrs, Volume= 24,569 cf, Depth> 4.18"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 17S: From Rain Gardens


Runoff = 6.31 cfs @ 12.33 hrs, Volume= 30,805 cf, Depth> 5.24"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
0.945	61	>75% Grass cover, Good, HSG B
* 0.585	98	Sidewalks/roofs
0.091	61	>75% Grass cover, Good, HSG B
1.621	74	Weighted Average
1.036		63.91% Pervious Area
0.585		36.09% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
37.2	100	0.0050	0.04		Sheet Flow, Sheet flow - courtyard Grass: Bermuda n= 0.410 P2= 3.36"
0.6	60	0.0100	1.61		Shallow Concentrated Flow, overland Unpaved Kv= 16.1 fps
0.6	310	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011 PVC, smooth interior
38.4	470	Total			

Subcatchment 17S: From Rain Gardens



LAH SWM Report - NO CISTERN CREDIT

Type II 24-hr 100-yr Rainfall=8.40"

Prepared by Nave Newell Inc.

Printed 12/2/2014

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Events for Pond 19P: Infiltration-1

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	2.79	0.34	424.31	7,843
2-yr	4.25	1.18	424.71	9,780
5-yr	6.33	2.97	425.09	11,489
10-yr	8.48	4.95	425.47	12,963
25-yr	10.67	6.90	426.02	14,505
50-yr	12.89	10.59	426.31	15,248
100-yr	15.67	12.24	426.80	16,490

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 0.97" for 1-yr event
 Inflow = 2.79 cfs @ 12.08 hrs, Volume= 11,076 cf
 Outflow = 0.34 cfs @ 13.39 hrs, Volume= 8,941 cf, Atten= 88%, Lag= 78.1 min
 Primary = 0.34 cfs @ 13.39 hrs, Volume= 8,941 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 424.31' @ 13.39 hrs Surf.Area= 6,399 sf Storage= 7,843 cf (5,284 cf above start)

Plug-Flow detention time= 349.5 min calculated for 6,381 cf (58% of inflow)
 Center-of-Mass det. time= 143.5 min (1,001.4 - 857.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 '/ Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.34 cfs @ 13.39 hrs HW=424.31' (Free Discharge)

- ↑ 1=Culvert (Passes 0.34 cfs of 1.98 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.34 cfs @ 3.85 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.00 cfs @ 0.24 fps)

Pond 19P: Infiltration-1 - Chamber Wizard Field A

Chamber Model = ADS_StormTechSC-740 (ADSStormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 10 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

18 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 128.60' Row Length +12.0" End Stone x 2 = 130.60' Base Length

10 Rows x 51.0" Wide + 6.0" Spacing x 9 + 12.0" Side Stone x 2 = 49.00' Base Width

12.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.50' Field Height

180 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 10 Rows = 8,297.6 cf Chamber Storage

28,797.3 cf Field - 8,297.6 cf Chambers = 20,499.7 cf Stone x 40.0% Voids = 8,199.9 cf Stone Storage


Chamber Storage + Stone Storage = 16,497.5 cf = 0.379 af

Overall Storage Efficiency = 57.3%

180 Chambers

1,066.6 cy Field

759.2 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 1.50" for 2-yr event
 Inflow = 4.25 cfs @ 12.08 hrs, Volume= 17,047 cf
 Outflow = 1.18 cfs @ 12.70 hrs, Volume= 14,613 cf, Atten= 72%, Lag= 37.1 min
 Primary = 1.18 cfs @ 12.70 hrs, Volume= 14,613 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 424.71' @ 12.70 hrs Surf.Area= 6,399 sf Storage= 9,780 cf (7,220 cf above start)

Plug-Flow detention time= 267.3 min calculated for 12,053 cf (71% of inflow)
 Center-of-Mass det. time= 119.6 min (966.4 - 846.8)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 ' /' Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.18 cfs @ 12.70 hrs HW=424.71' (Free Discharge)

- ↑ 1=Culvert (Passes 1.18 cfs of 3.79 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.43 cfs @ 4.91 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.75 cfs @ 2.17 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 2.26" for 5-yr event
 Inflow = 6.33 cfs @ 12.08 hrs, Volume= 25,746 cf
 Outflow = 2.97 cfs @ 12.46 hrs, Volume= 22,821 cf, Atten= 53%, Lag= 22.9 min
 Primary = 2.97 cfs @ 12.46 hrs, Volume= 22,821 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 425.09' @ 12.46 hrs Surf.Area= 6,399 sf Storage= 11,489 cf (8,929 cf above start)

Plug-Flow detention time= 196.5 min calculated for 20,261 cf (79% of inflow)
 Center-of-Mass det. time= 88.0 min (924.3 - 836.3)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 '/ Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=2.97 cfs @ 12.46 hrs HW=425.09' (Free Discharge)

- ↑ 1=Culvert (Passes 2.97 cfs of 5.88 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.50 cfs @ 5.74 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 2.47 cfs @ 3.02 fps)

LAH SWM Report

Prepared by Nave Newell Inc.


HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 3.07" for 10-yr event
 Inflow = 8.48 cfs @ 12.08 hrs, Volume= 34,994 cf
 Outflow = 4.95 cfs @ 12.35 hrs, Volume= 31,511 cf, Atten= 42%, Lag= 15.8 min
 Primary = 4.95 cfs @ 12.35 hrs, Volume= 31,511 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 425.47' @ 12.35 hrs Surf.Area= 6,399 sf Storage= 12,963 cf (10,404 cf above start)

Plug-Flow detention time= 157.5 min calculated for 28,951 cf (83% of inflow)
 Center-of-Mass det. time= 68.5 min (897.1 - 828.5)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 '/ Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=4.95 cfs @ 12.35 hrs HW=425.47' (Free Discharge)

- ↑ 1=Culvert (Passes 4.95 cfs of 8.09 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.56 cfs @ 6.46 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 4.39 cfs @ 3.68 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 3.91" for 25-yr event
 Inflow = 10.67 cfs @ 12.08 hrs, Volume= 44,606 cf
 Outflow = 6.90 cfs @ 12.29 hrs, Volume= 40,575 cf, Atten= 35%, Lag= 12.6 min
 Primary = 6.90 cfs @ 12.29 hrs, Volume= 40,575 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 426.02' @ 12.29 hrs Surf.Area= 6,399 sf Storage= 14,505 cf (11,945 cf above start)

Plug-Flow detention time= 133.2 min calculated for 37,999 cf (85% of inflow)
 Center-of-Mass det. time= 56.0 min (878.3 - 822.3)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 ' /' Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=6.88 cfs @ 12.29 hrs HW=426.02' (Free Discharge)

- ↑ **1=Culvert** (Passes 6.88 cfs of 11.02 cfs potential flow)
- ↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 0.05 cfs @ 0.48 fps)
- ↑ **3=Orifice/Grate** (Orifice Controls 0.64 cfs @ 7.39 fps)
- ↑ **4=Orifice/Grate** (Orifice Controls 6.19 cfs @ 5.04 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 50-yr Rainfall=7.20"
 Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 4.78" for 50-yr event
 Inflow = 12.89 cfs @ 12.08 hrs, Volume= 54,472 cf
 Outflow = 10.59 cfs @ 12.19 hrs, Volume= 49,943 cf, Atten= 18%, Lag= 6.4 min
 Primary = 10.59 cfs @ 12.19 hrs, Volume= 49,943 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 426.31' @ 12.19 hrs Surf.Area= 6,399 sf Storage= 15,248 cf (12,688 cf above start)

Plug-Flow detention time= 116.5 min calculated for 47,383 cf (87% of inflow)
 Center-of-Mass det. time= 47.0 min (864.2 - 817.2)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 ' /' Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=10.58 cfs @ 12.19 hrs HW=426.31' (Free Discharge)

- 1=Culvert (Passes 10.58 cfs of 12.03 cfs potential flow)
- 2=Sharp-Crested Rectangular Weir (Weir Controls 2.94 cfs @ 1.91 fps)
- 3=Orifice/Grate (Orifice Controls 0.68 cfs @ 7.83 fps)
- 4=Orifice/Grate (Orifice Controls 6.96 cfs @ 5.67 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 19P: Infiltration-1

Inflow Area = 136,735 sf, 49.79% Impervious, Inflow Depth > 5.89" for 100-yr event
 Inflow = 15.67 cfs @ 12.08 hrs, Volume= 67,059 cf
 Outflow = 12.24 cfs @ 12.37 hrs, Volume= 62,002 cf, Atten= 22%, Lag= 17.2 min
 Primary = 12.24 cfs @ 12.37 hrs, Volume= 62,002 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 423.30' Surf.Area= 6,399 sf Storage= 2,560 cf
 Peak Elev= 426.80' @ 12.22 hrs Surf.Area= 6,399 sf Storage= 16,490 cf (13,930 cf above start)

Plug-Flow detention time= 102.1 min calculated for 59,417 cf (89% of inflow)
 Center-of-Mass det. time= 39.5 min (851.4 - 811.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	422.30'	8,200 cf	49.00'W x 130.60'L x 4.50'H Field A 28,797 cf Overall - 8,298 cf Embedded = 20,500 cf x 40.0% Voids
#2A	423.30'	8,298 cf	ADS_StormTech SC-740x 180 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 10 rows
		16,497 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	423.30'	30.0" Round Culvert L= 35.0' Ke= 0.500 Inlet / Outlet Invert= 423.30' / 422.00' S= 0.0371 ' /' Cc= 0.900 n= 0.110, Flow Area= 4.91 sf
#2	Device 1	426.00'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 0.8' Crest Height
#3	Device 1	423.50'	4.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	424.30'	15.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=12.25 cfs @ 12.37 hrs HW=426.48' (Free Discharge)

- ↑ 1=Culvert (Barrel Controls 12.25 cfs @ 2.54 fps)
- ↑ 2=Sharp-Crested Rectangular Weir (Passes < 5.74 cfs potential flow)
- ↑ 3=Orifice/Grate (Passes < 0.70 cfs potential flow)
- ↑ 4=Orifice/Grate (Passes < 7.37 cfs potential flow)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 19P: Infiltration-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 0.55 cfs @ 12.19 hrs, Volume= 2,096 cf, Depth> 0.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 2-yr Rainfall=3.36"
 Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 0.91 cfs @ 12.19 hrs, Volume= 3,357 cf, Depth> 1.32"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 5-yr Rainfall=4.32"
 Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 1.45 cfs @ 12.17 hrs, Volume= 5,228 cf, Depth> 2.05"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 2.02 cfs @ 12.17 hrs, Volume= 7,239 cf, Depth> 2.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS

Runoff = 2.61 cfs @ 12.17 hrs, Volume= 9,346 cf, Depth> 3.67"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 3.20 cfs @ 12.17 hrs, Volume= 11,518 cf, Depth> 4.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS


Runoff = 3.96 cfs @ 12.16 hrs, Volume= 14,299 cf, Depth> 5.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
* 0.312	98	Sidewalks/seating
0.390	61	>75% Grass cover, Good, HSG B
0.702	77	Weighted Average
0.390		55.56% Pervious Area
0.312		44.44% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.4	100	0.0200	0.08		Sheet Flow, sheet flow Grass: Bermuda n= 0.410 P2= 3.36"
1.2	120	0.0100	1.61		Shallow Concentrated Flow, overland grass to RG Unpaved Kv= 16.1 fps
1.1	560	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
23.7	780	Total			

Subcatchment 16S: ROUTE 30 BIOSWALE AND RAIN GARDENS



LAH SWM Report - NO CISTERN CREDIT

Type II 24-hr 100-yr Rainfall=8.40"

Prepared by Nave Newell Inc.

Printed 12/2/2014

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Events for Pond 28P: DETENTION-1

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	0.55	0.24	425.50	571
2-yr	0.91	0.30	425.69	1,030
5-yr	1.45	0.39	426.03	1,828
10-yr	2.02	0.47	426.42	2,722
25-yr	2.61	0.55	426.87	3,679
50-yr	3.20	0.63	427.38	4,680
100-yr	3.96	1.19	428.11	5,723

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 0.82" for 1-yr event
 Inflow = 0.55 cfs @ 12.19 hrs, Volume= 2,096 cf
 Outflow = 0.24 cfs @ 0.00 hrs, Volume= 2,586 cf, Atten= 56%, Lag= 0.0 min
 Primary = 0.24 cfs @ 0.00 hrs, Volume= 2,586 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 425.50' @ 0.00 hrs Surf.Area= 2,856 sf Storage= 571 cf

Plug-Flow detention time= (not calculated: outflow precedes inflow)
 Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 ' /' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.24 cfs @ 0.00 hrs HW=425.50' (Free Discharge)

- ↑ 1=Culvert (Passes 0.24 cfs of 1.24 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.24 cfs @ 2.78 fps)

Pond 28P: DETENTION-1 - Chamber Wizard Field A

Chamber Model = ADS_StormTechSC-740 (ADSStormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 13 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

6 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 43.16' Row Length +12.0" End Stone x 2 = 45.16' Base Length

13 Rows x 51.0" Wide + 6.0" Spacing x 12 + 12.0" Side Stone x 2 = 63.25' Base Width

6.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.00' Field Height

78 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 13 Rows = 3,620.1 cf Chamber Storage

11,425.1 cf Field - 3,620.1 cf Chambers = 7,805.0 cf Stone x 40.0% Voids = 3,122.0 cf Stone Storage



Chamber Storage + Stone Storage = 6,742.1 cf = 0.155 af

Overall Storage Efficiency = 59.0%

78 Chambers

423.2 cy Field

289.1 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 1.32" for 2-yr event
 Inflow = 0.91 cfs @ 12.19 hrs, Volume= 3,357 cf
 Outflow = 0.30 cfs @ 12.57 hrs, Volume= 3,830 cf, Atten= 67%, Lag= 23.1 min
 Primary = 0.30 cfs @ 12.57 hrs, Volume= 3,830 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 425.69' @ 12.57 hrs Surf.Area= 2,856 sf Storage= 1,030 cf (459 cf above start)

Plug-Flow detention time= 51.9 min calculated for 3,259 cf (97% of inflow)
 Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.30 cfs @ 12.57 hrs HW=425.69' (Free Discharge)

- 1=Culvert (Passes 0.30 cfs of 2.26 cfs potential flow)
- 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- 3=Orifice/Grate (Orifice Controls 0.30 cfs @ 3.49 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 2.05" for 5-yr event
 Inflow = 1.45 cfs @ 12.17 hrs, Volume= 5,228 cf
 Outflow = 0.39 cfs @ 12.63 hrs, Volume= 5,679 cf, Atten= 73%, Lag= 27.6 min
 Primary = 0.39 cfs @ 12.63 hrs, Volume= 5,679 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 426.03' @ 12.63 hrs Surf.Area= 2,856 sf Storage= 1,828 cf (1,257 cf above start)

Plug-Flow detention time= 58.7 min calculated for 5,108 cf (98% of inflow)
 Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.39 cfs @ 12.63 hrs HW=426.03' (Free Discharge)

- ↑ **1=Culvert** (Passes 0.39 cfs of 4.48 cfs potential flow)
- ↑ **2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
- ↑ **3=Orifice/Grate** (Orifice Controls 0.39 cfs @ 4.48 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 2.84" for 10-yr event
 Inflow = 2.02 cfs @ 12.17 hrs, Volume= 7,239 cf
 Outflow = 0.47 cfs @ 12.68 hrs, Volume= 7,672 cf, Atten= 77%, Lag= 30.4 min
 Primary = 0.47 cfs @ 12.68 hrs, Volume= 7,672 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 426.42' @ 12.68 hrs Surf.Area= 2,856 sf Storage= 2,722 cf (2,151 cf above start)

Plug-Flow detention time= 67.3 min calculated for 7,098 cf (98% of inflow)
 Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard


Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 ' /' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.47 cfs @ 12.68 hrs HW=426.42' (Free Discharge)

- ↑ 1=Culvert (Passes 0.47 cfs of 7.04 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.47 cfs @ 5.40 fps)

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 3.67" for 25-yr event
 Inflow = 2.61 cfs @ 12.17 hrs, Volume= 9,346 cf
 Outflow = 0.55 cfs @ 12.71 hrs, Volume= 9,762 cf, Atten= 79%, Lag= 32.5 min
 Primary = 0.55 cfs @ 12.71 hrs, Volume= 9,762 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 426.87' @ 12.71 hrs Surf.Area= 2,856 sf Storage= 3,679 cf (3,108 cf above start)

Plug-Flow detention time= 75.8 min calculated for 9,187 cf (98% of inflow)
 Center-of-Mass det. time= 16.8 min (846.3 - 829.5)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 1' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.55 cfs @ 12.71 hrs HW=426.87' (Free Discharge)

- ↑ 1=Culvert (Passes 0.55 cfs of 9.00 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.55 cfs @ 6.28 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 4.52" for 50-yr event
 Inflow = 3.20 cfs @ 12.17 hrs, Volume= 11,518 cf
 Outflow = 0.63 cfs @ 12.73 hrs, Volume= 11,918 cf, Atten= 80%, Lag= 34.0 min
 Primary = 0.63 cfs @ 12.73 hrs, Volume= 11,918 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 427.38' @ 12.73 hrs Surf.Area= 2,856 sf Storage= 4,681 cf (4,109 cf above start)

Plug-Flow detention time= 83.7 min calculated for 11,347 cf (99% of inflow)
 Center-of-Mass det. time= 34.3 min (858.0 - 823.7)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.63 cfs @ 12.73 hrs HW=427.38' (Free Discharge)

- ↑ 1=Culvert (Passes 0.63 cfs of 10.86 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.63 cfs @ 7.16 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 28P: DETENTION-1

Inflow Area = 30,579 sf, 44.44% Impervious, Inflow Depth > 5.61" for 100-yr event
 Inflow = 3.96 cfs @ 12.16 hrs, Volume= 14,299 cf
 Outflow = 1.19 cfs @ 12.56 hrs, Volume= 14,682 cf, Atten= 70%, Lag= 24.0 min
 Primary = 1.19 cfs @ 12.56 hrs, Volume= 14,682 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 425.50' Surf.Area= 2,856 sf Storage= 571 cf
 Peak Elev= 428.11' @ 12.56 hrs Surf.Area= 2,856 sf Storage= 5,723 cf (5,151 cf above start)

Plug-Flow detention time= 87.9 min calculated for 14,110 cf (99% of inflow)
 Center-of-Mass det. time= 47.1 min (864.8 - 817.6)

Volume	Invert	Avail.Storage	Storage Description
#1A	425.00'	3,122 cf	63.25'W x 45.16'L x 4.00'H Field A 11,425 cf Overall - 3,620 cf Embedded = 7,805 cf x 40.0% Voids
#2A	425.50'	3,620 cf	ADS_StormTech SC-740x 78 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 13 rows
		6,742 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	425.00'	18.0" Round Culvert L= 39.0' Ke= 0.500 Inlet / Outlet Invert= 425.00' / 424.30' S= 0.0179 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	428.00'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	425.00'	4.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.18 cfs @ 12.56 hrs HW=428.11' (Free Discharge)

1=Culvert (Passes 1.18 cfs of 13.06 cfs potential flow)

2=Sharp-Crested Rectangular Weir (Weir Controls 0.46 cfs @ 1.09 fps)

3=Orifice/Grate (Orifice Controls 0.72 cfs @ 8.26 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 28P: DETENTION-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 1-yr Rainfall=2.64"
 Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS


Runoff = 0.96 cfs @ 12.08 hrs, Volume= 2,869 cf, Depth> 0.73"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS

Runoff = 1.65 cfs @ 12.08 hrs, Volume= 4,709 cf, Depth> 1.20"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS


Runoff = 2.68 cfs @ 12.07 hrs, Volume= 7,477 cf, Depth> 1.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 10-yr Rainfall=5.28"
 Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS


Runoff = 3.78 cfs @ 12.07 hrs, Volume= 10,486 cf, Depth> 2.67"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS

Runoff = 4.92 cfs @ 12.07 hrs, Volume= 13,658 cf, Depth> 3.47"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS

Runoff = 6.08 cfs @ 12.07 hrs, Volume= 16,945 cf, Depth> 4.31"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 30S: FROM RAIN GARDENS

Runoff = 7.55 cfs @ 12.07 hrs, Volume= 21,170 cf, Depth> 5.38"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
* 0.289	98	sidewalks
0.664	61	>75% Grass cover, Good, HSG B
0.130	98	Paved parking, HSG B
1.083	75	Weighted Average
0.664		61.31% Pervious Area
0.419		38.69% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	100	0.0200	0.12		Sheet Flow, sheet flow Grass: Dense n= 0.240 P2= 3.36"
0.3	30	0.0100	1.61		Shallow Concentrated Flow, overland grass Unpaved Kv= 16.1 fps
0.7	360	0.0100	8.51	26.74	Pipe Channel, 24.0" Round Area= 3.1 sf Perim= 6.3' r= 0.50' n= 0.011
14.9	490	Total			

Subcatchment 30S: FROM RAIN GARDENS

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 0.49" for 1-yr event
Inflow = 1.03 cfs @ 12.10 hrs, Volume= 5,456 cf
Primary = 1.03 cfs @ 12.10 hrs, Volume= 5,456 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 0.98" for 2-yr event
Inflow = 1.82 cfs @ 12.09 hrs, Volume= 10,899 cf
Primary = 1.82 cfs @ 12.09 hrs, Volume= 10,899 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 1.79" for 5-yr event
Inflow = 2.93 cfs @ 12.07 hrs, Volume= 19,953 cf
Primary = 2.93 cfs @ 12.07 hrs, Volume= 19,953 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 2.64" for 10-yr event
Inflow = 9.09 cfs @ 12.10 hrs, Volume= 29,395 cf
Primary = 9.09 cfs @ 12.10 hrs, Volume= 29,395 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 3.51" for 25-yr event
Inflow = 14.03 cfs @ 12.06 hrs, Volume= 39,099 cf
Primary = 14.03 cfs @ 12.06 hrs, Volume= 39,099 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 4.40" for 50-yr event
Inflow = 17.36 cfs @ 12.05 hrs, Volume= 48,986 cf
Primary = 17.36 cfs @ 12.05 hrs, Volume= 48,986 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014


Summary for Link 27L: DMH

Inflow Area = 133,555 sf, 65.62% Impervious, Inflow Depth > 5.53" for 100-yr event
Inflow = 20.85 cfs @ 12.04 hrs, Volume= 61,530 cf
Primary = 20.85 cfs @ 12.04 hrs, Volume= 61,530 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 27L: DMH

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 1.93 cfs @ 12.01 hrs, Volume= 4,715 cf, Depth> 1.91"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 2.58 cfs @ 12.01 hrs, Volume= 6,413 cf, Depth> 2.59"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 3.45 cfs @ 12.01 hrs, Volume= 8,714 cf, Depth> 3.52"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 4.30 cfs @ 12.01 hrs, Volume= 11,036 cf, Depth> 4.46"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2


Runoff = 5.15 cfs @ 12.01 hrs, Volume= 13,372 cf, Depth> 5.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 6.00 cfs @ 12.01 hrs, Volume= 15,716 cf, Depth> 6.36"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 22S: INFIL-2

Runoff = 7.05 cfs @ 12.01 hrs, Volume= 18,654 cf, Depth> 7.55"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
0.592	98	Paved parking, HSG B
0.089	61	>75% Grass cover, Good, HSG B
0.681	93	Weighted Average
0.089		13.07% Pervious Area
0.592		86.93% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 22S: INFIL-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Events for Pond 21P: Infiltration-2

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	2.78	0.27	420.42	7,451
2-yr	4.16	0.80	420.72	8,707
5-yr	6.08	2.72	421.09	10,190
10-yr	11.98	9.17	421.56	11,883
25-yr	18.63	16.76	421.88	12,782
50-yr	23.06	20.20	422.28	13,668
100-yr	27.61	23.51	422.92	15,058

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 0.75" for 1-yr event
 Inflow = 2.78 cfs @ 12.03 hrs, Volume= 10,171 cf
 Outflow = 0.27 cfs @ 13.54 hrs, Volume= 8,086 cf, Atten= 90%, Lag= 90.3 min
 Primary = 0.27 cfs @ 13.54 hrs, Volume= 8,086 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 420.42' @ 13.54 hrs Surf.Area= 5,489 sf Storage= 7,451 cf (5,256 cf above start)

Plug-Flow detention time= 444.7 min calculated for 5,884 cf (58% of inflow)
 Center-of-Mass det. time= 214.7 min (1,013.6 - 798.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.27 cfs @ 13.54 hrs HW=420.42' (Free Discharge)

- ↑ 1=Culvert (Passes 0.27 cfs of 4.60 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Controls 0.00 cfs)
- ↑ 4=Orifice/Grate (Controls 0.00 cfs)
- ↑ 5=Orifice/Grate (Orifice Controls 0.27 cfs @ 4.29 fps)

LAH SWM Report

Prepared by Nave Newell Inc.


HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 21P: Infiltration-2



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 1.27" for 2-yr event
 Inflow = 4.16 cfs @ 12.03 hrs, Volume= 17,313 cf
 Outflow = 0.80 cfs @ 12.58 hrs, Volume= 13,820 cf, Atten= 81%, Lag= 32.8 min
 Primary = 0.80 cfs @ 12.58 hrs, Volume= 13,820 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 420.72' @ 12.58 hrs Surf.Area= 5,489 sf Storage= 8,707 cf (6,511 cf above start)

Plug-Flow detention time= 339.9 min calculated for 11,616 cf (67% of inflow)
 Center-of-Mass det. time= 153.7 min (1,003.0 - 849.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.79 cfs @ 12.58 hrs HW=420.72' (Free Discharge)

- ↑ 1=Culvert (Passes 0.79 cfs of 7.50 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Controls 0.00 cfs)
- ↑ 4=Orifice/Grate (Orifice Controls 0.48 cfs @ 1.49 fps)
- ↑ 5=Orifice/Grate (Orifice Controls 0.31 cfs @ 5.02 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 2.11" for 5-yr event
 Inflow = 6.08 cfs @ 12.03 hrs, Volume= 28,666 cf
 Outflow = 2.72 cfs @ 12.33 hrs, Volume= 24,354 cf, Atten= 55%, Lag= 18.0 min
 Primary = 2.72 cfs @ 12.33 hrs, Volume= 24,354 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 421.09' @ 12.33 hrs Surf.Area= 5,489 sf Storage= 10,190 cf (7,994 cf above start)

Plug-Flow detention time= 205.4 min calculated for 22,145 cf (77% of inflow)
 Center-of-Mass det. time= 89.3 min (930.1 - 840.8)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=2.72 cfs @ 12.33 hrs HW=421.09' (Free Discharge)

- ↑ 1=Culvert (Passes 2.72 cfs of 11.45 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.32 cfs @ 0.94 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 2.04 cfs @ 2.72 fps)
- ↑ 5=Orifice/Grate (Orifice Controls 0.36 cfs @ 5.82 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/4/2014

Events for Pond 21P: Infiltration-2

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	2.78	0.27	420.42	7,451
2-yr	4.16	0.80	420.72	8,707
5-yr	6.08	2.72	421.09	10,190
10-yr	11.98	9.17	421.56	11,883
25-yr	18.63	16.76	421.88	12,782
50-yr	23.06	20.20	422.28	13,668
100-yr	27.61	23.51	422.92	15,058

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 2.97" for 10-yr event
 Inflow = 11.98 cfs @ 12.09 hrs, Volume= 40,431 cf
 Outflow = 9.17 cfs @ 12.16 hrs, Volume= 35,469 cf, Atten= 23%, Lag= 4.0 min
 Primary = 9.17 cfs @ 12.16 hrs, Volume= 35,469 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 421.56' @ 12.16 hrs Surf.Area= 5,489 sf Storage= 11,883 cf (9,687 cf above start)

Plug-Flow detention time= 149.6 min calculated for 33,255 cf (82% of inflow)
 Center-of-Mass det. time= 59.7 min (891.5 - 831.8)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=9.16 cfs @ 12.16 hrs HW=421.56' (Free Discharge)

- 1=Culvert (Passes 9.16 cfs of 15.58 cfs potential flow)
- 2=Sharp-Crested Rectangular Weir (Weir Controls 0.30 cfs @ 0.81 fps)
- 3=Orifice/Grate (Orifice Controls 5.20 cfs @ 2.60 fps)
- 4=Orifice/Grate (Orifice Controls 3.24 cfs @ 4.32 fps)
- 5=Orifice/Grate (Orifice Controls 0.42 cfs @ 6.70 fps)

Pond 21P: Infiltration-2 - Chamber Wizard Field A

Chamber Model = ADS_StormTech®SC-740 (ADSStormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 11 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

14 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 100.12' Row Length +12.0" End Stone x 2 = 102.12' Base Length

11 Rows x 51.0" Wide + 6.0" Spacing x 10 + 12.0" Side Stone x 2 = 53.75' Base Width

18.0" Base + 30.0" Chamber Height + 12.0" Cover = 5.00' Field Height

154 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 11 Rows = 7,105.9 cf Chamber Storage

27,444.3 cf Field - 7,105.9 cf Chambers = 20,338.4 cf Stone x 40.0% Voids = 8,135.4 cf Stone Storage



Chamber Storage + Stone Storage = 15,241.2 cf = 0.350 af

Overall Storage Efficiency = 55.5%

154 Chambers

1,016.5 cy Field

753.3 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 3.86" for 25-yr event
 Inflow = 18.63 cfs @ 12.05 hrs, Volume= 52,471 cf
 Outflow = 16.76 cfs @ 12.09 hrs, Volume= 47,016 cf, Atten= 10%, Lag= 2.6 min
 Primary = 16.76 cfs @ 12.09 hrs, Volume= 47,016 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 421.88' @ 12.09 hrs Surf.Area= 5,489 sf Storage= 12,783 cf (10,587 cf above start)

Plug-Flow detention time= 120.0 min calculated for 44,797 cf (85% of inflow)
 Center-of-Mass det. time= 44.5 min (870.8 - 826.2)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=16.72 cfs @ 12.09 hrs HW=421.88' (Free Discharge)

- 1=Culvert (Passes 16.72 cfs of 17.79 cfs potential flow)
- 2=Sharp-Crested Rectangular Weir (Weir Controls 4.81 cfs @ 2.12 fps)
- 3=Orifice/Grate (Orifice Controls 7.61 cfs @ 3.81 fps)
- 4=Orifice/Grate (Orifice Controls 3.84 cfs @ 5.12 fps)
- 5=Orifice/Grate (Orifice Controls 0.45 cfs @ 7.24 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 4.76" for 50-yr event
 Inflow = 23.06 cfs @ 12.04 hrs, Volume= 64,702 cf
 Outflow = 20.20 cfs @ 12.09 hrs, Volume= 59,032 cf, Atten= 12%, Lag= 3.2 min
 Primary = 20.20 cfs @ 12.09 hrs, Volume= 59,032 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 422.28' @ 12.09 hrs Surf.Area= 5,489 sf Storage= 13,668 cf (11,473 cf above start)

Plug-Flow detention time= 102.7 min calculated for 56,832 cf (88% of inflow)
 Center-of-Mass det. time= 37.4 min (859.8 - 822.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=20.20 cfs @ 12.09 hrs HW=422.28' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 20.20 cfs @ 6.43 fps)
- ↑ 2=Sharp-Crested Rectangular Weir (Passes < 14.51 cfs potential flow)
- ↑ 3=Orifice/Grate (Passes < 9.76 cfs potential flow)
- ↑ 4=Orifice/Grate (Passes < 4.47 cfs potential flow)
- ↑ 5=Orifice/Grate (Passes < 0.49 cfs potential flow)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 21P: Infiltration-2

Inflow Area = 163,219 sf, 69.50% Impervious, Inflow Depth > 5.90" for 100-yr event
 Inflow = 27.61 cfs @ 12.03 hrs, Volume= 80,184 cf
 Outflow = 23.51 cfs @ 12.09 hrs, Volume= 74,355 cf, Atten= 15%, Lag= 3.6 min
 Primary = 23.51 cfs @ 12.09 hrs, Volume= 74,355 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 419.00' Surf.Area= 5,489 sf Storage= 2,196 cf
 Peak Elev= 422.92' @ 12.09 hrs Surf.Area= 5,489 sf Storage= 15,058 cf (12,862 cf above start)

Plug-Flow detention time= 88.5 min calculated for 72,125 cf (90% of inflow)
 Center-of-Mass det. time= 32.3 min (850.5 - 818.1)

Volume	Invert	Avail.Storage	Storage Description
#1A	418.00'	8,135 cf	53.75'W x 102.12'L x 5.00'H Field A 27,444 cf Overall - 7,106 cf Embedded = 20,338 cf x 40.0% Voids
#2A	419.50'	7,106 cf	ADS_StormTech SC-740x 154 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 11 rows
		15,241 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	419.50'	24.0" Round Culvert L= 17.0' Ke= 0.500 Inlet / Outlet Invert= 419.50' / 417.80' S= 0.1000 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	421.50'	6.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	421.00'	48.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#4	Device 1	420.50'	18.0" W x 6.0" H Vert. Orifice/Grate C= 0.600
#5	Device 1	419.50'	3.0" W x 3.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=23.50 cfs @ 12.09 hrs HW=422.91' (Free Discharge)

- ↑ 1=Culvert (Inlet Controls 23.50 cfs @ 7.48 fps)
 - ↑ 2=Sharp-Crested Rectangular Weir (Passes < 36.89 cfs potential flow)
 - ↑ 3=Orifice/Grate (Passes < 12.41 cfs potential flow)
 - ↑ 4=Orifice/Grate (Passes < 5.31 cfs potential flow)
 - ↑ 5=Orifice/Grate (Passes < 0.55 cfs potential flow)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 21P: Infiltration-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3

Runoff = 0.52 cfs @ 12.02 hrs, Volume= 1,225 cf, Depth> 1.16"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3

Runoff = 0.78 cfs @ 12.02 hrs, Volume= 1,835 cf, Depth> 1.74"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 5-yr Rainfall=4.32"
 Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3

Runoff = 1.14 cfs @ 12.01 hrs, Volume= 2,704 cf, Depth> 2.56"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 5-yr Rainfall=4.32"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3

Runoff = 1.51 cfs @ 12.01 hrs, Volume= 3,614 cf, Depth> 3.42"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3


Runoff = 1.88 cfs @ 12.01 hrs, Volume= 4,548 cf, Depth> 4.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3

Runoff = 2.25 cfs @ 12.01 hrs, Volume= 5,499 cf, Depth> 5.21"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 28S: INFIL-3


Runoff = 2.72 cfs @ 12.01 hrs, Volume= 6,705 cf, Depth> 6.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (sf)	CN	Description
7,411	98	Paved parking, HSG B
5,266	61	>75% Grass cover, Good, HSG B
12,677	83	Weighted Average
5,266		41.54% Pervious Area
7,411		58.46% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 28S: INFIL-3



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/3/2014

Events for Pond 27P: INFILTRATION-3

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	0.52	0.13	416.44	924
2-yr	0.78	0.29	416.65	1,127
5-yr	1.14	0.64	416.85	1,322
10-yr	1.51	0.89	417.06	1,514
25-yr	1.88	1.09	417.29	1,722
50-yr	2.25	1.28	417.54	1,940
100-yr	2.72	1.50	417.89	2,223

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/3/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 6.35" for 100-yr event
 Inflow = 2.72 cfs @ 12.01 hrs, Volume= 6,705 cf
 Outflow = 1.50 cfs @ 12.12 hrs, Volume= 6,586 cf, Atten= 45%, Lag= 6.5 min
 Primary = 1.50 cfs @ 12.12 hrs, Volume= 6,586 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,221 sf Storage= 489 cf
 Peak Elev= 417.89' @ 12.12 hrs Surf.Area= 1,221 sf Storage= 2,223 cf (1,735 cf above start)

Plug-Flow detention time= 93.6 min calculated for 6,095 cf (91% of inflow)
 Center-of-Mass det. time= 27.9 min (820.9 - 793.1)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,601 cf	39.50'W x 30.92'L x 4.50'H Field A 5,496 cf Overall - 1,493 cf Embedded = 4,003 cf x 40.0% Voids
#2A	416.00'	1,493 cf	ADS_StormTech SC-740x 32 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 8 rows
		3,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	24.0" Round Culvert L= 23.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 414.90' S= 0.0478 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.50 cfs @ 12.12 hrs HW=417.89' (Free Discharge)

- ↑ 1=Culvert (Passes 1.50 cfs of 14.38 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.31 cfs @ 6.40 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 1.18 cfs @ 5.32 fps)

Pond 27P: INFILTRATION-3 - Chamber Wizard Field A

Chamber Model = ADS_StormTech®SC-740 (ADSSstormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 8 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 28.92' Row Length +12.0" End Stone x 2 = 30.92' Base Length

8 Rows x 51.0" Wide + 6.0" Spacing x 7 + 12.0" Side Stone x 2 = 39.50' Base Width

12.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.50' Field Height

32 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 8 Rows = 1,492.8 cf Chamber Storage

5,496.0 cf Field - 1,492.8 cf Chambers = 4,003.2 cf Stone x 40.0% Voids = 1,601.3 cf Stone Storage



Chamber Storage + Stone Storage = 3,094.1 cf = 0.071 af

Overall Storage Efficiency = 56.3%

32 Chambers

203.6 cy Field

148.3 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 1.74" for 2-yr event
 Inflow = 0.78 cfs @ 12.02 hrs, Volume= 1,835 cf
 Outflow = 0.32 cfs @ 12.16 hrs, Volume= 1,774 cf, Atten= 59%, Lag= 8.3 min
 Primary = 0.32 cfs @ 12.16 hrs, Volume= 1,774 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 416.67' @ 12.16 hrs Surf.Area= 1,140 sf Storage= 1,072 cf (616 cf above start)

Plug-Flow detention time= 188.1 min calculated for 1,318 cf (72% of inflow)
 Center-of-Mass det. time= 38.4 min (867.9 - 829.6)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS_StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.32 cfs @ 12.16 hrs HW=416.67' (Free Discharge)

- ↑ 1=Culvert (Passes 0.32 cfs of 2.09 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.17 cfs @ 3.55 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.15 cfs @ 1.32 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 5-yr Rainfall=4.32"
Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 2.56" for 5-yr event
 Inflow = 1.14 cfs @ 12.01 hrs, Volume= 2,704 cf
 Outflow = 0.67 cfs @ 12.12 hrs, Volume= 2,630 cf, Atten= 41%, Lag= 6.0 min
 Primary = 0.67 cfs @ 12.12 hrs, Volume= 2,630 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 416.87' @ 12.12 hrs Surf.Area= 1,140 sf Storage= 1,254 cf (798 cf above start)

Plug-Flow detention time= 144.2 min calculated for 2,174 cf (80% of inflow)
 Center-of-Mass det. time= 32.6 min (851.2 - 818.6)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS_StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 ' /' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.67 cfs @ 12.12 hrs HW=416.87' (Free Discharge)

- ↑ 1=Culvert (Passes 0.67 cfs of 3.23 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.20 cfs @ 4.16 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.47 cfs @ 2.11 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/4/2014

Events for Pond 27P: INFILTRATION-3

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	0.52	0.13	416.44	924
2-yr	0.78	0.29	416.65	1,127
5-yr	1.14	0.64	416.85	1,322
10-yr	1.51	0.89	417.06	1,514
25-yr	1.88	1.09	417.29	1,722
50-yr	2.25	1.28	417.54	1,940
100-yr	2.72	1.50	417.89	2,223

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 3.42" for 10-yr event
 Inflow = 1.51 cfs @ 12.01 hrs, Volume= 3,614 cf
 Outflow = 0.92 cfs @ 12.11 hrs, Volume= 3,530 cf, Atten= 39%, Lag= 5.8 min
 Primary = 0.92 cfs @ 12.11 hrs, Volume= 3,530 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 417.09' @ 12.11 hrs Surf.Area= 1,140 sf Storage= 1,439 cf (983 cf above start)

Plug-Flow detention time= 120.8 min calculated for 3,073 cf (85% of inflow)
 Center-of-Mass det. time= 29.8 min (840.2 - 810.4)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.92 cfs @ 12.11 hrs HW=417.09' (Free Discharge)

- ↑ 1=Culvert (Passes 0.92 cfs of 4.55 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.23 cfs @ 4.72 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.69 cfs @ 3.10 fps)

Pond 27P: INFILTRATION-3 - Chamber Wizard Field A

Chamber Model = ADS_StormTechSC-740 (ADSStormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 8 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

4 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 28.92' Row Length +12.0" End Stone x 2 = 30.92' Base Length

8 Rows x 51.0" Wide + 6.0" Spacing x 7 + 12.0" Side Stone x 2 = 39.50' Base Width

12.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.50' Field Height

32 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 8 Rows = 1,492.8 cf Chamber Storage

5,496.0 cf Field - 1,492.8 cf Chambers = 4,003.2 cf Stone x 40.0% Voids = 1,601.3 cf Stone Storage



Chamber Storage + Stone Storage = 3,094.1 cf = 0.071 af

Overall Storage Efficiency = 56.3%

32 Chambers

203.6 cy Field

148.3 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 4.31" for 25-yr event
 Inflow = 1.88 cfs @ 12.01 hrs, Volume= 4,548 cf
 Outflow = 1.12 cfs @ 12.11 hrs, Volume= 4,456 cf, Atten= 40%, Lag= 5.9 min
 Primary = 1.12 cfs @ 12.11 hrs, Volume= 4,456 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 417.33' @ 12.11 hrs Surf.Area= 1,140 sf Storage= 1,640 cf (1,184 cf above start)

Plug-Flow detention time= 106.6 min calculated for 3,998 cf (88% of inflow)
 Center-of-Mass det. time= 28.1 min (832.0 - 803.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS_StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.12 cfs @ 12.11 hrs HW=417.33' (Free Discharge)

- ↑ 1=Culvert (Passes 1.12 cfs of 6.11 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.26 cfs @ 5.27 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 0.87 cfs @ 3.90 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 5.21" for 50-yr event
 Inflow = 2.25 cfs @ 12.01 hrs, Volume= 5,499 cf
 Outflow = 1.31 cfs @ 12.11 hrs, Volume= 5,399 cf, Atten= 42%, Lag= 6.1 min
 Primary = 1.31 cfs @ 12.11 hrs, Volume= 5,399 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 417.59' @ 12.11 hrs Surf.Area= 1,140 sf Storage= 1,851 cf (1,395 cf above start)

Plug-Flow detention time= 97.2 min calculated for 4,943 cf (90% of inflow)
 Center-of-Mass det. time= 27.0 min (825.5 - 798.6)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.31 cfs @ 12.11 hrs HW=417.59' (Free Discharge)

- ↑ 1=Culvert (Passes 1.31 cfs of 7.79 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.29 cfs @ 5.82 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 1.03 cfs @ 4.62 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 27P: INFILTRATION-3

Inflow Area = 12,677 sf, 58.46% Impervious, Inflow Depth > 6.35" for 100-yr event
 Inflow = 2.72 cfs @ 12.01 hrs, Volume= 6,705 cf
 Outflow = 1.54 cfs @ 12.12 hrs, Volume= 6,594 cf, Atten= 43%, Lag= 6.3 min
 Primary = 1.54 cfs @ 12.12 hrs, Volume= 6,594 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Starting Elev= 416.00' Surf.Area= 1,140 sf Storage= 456 cf
 Peak Elev= 417.96' @ 12.12 hrs Surf.Area= 1,140 sf Storage= 2,125 cf (1,669 cf above start)

Plug-Flow detention time= 88.4 min calculated for 6,136 cf (92% of inflow)
 Center-of-Mass det. time= 26.0 min (819.1 - 793.1)

Volume	Invert	Avail.Storage	Storage Description
#1A	415.00'	1,496 cf	25.25'W x 45.16'L x 4.50'H Field A 5,131 cf Overall - 1,392 cf Embedded = 3,739 cf x 40.0% Voids
#2A	416.00'	1,392 cf	ADS_StormTech SC-740x 30 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 5 rows
		2,888 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	416.00'	18.0" Round Culvert L= 22.0' Ke= 0.500 Inlet / Outlet Invert= 416.00' / 415.68' S= 0.0145 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 1.77 sf
#2	Device 1	418.50'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height
#3	Device 1	416.00'	3.0" Vert. Orifice/Grate C= 0.600
#4	Device 1	416.50'	8.0" W x 4.0" H Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=1.54 cfs @ 12.12 hrs HW=417.96' (Free Discharge)

- ↑ 1=Culvert (Passes 1.54 cfs of 9.36 cfs potential flow)
- ↑ 2=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
- ↑ 3=Orifice/Grate (Orifice Controls 0.32 cfs @ 6.52 fps)
- ↑ 4=Orifice/Grate (Orifice Controls 1.22 cfs @ 5.47 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 27P: INFILTRATION-3

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1

Runoff = 4.19 cfs @ 12.01 hrs, Volume= 11,186 cf, Depth> 2.41"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1


Runoff = 5.37 cfs @ 12.01 hrs, Volume= 14,515 cf, Depth> 3.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1

Runoff = 6.93 cfs @ 12.01 hrs, Volume= 18,959 cf, Depth> 4.08"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1


Runoff = 8.49 cfs @ 12.01 hrs, Volume= 23,408 cf, Depth> 5.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1


Runoff = 10.05 cfs @ 12.01 hrs, Volume= 27,860 cf, Depth> 5.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1


Runoff = 11.61 cfs @ 12.01 hrs, Volume= 32,312 cf, Depth> 6.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 13S: Cistern-1


Runoff = 13.55 cfs @ 12.01 hrs, Volume= 37,880 cf, Depth> 8.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
0.538	98	Roofs, HSG B
0.743	98	Roofs, HSG B
1.281	98	Weighted Average
1.281		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 13S: Cistern-1



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Events for Pond 14P: CISTERN-1

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	4.19	0.00	427.71	11,186
2-yr	5.37	0.12	428.13	12,200
5-yr	6.93	1.04	428.26	12,469
10-yr	8.49	5.15	428.55	13,114
25-yr	10.05	8.82	428.74	13,528
50-yr	11.61	11.11	428.84	13,752
100-yr	13.55	13.16	428.93	13,940

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 2.41" for 1-yr event
 Inflow = 4.19 cfs @ 12.01 hrs, Volume= 11,186 cf
 Outflow = 0.00 cfs @ 0.00 hrs, Volume= 0 cf, Atten= 100%, Lag= 0.0 min
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 427.71' @ 24.00 hrs Surf.Area= 5,471 sf Storage= 11,186 cf

Plug-Flow detention time= (not calculated: initial storage exceeds outflow)
 Center-of-Mass det. time= (not calculated: no outflow)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=424.50' (Free Discharge)

↑ **1=Culvert** (Passes 0.00 cfs of 1.35 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 14P: CISTERN-1 - Chamber Wizard Field A

Chamber Model = ADS_StormTech®SC-740 (ADSStormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 17 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

9 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 64.52' Row Length +12.0" End Stone x 2 = 66.52' Base Length

17 Rows x 51.0" Wide + 6.0" Spacing x 16 + 12.0" Side Stone x 2 = 82.25' Base Width

12.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.50' Field Height

153 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 17 Rows = 7,076.9 cf Chamber Storage

24,620.1 cf Field - 7,076.9 cf Chambers = 17,543.2 cf Stone x 40.0% Voids = 7,017.3 cf Stone Storage


Chamber Storage + Stone Storage = 14,094.2 cf = 0.324 af

Overall Storage Efficiency = 57.2%

153 Chambers

911.9 cy Field

649.7 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 3.12" for 2-yr event
 Inflow = 5.37 cfs @ 12.01 hrs, Volume= 14,515 cf
 Outflow = 0.12 cfs @ 15.45 hrs, Volume= 2,360 cf, Atten= 98%, Lag= 206.4 min
 Primary = 0.12 cfs @ 15.45 hrs, Volume= 2,360 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.13' @ 15.45 hrs Surf.Area= 5,471 sf Storage= 12,200 cf

Plug-Flow detention time= 650.7 min calculated for 2,359 cf (16% of inflow)
 Center-of-Mass det. time= 369.8 min (1,123.8 - 753.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.11 cfs @ 15.45 hrs HW=428.13' (Free Discharge)

↑1=Culvert (Passes 0.11 cfs of 26.78 cfs potential flow)

↑2=Sharp-Crested Rectangular Weir (Weir Controls 0.11 cfs @ 0.61 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 4.08" for 5-yr event
 Inflow = 6.93 cfs @ 12.01 hrs, Volume= 18,959 cf
 Outflow = 1.04 cfs @ 12.32 hrs, Volume= 6,796 cf, Atten= 85%, Lag= 18.7 min
 Primary = 1.04 cfs @ 12.32 hrs, Volume= 6,796 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.26' @ 12.32 hrs Surf.Area= 5,471 sf Storage= 12,469 cf

Plug-Flow detention time= 355.8 min calculated for 6,793 cf (36% of inflow)
 Center-of-Mass det. time= 191.3 min (940.3 - 749.0)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.03 cfs @ 12.32 hrs HW=428.26' (Free Discharge)

↑1=Culvert (Passes 1.03 cfs of 27.30 cfs potential flow)

↑2=Sharp-Crested Rectangular Weir (Weir Controls 1.03 cfs @ 1.32 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 5.03" for 10-yr event
 Inflow = 8.49 cfs @ 12.01 hrs, Volume= 23,408 cf
 Outflow = 5.15 cfs @ 12.11 hrs, Volume= 11,236 cf, Atten= 39%, Lag= 5.9 min
 Primary = 5.15 cfs @ 12.11 hrs, Volume= 11,236 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.55' @ 12.11 hrs Surf.Area= 5,471 sf Storage= 13,114 cf

Plug-Flow detention time= 272.6 min calculated for 11,231 cf (48% of inflow)
 Center-of-Mass det. time= 139.6 min (885.1 - 745.5)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 ' /' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=5.14 cfs @ 12.11 hrs HW=428.55' (Free Discharge)

↑ **1=Culvert** (Passes 5.14 cfs of 28.51 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 5.14 cfs @ 2.32 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 5.99" for 25-yr event
 Inflow = 10.05 cfs @ 12.01 hrs, Volume= 27,860 cf
 Outflow = 8.82 cfs @ 12.06 hrs, Volume= 15,679 cf, Atten= 12%, Lag= 2.9 min
 Primary = 8.82 cfs @ 12.06 hrs, Volume= 15,679 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.74' @ 12.06 hrs Surf.Area= 5,471 sf Storage= 13,528 cf

Plug-Flow detention time= 235.2 min calculated for 15,672 cf (56% of inflow)
 Center-of-Mass det. time= 117.1 min (860.0 - 742.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=8.81 cfs @ 12.06 hrs HW=428.74' (Free Discharge)

↑1=Culvert (Passes 8.81 cfs of 29.26 cfs potential flow)

↑2=Sharp-Crested Rectangular Weir (Weir Controls 8.81 cfs @ 2.82 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 6.95" for 50-yr event
 Inflow = 11.61 cfs @ 12.01 hrs, Volume= 32,312 cf
 Outflow = 11.11 cfs @ 12.04 hrs, Volume= 20,123 cf, Atten= 4%, Lag= 1.7 min
 Primary = 11.11 cfs @ 12.04 hrs, Volume= 20,123 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.84' @ 12.04 hrs Surf.Area= 5,471 sf Storage= 13,752 cf

Plug-Flow detention time= 213.6 min calculated for 20,114 cf (62% of inflow)
 Center-of-Mass det. time= 104.7 min (845.5 - 740.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=11.09 cfs @ 12.04 hrs HW=428.84' (Free Discharge)

↑ 1=Culvert (Passes 11.09 cfs of 29.65 cfs potential flow)

↑ 2=Sharp-Crested Rectangular Weir (Weir Controls 11.09 cfs @ 3.08 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 14P: CISTERN-1

Inflow Area = 55,800 sf, 100.00% Impervious, Inflow Depth > 8.15" for 100-yr event
 Inflow = 13.55 cfs @ 12.01 hrs, Volume= 37,880 cf
 Outflow = 13.16 cfs @ 12.03 hrs, Volume= 25,679 cf, Atten= 3%, Lag= 1.4 min
 Primary = 13.16 cfs @ 12.03 hrs, Volume= 25,679 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 428.93' @ 12.03 hrs Surf.Area= 5,471 sf Storage= 13,940 cf

Plug-Flow detention time= 196.4 min calculated for 25,668 cf (68% of inflow)
 Center-of-Mass det. time= 95.2 min (834.1 - 738.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	424.50'	7,017 cf	82.25'W x 66.52'L x 4.50'H Field A 24,620 cf Overall - 7,077 cf Embedded = 17,543 cf x 40.0% Voids
#2A	425.50'	7,077 cf	ADS_StormTech SC-740x 153 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 17 rows
		14,094 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	424.00'	24.0" Round Culvert L= 16.0' Ke= 0.500 Inlet / Outlet Invert= 424.00' / 423.80' S= 0.0125 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 3.14 sf
#2	Device 1	428.10'	5.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=13.15 cfs @ 12.03 hrs HW=428.93' (Free Discharge)

↑ **1=Culvert** (Passes 13.15 cfs of 29.98 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 13.15 cfs @ 3.28 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 14P: CISTERN-1

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 1-yr Rainfall=2.64"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2

Runoff = 0.67 cfs @ 12.01 hrs, Volume= 1,781 cf, Depth> 2.41"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 1-yr Rainfall=2.64"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 2-yr Rainfall=3.36"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2


Runoff = 0.85 cfs @ 12.01 hrs, Volume= 2,311 cf, Depth> 3.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 2-yr Rainfall=3.36"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 5-yr Rainfall=4.32"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2


Runoff = 1.10 cfs @ 12.01 hrs, Volume= 3,019 cf, Depth> 4.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 5-yr Rainfall=4.32"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 10-yr Rainfall=5.28"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2

Runoff = 1.35 cfs @ 12.01 hrs, Volume= 3,728 cf, Depth> 5.03"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
* 0.122	98	Equipment Area Roof
* 0.082	98	Lower Roof
0.204	98	Weighted Average
0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2

Runoff = 1.60 cfs @ 12.01 hrs, Volume= 4,437 cf, Depth> 5.99"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 50-yr Rainfall=7.20"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2


Runoff = 1.85 cfs @ 12.01 hrs, Volume= 5,146 cf, Depth> 6.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 50-yr Rainfall=7.20"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 100-yr Rainfall=8.40"
 Printed 12/2/2014

Summary for Subcatchment 29S: Cistern-2

Runoff = 2.16 cfs @ 12.01 hrs, Volume= 6,032 cf, Depth> 8.15"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 100-yr Rainfall=8.40"

	Area (ac)	CN	Description
*	0.122	98	Equipment Area Roof
*	0.082	98	Lower Roof
	0.204	98	Weighted Average
	0.204		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 29S: Cistern-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Events for Pond 30P: CISTERN-2

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	0.67	0.01	416.51	1,652
2-yr	0.85	0.06	416.53	1,659
5-yr	1.10	0.72	416.68	1,705
10-yr	1.35	1.32	416.76	1,732
25-yr	1.60	1.59	416.80	1,743
50-yr	1.85	1.84	416.83	1,752
100-yr	2.16	2.15	416.86	1,763

LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 1-yr Rainfall=2.64"
 Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 2.41" for 1-yr event
 Inflow = 0.67 cfs @ 12.01 hrs, Volume= 1,781 cf
 Outflow = 0.01 cfs @ 19.01 hrs, Volume= 130 cf, Atten= 99%, Lag= 419.7 min
 Primary = 0.01 cfs @ 19.01 hrs, Volume= 130 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.51' @ 19.01 hrs Surf.Area= 780 sf Storage= 1,652 cf

Plug-Flow detention time= 903.8 min calculated for 130 cf (7% of inflow)
 Center-of-Mass det. time= 514.8 min (1,274.1 - 759.3)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=0.00 cfs @ 19.01 hrs HW=416.51' (Free Discharge)
 ↑ **1=Culvert** (Passes 0.00 cfs of 6.56 cfs potential flow)
 ↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 0.00 cfs @ 0.26 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 2-yr Rainfall=3.36"
Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 3.12" for 2-yr event
 Inflow = 0.85 cfs @ 12.01 hrs, Volume= 2,311 cf
 Outflow = 0.06 cfs @ 12.75 hrs, Volume= 660 cf, Atten= 93%, Lag= 44.3 min
 Primary = 0.06 cfs @ 12.75 hrs, Volume= 660 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.53' @ 12.75 hrs Surf.Area= 780 sf Storage= 1,659 cf

Plug-Flow detention time= 425.1 min calculated for 660 cf (29% of inflow)
 Center-of-Mass det. time= 236.4 min (990.3 - 753.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 ' /' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=0.05 cfs @ 12.75 hrs HW=416.53' (Free Discharge)

↑ **1=Culvert** (Passes 0.05 cfs of 6.58 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 0.05 cfs @ 0.57 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 4.08" for 5-yr event
 Inflow = 1.10 cfs @ 12.01 hrs, Volume= 3,019 cf
 Outflow = 0.72 cfs @ 12.10 hrs, Volume= 1,367 cf, Atten= 35%, Lag= 5.4 min
 Primary = 0.72 cfs @ 12.10 hrs, Volume= 1,367 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.68' @ 12.10 hrs Surf.Area= 780 sf Storage= 1,705 cf

Plug-Flow detention time= 281.7 min calculated for 1,367 cf (45% of inflow)
 Center-of-Mass det. time= 144.6 min (893.6 - 749.0)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=0.72 cfs @ 12.10 hrs HW=416.68' (Free Discharge)

↑ **1=Culvert** (Passes 0.72 cfs of 6.74 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 0.72 cfs @ 1.38 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/4/2014

Events for Pond 30P: CISTERN-2

Event	Inflow (cfs)	Primary (cfs)	Elevation (feet)	Storage (cubic-feet)
1-yr	0.67	0.01	416.51	1,652
2-yr	0.85	0.06	416.53	1,659
5-yr	1.10	0.72	416.68	1,705
10-yr	1.35	1.32	416.76	1,732
25-yr	1.60	1.59	416.80	1,743
50-yr	1.85	1.84	416.83	1,752
100-yr	2.16	2.15	416.86	1,763

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 5.03" for 10-yr event
 Inflow = 1.35 cfs @ 12.01 hrs, Volume= 3,728 cf
 Outflow = 1.32 cfs @ 12.03 hrs, Volume= 2,075 cf, Atten= 2%, Lag= 1.3 min
 Primary = 1.32 cfs @ 12.03 hrs, Volume= 2,075 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.76' @ 12.03 hrs Surf.Area= 780 sf Storage= 1,732 cf

Plug-Flow detention time= 232.7 min calculated for 2,074 cf (56% of inflow)
 Center-of-Mass det. time= 114.7 min (860.2 - 745.5)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 ' / Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=1.32 cfs @ 12.03 hrs HW=416.76' (Free Discharge)

↑ **1=Culvert** (Passes 1.32 cfs of 6.83 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 1.32 cfs @ 1.70 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/4/2014

Pond 30P: CISTERN-2 - Chamber Wizard Field A

Chamber Model = ADS_StormTechSC-740 (ADSSstormTech®SC-740)

Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf

Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap

Row Length Adjustment= +0.44' x 6.45 sf x 4 rows

51.0" Wide + 6.0" Spacing = 57.0" C-C Row Spacing

5 Chambers/Row x 7.12' Long +0.44' Row Adjustment = 36.04' Row Length +12.0" End Stone x 2 = 38.04' Base Length

4 Rows x 51.0" Wide + 6.0" Spacing x 3 + 12.0" Side Stone x 2 = 20.50' Base Width

6.0" Base + 30.0" Chamber Height + 12.0" Cover = 4.00' Field Height



20 Chambers x 45.9 cf +0.44' Row Adjustment x 6.45 sf x 4 Rows = 930.2 cf Chamber Storage

3,119.3 cf Field - 930.2 cf Chambers = 2,189.1 cf Stone x 40.0% Voids = 875.6 cf Stone Storage

Chamber Storage + Stone Storage = 1,805.8 cf = 0.041 af

Overall Storage Efficiency = 57.9%

20 Chambers
115.5 cy Field
81.1 cy Stone



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.
 HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 25-yr Rainfall=6.24"
 Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 5.99" for 25-yr event
 Inflow = 1.60 cfs @ 12.01 hrs, Volume= 4,437 cf
 Outflow = 1.59 cfs @ 12.02 hrs, Volume= 2,784 cf, Atten= 1%, Lag= 0.6 min
 Primary = 1.59 cfs @ 12.02 hrs, Volume= 2,784 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.80' @ 12.02 hrs Surf.Area= 780 sf Storage= 1,743 cf

Plug-Flow detention time= 207.9 min calculated for 2,782 cf (63% of inflow)
 Center-of-Mass det. time= 100.3 min (843.2 - 742.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=1.59 cfs @ 12.02 hrs HW=416.80' (Free Discharge)

↑1=Culvert (Passes 1.59 cfs of 6.87 cfs potential flow)

↑2=Sharp-Crested Rectangular Weir (Weir Controls 1.59 cfs @ 1.82 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 6.95" for 50-yr event
 Inflow = 1.85 cfs @ 12.01 hrs, Volume= 5,146 cf
 Outflow = 1.84 cfs @ 12.02 hrs, Volume= 3,492 cf, Atten= 1%, Lag= 0.6 min
 Primary = 1.84 cfs @ 12.02 hrs, Volume= 3,492 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.83' @ 12.02 hrs Surf.Area= 780 sf Storage= 1,752 cf

Plug-Flow detention time= 192.5 min calculated for 3,491 cf (68% of inflow)
 Center-of-Mass det. time= 91.8 min (832.7 - 740.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 '/ Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=1.83 cfs @ 12.02 hrs HW=416.83' (Free Discharge)
 ↑ **1=Culvert** (Passes 1.83 cfs of 6.90 cfs potential flow)
 ↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 1.83 cfs @ 1.91 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Pond 30P: CISTERN-2

Inflow Area = 8,886 sf, 100.00% Impervious, Inflow Depth > 8.15" for 100-yr event
 Inflow = 2.16 cfs @ 12.01 hrs, Volume= 6,032 cf
 Outflow = 2.15 cfs @ 12.02 hrs, Volume= 4,378 cf, Atten= 1%, Lag= 0.6 min
 Primary = 2.15 cfs @ 12.02 hrs, Volume= 4,378 cf

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 416.86' @ 12.02 hrs Surf.Area= 780 sf Storage= 1,763 cf

Plug-Flow detention time= 179.3 min calculated for 4,378 cf (73% of inflow)
 Center-of-Mass det. time= 85.1 min (823.9 - 738.9)

Volume	Invert	Avail.Storage	Storage Description
#1A	413.00'	876 cf	20.50'W x 38.04'L x 4.00'H Field A 3,119 cf Overall - 930 cf Embedded = 2,189 cf x 40.0% Voids
#2A	413.50'	930 cf	ADS_StormTech SC-740x 20 Inside #1 Effective Size= 44.6"W x 30.0"H => 6.45 sf x 7.12'L = 45.9 cf Overall Size= 51.0"W x 30.0"H x 7.56'L with 0.44' Overlap Row Length Adjustment= +0.44' x 6.45 sf x 4 rows
		1,806 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	413.00'	12.0" Round Culvert L= 5.0' Ke= 0.500 Inlet / Outlet Invert= 413.00' / 412.90' S= 0.0200 '/' Cc= 0.900 n= 0.011 PVC, smooth interior, Flow Area= 0.79 sf
#2	Device 1	416.50'	3.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s) 2.0' Crest Height

Primary OutFlow Max=2.14 cfs @ 12.02 hrs HW=416.86' (Free Discharge)

↑ **1=Culvert** (Passes 2.14 cfs of 6.94 cfs potential flow)

↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 2.14 cfs @ 2.01 fps)

LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC


LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Pond 30P: CISTERN-2

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11

Runoff = 0.57 cfs @ 12.01 hrs, Volume= 1,442 cf, Depth> 2.19"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (ac)	CN	Description
* 0.032	98	Portion of sidewalk
* 0.140	98	Plaza
0.009	61	>75% Grass cover, Good, HSG B
0.181	96	Weighted Average
0.009		4.97% Pervious Area
0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
 Type II 24-hr 2-yr Rainfall=3.36"
 Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11


Runoff = 0.74 cfs @ 12.01 hrs, Volume= 1,906 cf, Depth> 2.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Type II 24-hr 2-yr Rainfall=3.36"

Area (ac)	CN	Description
* 0.032	98	Portion of sidewalk
* 0.140	98	Plaza
0.009	61	>75% Grass cover, Good, HSG B
0.181	96	Weighted Average
0.009		4.97% Pervious Area
0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11


Runoff = 0.96 cfs @ 12.01 hrs, Volume= 2,530 cf, Depth> 3.85"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

	Area (ac)	CN	Description
*	0.032	98	Portion of sidewalk
*	0.140	98	Plaza
	0.009	61	>75% Grass cover, Good, HSG B
	0.181	96	Weighted Average
	0.009		4.97% Pervious Area
	0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11

Runoff = 1.18 cfs @ 12.01 hrs, Volume= 3,155 cf, Depth> 4.80"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (ac)	CN	Description
* 0.032	98	Portion of sidewalk
* 0.140	98	Plaza
0.009	61	>75% Grass cover, Good, HSG B
0.181	96	Weighted Average
0.009		4.97% Pervious Area
0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11

Runoff = 1.41 cfs @ 12.01 hrs, Volume= 3,782 cf, Depth> 5.76"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

	Area (ac)	CN	Description
*	0.032	98	Portion of sidewalk
*	0.140	98	Plaza
	0.009	61	>75% Grass cover, Good, HSG B
	0.181	96	Weighted Average
	0.009		4.97% Pervious Area
	0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11

Runoff = 1.63 cfs @ 12.01 hrs, Volume= 4,409 cf, Depth> 6.71"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (ac)	CN	Description
* 0.032	98	Portion of sidewalk
* 0.140	98	Plaza
0.009	61	>75% Grass cover, Good, HSG B
0.181	96	Weighted Average
0.009		4.97% Pervious Area
0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11

Hydrograph



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 31S: FROM RG-11


Runoff = 1.90 cfs @ 12.01 hrs, Volume= 5,195 cf, Depth> 7.91"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (ac)	CN	Description
* 0.032	98	Portion of sidewalk
* 0.140	98	Plaza
0.009	61	>75% Grass cover, Good, HSG B
0.181	96	Weighted Average
0.009		4.97% Pervious Area
0.172		95.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

Subcatchment 31S: FROM RG-11



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 2.93 cfs @ 11.97 hrs, Volume= 5,758 cf, Depth> 0.83"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 1-yr Rainfall=2.64"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 4.73 cfs @ 11.97 hrs, Volume= 9,215 cf, Depth> 1.33"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 2-yr Rainfall=3.36"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 7.35 cfs @ 11.96 hrs, Volume= 14,340 cf, Depth> 2.06"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 5-yr Rainfall=4.32"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 10.09 cfs @ 11.96 hrs, Volume= 19,851 cf, Depth> 2.86"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 10-yr Rainfall=5.28"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT
Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 12.90 cfs @ 11.96 hrs, Volume= 25,620 cf, Depth> 3.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 25-yr Rainfall=6.24"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured


Runoff = 15.74 cfs @ 11.96 hrs, Volume= 31,569 cf, Depth> 4.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 50-yr Rainfall=7.20"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured



LAH SWM Report

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/2/2014

Summary for Subcatchment 12S: Ithan and Uncaptured

Runoff = 19.32 cfs @ 11.96 hrs, Volume= 39,185 cf, Depth> 5.64"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
Type II 24-hr 100-yr Rainfall=8.40"

Area (sf)	CN	Description
14,428	98	Paved parking, HSG B
566	61	>75% Grass cover, Good, HSG B
* 6,839	98	Lower Level Driveway Pavement
* 4,530	85	offsite contributing
* 57,064	69	uncaptured slope
83,427	77	Weighted Average
62,160		74.51% Pervious Area
21,267		25.49% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment 12S: Ithan and Uncaptured

Hydrograph



LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 1-yr Rainfall=2.64"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 1.12" for 1-yr event
Inflow = 8.29 cfs @ 11.99 hrs, Volume= 38,365 cf
Primary = 8.29 cfs @ 11.99 hrs, Volume= 38,365 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 2-yr Rainfall=3.36"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 1.65" for 2-yr event
Inflow = 11.68 cfs @ 11.99 hrs, Volume= 56,769 cf
Primary = 11.68 cfs @ 11.99 hrs, Volume= 56,769 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 5-yr Rainfall=4.32"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 2.41" for 5-yr event
Inflow = 16.44 cfs @ 11.98 hrs, Volume= 83,057 cf
Primary = 16.44 cfs @ 11.98 hrs, Volume= 83,057 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 10-yr Rainfall=5.28"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 3.22" for 10-yr event
Inflow = 21.99 cfs @ 11.99 hrs, Volume= 110,678 cf
Primary = 21.99 cfs @ 11.99 hrs, Volume= 110,678 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 25-yr Rainfall=6.24"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 4.05" for 25-yr event
Inflow = 30.23 cfs @ 12.01 hrs, Volume= 139,288 cf
Primary = 30.23 cfs @ 12.01 hrs, Volume= 139,288 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 50-yr Rainfall=7.20"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 4.90" for 50-yr event
Inflow = 39.99 cfs @ 12.00 hrs, Volume= 168,664 cf
Primary = 39.99 cfs @ 12.00 hrs, Volume= 168,664 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

LAH SWM Report_No Cistern Credit

Prepared by Nave Newell Inc.

HydroCAD® 10.00-12 s/n 07511 © 2014 HydroCAD Software Solutions LLC

LAH SWM REPORT

Type II 24-hr 100-yr Rainfall=8.40"

Printed 12/4/2014

Summary for Link 15L: POI 2A - POST

Inflow Area = 412,829 sf, 54.88% Impervious, Inflow Depth > 5.99" for 100-yr event
Inflow = 51.21 cfs @ 12.00 hrs, Volume= 206,219 cf
Primary = 51.21 cfs @ 12.00 hrs, Volume= 206,219 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

VIII.

Drainage Areas

Inlet	A total SF	Lawn - B SF	Impervious SF	C wt	25 yr Q cfs	100 yr Q cfs
I-1	8096	1731	6365	0.83	1.04	1.27
I-2	3597	404	3193	0.91	0.50	0.61
I-3	980	0	980	0.99	0.15	0.18
I-4	8646	1349	7297	0.87	1.16	1.42
I-5	2972	203	2769	0.94	0.43	0.52
I-6	2556	200	2356	0.93	0.37	0.45
I-7	1521	0	1521	0.99	0.23	0.28
I-8	19603	5848	13755	0.77	2.32	2.84
I-9	15282	2923	12359	0.85	1.99	2.44
I-10	7784	729	7055	0.92	1.10	1.35
I-11	1700	674	1026	0.70	0.18	0.22
I-12	221	0	221	0.99	0.03	0.04
I-13	3851	196	3655	0.95	0.56	0.69
I-14	3200	200	3000	0.94	0.46	0.57
I-15	4918	0	4918	0.99	0.75	0.92
I-16	2600	0	2600	0.99	0.40	0.48
I-17	1036	0	1036	0.99	0.16	0.19
I-18	5040	0	5040	0.99	0.77	0.94
I-20	2266	0	2266	0.99	0.35	0.42
RD-1	4117	0	4117	0.99	0.63	0.77
RD-2	7288	0	7288	0.99	1.11	1.36
RD-3A	5809	0	5809	0.99	0.88	1.08
RD-3B	9368	0	9368	0.99	1.43	1.74
RD-4	5925	0	5925	0.99	0.90	1.10
RD-5	7177	0	7177	0.99	1.09	1.34
RD-6	4275	0	4275	0.99	0.65	0.80
RD-7	4115	0	4115	0.99	0.63	0.77
RD-8	5765	0	5765	0.99	0.88	1.07
RD-9	2044	0	2044	0.99	0.31	0.38
RD-10	2044	0	2044	0.99	0.31	0.38
RD-11	4269	0	4269	0.99	0.65	0.79
RD-12	5028	0	5028	0.99	0.77	0.94
YD-1	3422	2393	1029	0.47	0.25	0.30
YD-2	769	769	0	0.25	0.03	0.04
RG-1	14913	5667	9246	0.71	1.63	1.99
RG-2	15554	12247	3307	0.41	0.97	1.19
RG-3	15197	6330	8867	0.68	1.59	1.95
RG-4	13979	8915	5064	0.52	1.11	1.36
RG-5	24212	16893	7319	0.47	1.76	2.16
RG-6	12712	6085	6627	0.64	1.24	1.52
RG-7	11945	9326	2619	0.41	0.76	0.93
RG-8	18063	10879	7184	0.54	1.51	1.85
RG-9	9942	5557	4385	0.58	0.88	1.08
RG-10	19789	13573	6216	0.48	1.47	1.80
TD-1	10840	2921	7919	0.79	1.32	1.61

$$Q = (C \text{ wt}) \times I \times (A \text{ total acres})$$

$$C \text{ wt} = \frac{[0.99 \times (\text{Impervious})] + [0.25 \times (\text{Lawn - B})]}{A \text{ total}}$$

I 25 = 6.70 in/hr; per PennDOT Road Design Manual, Vol
 I 100 = 8.19 Fig. 2.10.4.2(E), Region 5 I.D.F., 5 min. durati

C = 0.25 Lawn - B
 C = 0.99 Impervious

25-year

Conduit FlexTable: Villanova LAH Pipe / Node Report for Report (StormCAD - LAH.stc)

Table with 15 columns: Upstream Node, Downstream Node, Length (ft), Conduit Description, Slope (ft/ft), Mannin g's n, Flow (Link) (ft³/s), Full Capacity (ft³/s), Upstream Invert Elevation (ft), Downstream Invert Elevation (ft), Elevation Ground (Start) (ft), Elevation Ground (Stop) (ft), Hydraulic Grade Line (In) (ft), Hydraulic Grade Line (Out) (ft), Average Velocity (ft/s). Rows include nodes like I-15, I-16, I-18, INF-3 Outlet, INF-2 Outlet, Cistern 1 Outlet, I-10, I-11, I-12, I-13, I-9, MH-19, MH-18, MH-1, INF-1 Outlet, I-8, I-4, I-7, DET-1 Outlet, RG-8, RG-4, RG-10, RG-3, RG-2, RG-7, MH-15, MH-2, RD-8, RD-1, RD-7, RD-6, RD-5.

Conduit FlexTable: Villanova LAH Pipe / Node Report for Report (StormCAD - LAH.stc)

Upstream Node	Downstream Node	Length (ft)	Conduit Description	Slope (ft/ft)	Mannin g's n	Flow (Link) (ft³/s)	Full Capacity (ft³/s)	Upstream Invert Elevation (ft)	Downstream Invert Elevation (ft)	Elevation Ground (Start) (ft)	Elevation Ground (Stop) (ft)	Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Average Velocity (ft/s)
		21.0	Circular Pipe - 12.0 in	0.005	0.012	1.12	2.79	427.49	427.38	430.00	430.00	429.13	429.11	1.42
	MH-3	143.0	Circular Pipe - 12.0 in	0.003	0.012	1.12	2.24	427.38	426.90	430.00	430.50	429.11	428.99	1.42
RG-1	I-5	35.0	Circular Pipe - 12.0 in	0.006	0.012	1.64	2.92	431.10	430.90	436.50	436.64	431.64	431.54	3.82
RD-10		130.0	Circular Pipe - 8.0 in	0.029	0.012	0.31	2.22	432.00	428.26	435.00	435.00	432.26	430.90	4.50
I-6	I-5	43.0	Circular Pipe - 18.0 in	0.005	0.012	1.37	8.14	433.00	432.78	437.37	436.64	433.44	433.20	3.42
I-5	I-4	83.0	Circular Pipe - 18.0 in	0.005	0.012	3.44	8.09	430.70	430.28	436.64	435.53	431.41	431.07	4.39
I-3	I-2	48.0	Circular Pipe - 18.0 in	0.005	0.012	4.76	8.05	429.42	429.18	435.00	433.78	430.26	430.01	4.74
I-2	I-1	77.0	Circular Pipe - 18.0 in	0.005	0.012	9.38	8.10	425.98	425.59	433.78	431.70	427.80	427.27	5.31
I-1	INF-1A	36.0	Circular Pipe - 18.0 in	0.005	0.012	10.42	8.05	425.40	425.22	431.70	430.80	427.00	426.70	5.90
DB-7	DB-6	76.0	Circular Pipe - 12.0 in	0.005	0.012	2.51	2.73	427.88	427.50	435.34	436.00	429.54	429.22	3.19
DB-6	DB-5	95.0	Circular Pipe - 12.0 in	0.005	0.012	2.51	2.74	427.30	426.82	436.00	434.25	429.14	428.74	3.19
DB-5	I-2	45.0	Circular Pipe - 12.0 in	0.005	0.012	4.11	2.76	426.41	426.18	434.25	433.78	428.53	428.01	5.24
RG-5	Cistern 1 Outlet	7.0	Circular Pipe - 12.0 in	0.006	0.012	1.78	2.92	425.30	425.26	428.75	430.00	426.66	426.64	2.26
RG-9	YD-2	16.0	Circular Pipe - 12.0 in	0.005	0.012	0.89	2.73	431.00	430.92	433.50	434.00	431.39	431.31	3.10
YD-1	YD-2	27.0	Circular Pipe - 12.0 in	0.005	0.012	0.25	2.78	430.70	430.56	434.00	434.00	430.91	430.76	2.20
DB-2	MH-22	13.0	Circular Pipe - 12.0 in	0.005	0.012	1.17	2.83	426.97	426.90	434.00	434.00	428.52	428.51	1.49
RG-6	I-18	26.0	Circular Pipe - 12.0 in	0.005	0.012	1.25	2.73	427.80	427.67	432.50	432.00	428.28	428.14	3.40
I-17	I-16	98.0	Circular Pipe - 18.0 in	0.051	0.012	4.33	25.70	426.70	421.70	430.60	425.40	427.50	422.51	10.81
I-19	MH-15	210.0	Circular Pipe - 24.0 in	0.005	0.012	15.00	17.33	426.15	425.10	434.50	431.50	427.59	426.64	6.21
MH-10	MH-8	20.0	Circular Pipe - 18.0 in	0.014	0.012	34.58	13.46	413.40	413.12	424.00	416.00	416.85	415.00	19.57
RD-3A		104.0	Circular Pipe - 8.0 in	0.005	0.012	0.89	0.93	428.31	427.79	435.00	435.00	430.23	429.75	2.55
RD-3B		94.0	Circular Pipe - 10.0 in	0.005	0.012	1.44	1.68	428.55	428.08	430.00	430.00	429.72	429.37	2.64
	Cistern 1B	22.0	Circular Pipe - 12.0 in	0.005	0.012	1.44	2.73	427.01	426.90	430.00	430.50	429.02	428.99	1.83
RD-2		102.0	Circular Pipe - 12.0 in	0.005	0.012	1.12	2.73	428.00	427.49	430.00	430.00	429.21	429.13	1.42
		164.0	Circular Pipe - 12.0 in	0.005	0.012	3.59	2.63	428.26	427.50	435.00	435.00	430.90	429.48	4.58
INF-1 Outfall	MH-10	4.0	Circular Pipe - 18.0 in	0.025	0.012	12.00	17.99	418.00	417.90	422.00	424.00	419.87	419.82	6.79
I-20	INF-3B	5.0	Circular Pipe - 12.0 in	0.020	0.012	0.35	5.46	416.10	416.00	423.75	423.75	417.96	417.96	0.44
RD-11		84.0	Circular Pipe - 8.0 in	0.024	0.012	0.66	2.02	433.00	431.00	435.00	433.25	433.38	431.26	5.17
		50.0	Circular Pipe - 8.0 in	0.020	0.012	0.66	1.85	431.00	430.00	433.25	432.50	431.38	430.27	4.85
		20.0	Circular Pipe - 12.0 in	0.005	0.012	0.66	2.73	416.00	415.90	432.50	418.25	416.50	416.50	2.86
RD-12	MH-20	113.0	Circular Pipe - 8.0 in	0.027	0.012	0.77	2.13	419.00	416.00	421.10	418.10	419.42	416.50	5.62
I-14		6.0	Circular Pipe - 18.0 in	0.005	0.013	0.47	7.43	434.75	434.72	436.50	435.00	435.01	434.97	2.35
YD-2	DB-2	177.0	Circular Pipe - 12.0 in	0.005	0.012	1.17	2.74	428.06	427.17	434.00	434.00	428.67	428.54	3.35

100-yr

Conduit FlexTable: Villanova LAH Pipe / Node Report for Report (StormCAD - LAH.stc)

Upstream Node	Downstream Node	Length (ft)	Conduit Description	Slope (ft/ft)	Mannin g's n	Flow (Link) (ft ³ /s)	Full Capacity (ft ³ /s)	Upstream Invert Elevation (ft)	Downstream Invert Elevation (ft)	Elevation Ground (Start) (ft)	Elevation Ground (Stop) (ft)	Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Average Velocity (ft/s)
I-15	MH-8	47.0	Circular Pipe - 18.0 in	0.038	0.012	6.22	22.14	414.90	413.12	418.80	416.00	415.86	415.00	10.76
I-16	I-15	112.0	Circular Pipe - 18.0 in	0.057	0.012	5.30	27.20	421.50	415.10	425.40	418.80	422.39	416.07	11.93
I-18	I-17	38.0	Circular Pipe - 18.0 in	0.007	0.012	2.48	9.59	427.17	426.90	432.00	430.60	427.77	427.72	4.55
INF-3 Outlet	MH-10	23.0	Circular Pipe - 24.0 in	0.017	0.012	22.58	32.32	414.90	414.50	423.75	424.00	420.02	419.82	7.19
INF-2 Outlet	INF-3 Outlet	81.0	Circular Pipe - 24.0 in	0.041	0.012	21.04	49.46	419.50	416.20	426.60	423.75	421.14	420.42	15.11
Cistern 1 Outlet	MH-2	94.0	Circular Pipe - 24.0 in	0.005	0.012	14.33	17.33	424.00	423.53	430.00	430.10	426.70	426.38	4.56
I-10	INF-3A	5.0	Circular Pipe - 12.0 in	0.020	0.012	1.62	5.46	416.10	416.00	421.30	422.50	417.97	417.96	2.07
I-11	I-10	47.0	Circular Pipe - 12.0 in	0.005	0.012	0.27	2.76	416.85	416.61	422.30	421.30	418.00	418.00	0.34
I-12	I-11	30.0	Circular Pipe - 12.0 in	0.005	0.012	0.04	2.73	417.20	417.05	420.90	422.30	418.01	418.01	1.27
I-13	INF-2C	9.0	Circular Pipe - 12.0 in	0.006	0.012	0.70	2.88	420.95	420.90	425.90	426.80	422.16	422.16	0.88
I-9	INF-2A	12.0	Circular Pipe - 12.0 in	0.192	0.012	2.46	16.90	421.80	419.50	428.17	428.35	422.47	422.16	15.34
MH-19	MH-23	28.0	Circular Pipe - 24.0 in	0.009	0.012	21.29	23.61	421.51	421.25	429.00	428.46	423.16	422.77	8.51
MH-18	MH-19	76.0	Circular Pipe - 24.0 in	0.005	0.012	21.29	17.33	422.09	421.71	429.95	429.00	424.19	423.62	6.78
MH-1	MH-18	67.0	Circular Pipe - 24.0 in	0.005	0.012	21.29	17.46	422.63	422.29	430.00	429.95	425.05	424.55	6.78
INF-1 Outlet	INF-1 Outfall	14.0	Circular Pipe - 30.0 in	0.093	0.012	12.24	135.40	423.30	422.00	428.40	423.00	424.47	422.68	17.12
I-8	INF-1B	6.0	Circular Pipe - 12.0 in	0.005	0.012	2.86	2.73	424.73	424.70	428.88	429.30	426.73	426.70	3.64
I-4	I-3	91.0	Circular Pipe - 18.0 in	0.005	0.012	5.64	8.09	430.08	429.62	435.53	435.00	431.00	430.56	4.95
I-7	I-6	64.0	Circular Pipe - 18.0 in	0.005	0.012	1.22	8.05	433.50	433.18	438.50	437.37	433.91	433.57	3.28
DET-1 Outlet	MH-2	47.0	Circular Pipe - 18.0 in	0.005	0.012	5.58	8.13	425.00	424.76	430.90	430.10	426.49	426.38	4.96
RG-8	DB-7	100.0	Circular Pipe - 12.0 in	0.005	0.012	1.86	2.73	428.58	428.08	435.00	435.34	431.30	431.06	2.37
RG-4	MH-1	36.0	Circular Pipe - 12.0 in	0.005	0.012	1.37	2.73	425.30	425.12	428.75	430.00	425.80	425.62	3.48
RG-10	MH-21	13.0	Circular Pipe - 12.0 in	0.005	0.012	1.81	2.83	431.00	430.93	433.50	434.00	431.58	431.50	3.82
RG-3	DB-5	38.0	Circular Pipe - 12.0 in	0.005	0.012	1.96	2.73	426.80	426.61	431.25	434.25	429.85	429.75	2.50
RG-2	DB-7	17.0	Circular Pipe - 12.0 in	0.005	0.012	1.20	2.81	430.80	430.71	435.00	435.34	431.26	431.17	3.44
RG-7	I-7	67.0	Circular Pipe - 12.0 in	0.005	0.012	0.93	2.71	434.00	433.67	437.75	438.50	434.41	434.08	3.13
MH-15	MH-20 Outfall to Exist Pipe	76.0	Circular Pipe - 24.0 in	0.005	0.012	15.00	17.33	424.90	424.52	431.50	431.50	426.34	425.92	6.21
MH-2	MH-1	100.0	Circular Pipe - 24.0 in	0.005	0.012	19.91	17.33	423.33	422.83	430.10	430.00	426.07	425.41	6.34
RD-8		13.0	Circular Pipe - 8.0 in	0.005	0.012	1.08	0.96	430.86	430.79	435.00	435.00	435.29	435.20	3.10
		24.0	Circular Pipe - 8.0 in	0.005	0.012	1.08	0.93	430.79	430.67	435.00	435.00	435.20	435.04	3.10
		156.0	Circular Pipe - 12.0 in	0.005	0.012	1.08	2.73	430.67	429.89	435.00	435.00	435.04	434.91	1.38
	RD-5	133.0	Circular Pipe - 12.0 in	0.005	0.012	1.86	2.74	429.89	429.22	435.00	435.00	434.91	434.61	2.36
		58.0	Circular Pipe - 15.0 in	0.005	0.012	5.48	4.95	427.42	427.13	435.00	435.00	429.62	429.27	4.47
	MH-3	45.0	Circular Pipe - 15.0 in	0.005	0.012	5.48	5.00	427.13	426.90	435.00	430.50	429.27	428.99	4.47
RD-1		176.0	Circular Pipe - 8.0 in	0.009	0.012	0.77	1.21	433.00	431.50	435.00	434.00	433.42	431.89	3.67
	MH-3	64.0	Circular Pipe - 8.0 in	0.063	0.012	0.77	3.27	431.50	427.50	434.00	430.50	431.92	428.99	7.67
RD-7		52.0	Circular Pipe - 12.0 in	0.010	0.012	0.77	3.78	433.00	432.50	435.00	435.00	434.98	434.96	0.99
		113.0	Circular Pipe - 12.0 in	0.009	0.012	0.77	3.63	432.50	431.50	435.00	435.00	434.96	434.91	0.99
RD-6		51.0	Circular Pipe - 12.0 in	0.020	0.012	0.81	5.40	434.00	433.00	436.00	435.00	434.66	434.66	4.94
	RD-5	113.0	Circular Pipe - 12.0 in	0.013	0.012	0.81	4.45	433.00	431.50	435.00	435.00	434.66	434.61	1.03
RD-5		237.0	Circular Pipe - 12.0 in	0.004	0.012	4.01	2.45	429.22	428.26	435.00	435.00	434.40	431.85	5.11
		91.0	Circular Pipe - 12.0 in	0.005	0.012	1.76	2.74	427.96	427.50	430.00	430.00	429.43	429.24	2.24
		24.0	Circular Pipe - 10.0 in	0.005	0.012	1.76	1.68	428.08	427.96	430.00	430.00	429.56	429.43	3.22
		58.0	Circular Pipe - 8.0 in	0.005	0.012	1.09	0.93	427.79	427.50	435.00	435.00	430.12	429.72	3.12
		16.0	Circular Pipe - 15.0 in	0.005	0.012	5.48	4.95	427.50	427.42	435.00	435.00	429.72	429.62	4.47
		24.0	Circular Pipe - 12.0 in	0.005	0.012	1.76	2.73	427.50	427.38	430.00	430.00	429.24	429.19	2.24
		74.0	Circular Pipe - 12.0 in	0.005	0.012	1.76	2.73	427.38	427.01	430.00	430.00	429.19	429.04	2.24


100-yr

Conduit FlexTable: Villanova LAH Pipe / Node Report for Report (StormCAD - LAH.stc)

Upstream Node	Downstream Node	Length (ft)	Conduit Description	Slope (ft/ft)	Mannin g's n	Flow (Link) (ft³/s)	Full Capacity (ft³/s)	Upstream Invert Elevation (ft)	Downstream Invert Elevation (ft)	Elevation Ground (Start) (ft)	Elevation Ground (Stop) (ft)	Hydraulic Grade Line (In) (ft)	Hydraulic Grade Line (Out) (ft)	Average Velocity (ft/s)
		21.0	Circular Pipe - 12.0 in	0.005	0.012	1.37	2.79	427.49	427.38	430.00	430.00	429.20	429.17	1.74
	MH-3	143.0	Circular Pipe - 12.0 in	0.003	0.012	1.37	2.24	427.38	426.90	430.00	430.50	429.17	428.99	1.74
RG-1	I-5	35.0	Circular Pipe - 12.0 in	0.006	0.012	2.00	2.92	431.10	430.90	436.50	436.64	431.71	431.64	4.00
RD-10		130.0	Circular Pipe - 8.0 in	0.029	0.012	0.38	2.22	432.00	428.26	435.00	435.00	432.29	431.85	4.76
I-6	I-5	43.0	Circular Pipe - 18.0 in	0.005	0.012	1.67	8.14	433.00	432.78	437.37	436.64	433.49	433.24	3.62
I-5	I-4	83.0	Circular Pipe - 18.0 in	0.005	0.012	4.20	8.09	430.70	430.28	436.64	435.53	431.49	431.19	4.62
I-3	I-2	48.0	Circular Pipe - 18.0 in	0.005	0.012	5.82	8.05	429.42	429.18	435.00	433.78	430.37	430.11	4.96
I-2	I-1	77.0	Circular Pipe - 18.0 in	0.005	0.012	11.47	8.10	425.98	425.59	433.78	431.70	428.34	427.56	6.49
I-1	INF-1A	36.0	Circular Pipe - 18.0 in	0.005	0.012	12.74	8.05	425.40	425.22	431.70	430.80	427.15	426.70	7.21
DB-7	DB-6	76.0	Circular Pipe - 12.0 in	0.005	0.012	3.06	2.73	427.88	427.50	435.34	436.00	430.94	430.47	3.90
DB-6	DB-5	95.0	Circular Pipe - 12.0 in	0.005	0.012	3.06	2.74	427.30	426.82	436.00	434.25	430.35	429.75	3.90
DB-5	I-2	45.0	Circular Pipe - 12.0 in	0.005	0.012	5.03	2.76	426.41	426.18	434.25	433.78	429.43	428.67	6.40
RG-5	Cistern 1 Outlet	7.0	Circular Pipe - 12.0 in	0.006	0.012	2.17	2.92	425.30	425.26	428.75	430.00	426.89	426.86	2.77
RG-9	YD-2	16.0	Circular Pipe - 12.0 in	0.005	0.012	1.09	2.73	431.00	430.92	433.50	434.00	431.44	431.36	3.27
YD-1	YD-2	27.0	Circular Pipe - 12.0 in	0.005	0.012	0.31	2.78	430.70	430.56	434.00	434.00	430.93	430.78	2.33
DB-2	MH-22	13.0	Circular Pipe - 12.0 in	0.005	0.012	1.43	2.83	426.97	426.90	434.00	434.00	428.53	428.51	1.82
RG-6	I-18	26.0	Circular Pipe - 12.0 in	0.005	0.012	1.53	2.73	427.80	427.67	432.50	432.00	428.34	428.20	3.58
I-17	I-16	98.0	Circular Pipe - 18.0 in	0.051	0.012	4.81	25.70	426.70	421.70	430.60	425.40	427.54	422.57	11.15
I-19	MH-15	210.0	Circular Pipe - 24.0 in	0.005	0.012	15.00	17.33	426.15	425.10	434.50	431.50	427.59	426.64	6.21
MH-10	MH-8	20.0	Circular Pipe - 18.0 in	0.014	0.012	34.58	13.46	413.40	413.12	424.00	416.00	416.85	415.00	19.57
RD-3A		104.0	Circular Pipe - 8.0 in	0.005	0.012	1.09	0.93	428.31	427.79	435.00	435.00	430.84	430.12	3.12
RD-3B		94.0	Circular Pipe - 10.0 in	0.005	0.012	1.76	1.68	428.55	428.08	430.00	430.00	430.07	429.56	3.22
	Cistern 1B	22.0	Circular Pipe - 12.0 in	0.005	0.012	1.76	2.73	427.01	426.90	430.00	430.50	429.04	428.99	2.24
RD-2		102.0	Circular Pipe - 12.0 in	0.005	0.012	1.37	2.73	428.00	427.49	430.00	430.00	429.32	429.20	1.74
		164.0	Circular Pipe - 12.0 in	0.005	0.012	4.39	2.63	428.26	427.50	435.00	435.00	431.85	429.72	5.59
INF-1 Outfall	MH-10	4.0	Circular Pipe - 18.0 in	0.025	0.012	12.00	17.99	418.00	417.90	422.00	424.00	419.87	419.82	6.79
I-20	INF-3B	5.0	Circular Pipe - 12.0 in	0.020	0.012	0.43	5.46	416.10	416.00	423.75	423.75	417.96	417.96	0.54
RD-11		84.0	Circular Pipe - 8.0 in	0.024	0.012	0.80	2.02	433.00	431.00	435.00	433.25	433.42	431.29	5.46
		50.0	Circular Pipe - 8.0 in	0.020	0.012	0.80	1.85	431.00	430.00	433.25	432.50	431.42	430.31	5.11
		20.0	Circular Pipe - 12.0 in	0.005	0.012	0.80	2.73	416.00	415.90	432.50	418.25	416.50	416.50	3.02
RD-12	MH-20	113.0	Circular Pipe - 8.0 in	0.027	0.012	0.94	2.13	419.00	416.00	421.10	418.10	419.46	416.50	5.92
I-14		6.0	Circular Pipe - 18.0 in	0.005	0.013	0.58	7.43	434.75	434.72	436.50	435.00	435.03	435.00	2.50
YD-2	DB-2	177.0	Circular Pipe - 12.0 in	0.005	0.012	1.43	2.74	428.06	427.17	434.00	434.00	428.76	428.55	3.52


Profile Report

Engineering Profile - RG-10 to MH-21 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RD-3B to Cistern 1 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - I-19 to MH-20 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RD-8 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-7 to INF-1 (StormCAD - LAH.stc)




Profile Report
Engineering Profile - RG-4 to MH-1 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - YD-1 to DET-1 (StormCAD - LAH.stc)




Profile Report
Engineering Profile - RG-9 to YD-2 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - I-20 to INF-3 (StormCAD - LAH.stc)



Profile Report

Engineering Profile - I-12 to INF-3 (StormCAD - LAH.stc)




Elevation (ft)

Station (ft)


Profile Report

Engineering Profile - INF-1 to out (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-6 to out (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RD-12 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RD-11 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RD-1 to MH-3 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - YD-1 to MH-22 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - DET-1 OUT to MH-23 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-2 to DB-7 (StormCAD - LAH.stc)




Profile Report
Engineering Profile - RG-1 to I-5 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-4 to MH-2 (StormCAD - LAH.stc)




Profile Report


Engineering Profile - RG-5 to MH-2 (StormCAD - LAH.stc)



Profile Report
Engineering Profile - INF-1 Outlet to Outfall (StormCAD - LAH.stc)




Profile Report
Engineering Profile - I-14 to Outfall (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-8 to I-2 (StormCAD - LAH.stc)




Profile Report
Engineering Profile - RG-10 to MH-21 (StormCAD - LAH.stc)




Profile Report

Engineering Profile - RG-9 to MH-22 (StormCAD - LAH.stc)




Profile Report
Engineering Profile - RG-3 to DB-5 (StormCAD - LAH.stc)




OS - Inf-1

FIGURE 9.3
Riprap Apron Design, Minimum Tailwater Condition



DESIGN OF RIPRAP APRON OUTLET PROTECTION FROM A ROUND PIPE FLOWING FULL
 MINIMUM TAILWATER CONDITION ($T_w < 0.5$ DIAMETER)



Adapted from USDA - NRCS


NOTE: Do not extrapolate

Not to be used for Box Culverts

* For discharge velocities exceeding Maximum Allowable for Riprap indicated, increase d₅₀ stone size and/or provide velocity reduction device.

D_o = 30"
V = 17.12 ft/s
Q = 1224 cfs
L_a = 16'
W = 3(2.5') + 16' = 23.5'

FIGURE 9.3
Riprap Apron Design, Minimum Tailwater Condition



DESIGN OF RIPRAP APRON OUTLET PROTECTION FROM A ROUND PIPE FLOWING FULL
 MINIMUM TAILWATER CONDITION ($T_w < 0.5$ DIAMETER)

Adapted from USDA - NRCS

NOTE: Do not extrapolate

Not to be used for Box Culverts

* For discharge velocities exceeding Maximum Allowable for Riprap indicated, increase d_{50} stone size and/or provide velocity reduction device.

Handwritten calculations:
 $D_o = 12''$
 $V = \frac{Q}{A}$
 $Q = 0.57cf$
 $A = \frac{\pi \cdot (\pi)^2}{2} = 0.8835 ft^2$
 $V = 0.645 ft/s$
 $L_a = 8'$
 $W = 3(12) + 8 = 44'$

IX.

October 8, 2014

2014-3198-01

Villanova University
Maintenance Building 1st
Project Management
800 Lancaster Avenue
Villanova, PA 19085

Attention: Ms. Marilou Smith, LEED

**INFILTRATION TEST REPORT
LAH DEVELOPMENT
VILLANOVA UNIVERSITY**

Dear Ms. Smith:

Advanced GeoServices is pleased to present this summary of the infiltration testing performed for the proposed LAH Development at Villanova University. This work was performed in accordance with the infiltration testing scope of work included in our September 18, 2014 Service Agreement with Villanova University.

Infiltration testing was originally planned for a total of 40 locations, as shown on Drawings CU4.01, CU4.02, and CU4.03 developed by Voith & Mactavish Architects LLP and Robert A. M. Stern Architects LLP and included in the Request for Proposal. However, the two locations on the north side of Lancaster Avenue by the proposed future pedestrian bridge (TP-9 and TP-10) and the two locations within Pike Filed (TP-26 and TP-27) were eliminated from the present study. Thus, testing was performed at 36 locations.


Test Borings

To provide an indication of subsurface conditions, an initial boring was drilled at each infiltration test location to a depth of 7 feet to determine if any limiting zones (groundwater and/or rock) were present. No limiting zones were encountered at the test locations. The boring locations are shown on the attached drawings and logs of the borings are included in Appendix A.

Infiltration Testing

Infiltration testing was conducted at 36 locations via the Maryland Method (Maryland Stormwater Manual Appendix D.1) using test borings and 5-inch diameter casing. The test locations are shown on the attached drawings. The Maryland Method is an approved alternative for infiltration testing in the PADEP Manual (Appendix C) and provides the same measurements (infiltration rate in inches per hour). The tests were conducted on September 23, 24 and 26, 2014. The weather at the time of testing was generally partly sunny and warm (in the mid- 70's F). A description of the test method is provided below.

Ms. Marilou Smith
Villanova University
2014-3198-01
October 8, 2014
Page 2 of 2



- A secondary boring was drilled at each of the test locations adjacent to the initial boring used to characterize the subsurface conditions. The secondary boring was extended to the depth of 5 feet.
- A five-inch diameter PVC pipe was installed to the bottom of each borehole and the annular space around the pipe was backfilled with the drilling spoils.
- The pipes were filled with clean water to a depth of 24 inches above the bottom of the borehole (2 gallons of water) and allowed to pre-soak for 24 hours.
- Following the pre-soak, the pipes were refilled to a depth of 24 inches above the bottom of the borehole.
- Using a depth-to-water meter, the water levels in the pipes were monitored for a period of one hour and the data (time and depth) were recorded. This procedure (i.e., refilling to a depth of 24 inches above the bottom of the pipe and monitoring the water level for one hour) was repeated three additional times, for a total of four trials at each test location.

The field data is included in Appendix B and a summary of the results with the calculated infiltration rates are shown on the attached Table. The infiltration rate was calculated as the average of the last readings from the four trials at that location. Note that the listed infiltration rates are the calculated results; no factor of safety was applied.

The infiltration rates calculated in this report are estimates based upon the conditions encountered at the test locations and the depths of the testing. The actual average infiltration rate for each stormwater feature will depend upon the soil types and soil densities encountered throughout the bottom of the feature.

We appreciate this opportunity to be of service to you. If you have any questions regarding the contents of this report, please contact us.

Very truly yours,

ADVANCED GEOSERVICES CORP.


A handwritten signature in cursive script, appearing to read 'Paul F. Marano'.

Paul F. Marano, P.E.
Project Consultant

PFM:kk

Attachments

cc: A. Tweedie (Nave Newell)



TABLE

VILLANOVA UNIVERSITY LAH DEVELOPMENT
INFILTRATION TESTING RESULTS

Location	Test Depth (feet)	Test Elev. (feet)	Soil Type	Infiltration Rate (in/hr)
TP-1	5	400	silty fine sand	0.36
TP-2	5	402.5	silty coarse to fine sand	0.27
TP-3	5	409.5	silty coarse to fine sand	0.12
TP-4	5	414.25	silty coarse to fine sand	1.14
TP-5	5	418.25	silty coarse to fine sand	0.90
TP-6	5	430.5	silty fine sand	0.12
TP-7	5	431.25	silty fine sand	0.30
TP-8	5	431.5	silty fine sand	0.12
TP-9	5			
TP-10	5			
TP-11	5	433.75	fine sandy silt *	0.18
TP-12	5	432.5	clayey silt *	4.05
TP-13	5	430.5	coarse to fine sand and gravel *	0.27
TP-14	5	428.5	silty fine sand	0.90
TP-15	5	427.5	silty coarse to fine sand and gravel *	11.70
TP-16	5	426	silty coarse to fine sand *	0.03
TP-17	5	424.5	silty coarse to fine sand and gravel *	12.84
TP-18	5	424.25	silty coarse to fine sand and gravel *	1.23
TP-19	5	428.5	coarse to fine sand and gravel *	0.48
TP-20	5	423.5	clayey silt *	12.69
TP-21	5	428.25	coarse to fine sand and gravel *	16.44
TP-22	5	430.25	silty fine sand	0.30
TP-23	5	430.5	silty coarse to fine sand *	0.33
TP-24	5	423.25	clayey silt	3.66
TP-25	5	422.5	silty coarse to fine sand and gravel *	0.75
TP-26	5			
TP-27	5			
TP-28	5	397.5	fine sandy silt with clay	0.33
TP-29	5	401.5	silty fine sand	0.09
TP-30	5	414	silty fine sand	0.60
TP-31	5	417	silty coarse to fine sand	0.72
TP-32	5	422	silty coarse to fine sand	0.87
TP-33	5	424.5	silty fine sand	0.90
TP-34	5	425.5	silty fine sand	1.00
TP-35	5	431.5	clayey silt w/ concrete fragments*	9.06
TP-36	5	431	clayey silt	1.86
TP-37	5	430	sand gravel and cobbles *	1.29
TP-38	5	430	silty fine sand	0.63
TP-39	5	429	silty coarse to fine sand and gravel *	1.32
TP-40	5	429	silty sand and gravel	1.44

* Fill Material

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-1
 September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
10:23	0	0	3.27	0.00	0	0	0
10:53	30	30	3.3	0.03	0.03	0.72	0.72
11:23	30	60	3.31	0.01	0.04	0.24	0.48

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
11:23	0	0	3.04	0.00	0	0	0
11:53	30	30	3.06	0.02	0.02	0.48	0.48
12:23	30	60	3.07	0.01	0.03	0.24	0.36

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:23	0	0	3.01	0.00	0	0	0
12:53	30	30	3.02	0.01	0.01	0.24	0.24
1:23	30	60	3.03	0.01	0.02	0.24	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:23	0	0	3	0.00	0	0	0
1:53	30	30	3.02	0.02	0.02	0.48	0.48
2:23	30	60	3.03	0.01	0.03	0.24	0.36

Test conducted in silty fine sand (elev. 400)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-2
 September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:22	0	0	2.72	0.00	0	0	0
10:52	30	30	2.73	0.01	0.01	0.24	0.24
11:22	30	60	2.74	0.01	0.02	0.24	0.24

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:22	0	0	2.74	0.00	0	0	0
11:52	30	30	2.75	0.01	0.01	0.24	0.24
12:22	30	60	2.76	0.01	0.02	0.24	0.24

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:22	0	0	2.76	0.00	0	0	0
12:52	30	30	2.78	0.02	0.02	0.48	0.48
1:22	30	60	2.78	0.00	0.02	0.00	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:22	0	0	2.78	0.00	0	0	0
1:52	30	30	2.8	0.02	0.02	0.48	0.48
2:22	30	60	2.81	0.01	0.03	0.24	0.36

Test conducted in silty coarse to fine sand (elev. 402.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-3
 September 23, 2014

Trial No. 1

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
10:20	0	0	2.82	0.00	0	0	0
10:50	30	30	2.84	0.02	0.02	0.48	0.48
11:20	30	60	2.84	0.00	0.02	0.00	0.24

Trial No. 2

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
11:20	0	0	2.84	0.00	0	0	0
11:50	30	30	2.85	0.01	0.01	0.24	0.24
12:20	30	60	2.85	0.00	0.01	0.00	0.12

Trial No. 3

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
12:20	0	0	2.85	0.00	0	0	0
12:50	30	30	2.85	0.00	0.00	0.00	0.00
1:20	30	60	2.85	0.00	0.00	0.00	0.00

Trial No. 4

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
1:20	0	0	2.85	0.00	0	0	0
1:50	30	30	2.85	0.00	0.00	0.00	0.00
2:20	30	60	2.86	0.01	0.01	0.24	0.12

Test conducted in silty coarse to fine sand (elev.409.5)

- t_i = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- h_i = change in depth during interval
- H = cumulative change in depth
- l_i = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-4
 September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:19	0	0	3.05	0.00	0	0	0
10:49	30	30	3.11	0.06	0.06	1.44	1.44
11:19	30	60	3.18	0.07	0.13	1.68	1.56

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:19	0	0	3	0.00	0	0	0
11:49	30	30	3.06	0.06	0.06	1.44	1.44
12:19	30	60	3.11	0.05	0.11	1.20	1.32

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:19	0	0	3.02	0.00	0	0	0
12:49	30	30	3.06	0.04	0.04	0.96	0.96
1:19	30	60	3.09	0.03	0.07	0.72	0.84

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:19	0	0	3.01	0.00	0	0	0
1:49	30	30	3.05	0.04	0.04	0.96	0.96
2:19	30	60	3.08	0.03	0.07	0.72	0.84

Test conducted in silty coarse to fine sand (elev. 414.25)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-5

September 24, 2014

Trial No. 1

Time	ti	T	Depth	hi	H	li	l
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
7:35	0	0	3.03	0.00	0	0	0
8:05	30	30	3.06	0.03	0.03	0.72	0.72
8:35	30	60	3.1	0.04	0.07	0.96	0.84

Trial No. 2

Time	ti	T	Depth	hi	H	li	l
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
8:35	0	0	3.01	0.00	0	0	0
9:05	30	30	3.05	0.04	0.04	0.96	0.96
9:35	30	60	3.09	0.04	0.08	0.96	0.96

Trial No. 3

Time	ti	T	Depth	hi	H	li	l
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
9:35	0	0	2.95	0.00	0	0	0
10:05	30	30	2.98	0.03	0.03	0.72	0.72
10:35	30	60	3.02	0.04	0.07	0.96	0.84

Trial No. 4

Time	ti	T	Depth	hi	H	li	l
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
10:35	0	0	3.01	0.00	0	0	0
11:05	30	30	3.05	0.04	0.04	0.96	0.96
11:35	30	60	3.09	0.04	0.08	0.96	0.96

Test conducted in silty coarse to fine sand (elev. 418.25)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-6
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:30	0	0	2.97	0.00	0	0	0
8:00	30	30	2.97	0.00	0.00	0.00	0.00
8:30	30	60	2.98	0.01	0.01	0.24	0.12

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:30	0	0	2.98	0.00	0	0	0
9:00	30	30	2.98	0.00	0.00	0.00	0.00
9:30	30	60	2.99	0.01	0.01	0.24	0.12

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:30	0	0	2.99	0.00	0	0	0
10:00	30	30	3	0.01	0.01	0.24	0.24
10:30	30	60	3	0.00	0.01	0.00	0.12

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:30	0	0	3	0.00	0	0	0
11:00	30	30	3	0.00	0.00	0.00	0.00
11:30	30	60	3.01	0.01	0.01	0.24	0.12

Test conducted in silty fine sand (elev. 430.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-7
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:31	0	0	2.89	0.00	0	0	0
8:01	30	30	2.91	0.02	0.02	0.48	0.48
8:31	30	60	2.92	0.01	0.03	0.24	0.36

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:31	0	0	2.92	0.00	0	0	0
9:01	30	30	2.94	0.02	0.02	0.48	0.48
9:31	30	60	2.95	0.01	0.03	0.24	0.36

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:31	0	0	2.95	0.00	0	0	0
10:01	30	30	2.96	0.01	0.01	0.24	0.24
10:31	30	60	2.97	0.01	0.02	0.24	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:31	0	0	2.98	0.00	0	0	0
11:01	30	30	2.99	0.01	0.01	0.24	0.24
11:31	30	60	3	0.01	0.02	0.24	0.24

Test conducted in silty fine sand (elev. 431.25)

ti = duration of interval
 T = cumulative time
 Depth = distance from top of pipe to top of water level in pipe
 hi = change in depth during interval
 H = cumulative change in depth
 li = infiltration rate for interval
 I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-8
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:32	0	0	2.68	0.00	0	0	0
8:02	30	30	2.68	0.00	0.00	0.00	0.00
8:32	30	60	2.68	0.00	0.00	0.00	0.00

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:32	0	0	2.68	0.00	0	0	0
9:02	30	30	2.69	0.01	0.01	0.24	0.24
9:32	30	60	2.69	0.00	0.01	0.00	0.12

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:32	0	0	2.69	0.00	0	0	0
10:02	30	30	2.7	0.01	0.01	0.24	0.24
10:32	30	60	2.71	0.01	0.02	0.24	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:32	0	0	2.71	0.00	0	0	0
11:02	30	30	2.71	0.00	0.00	0.00	0.00
11:32	30	60	2.72	0.01	0.01	0.24	0.12

Test conducted in silty fine sand (elev. 431.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-11
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:29	0	0	3.07	0.00	0	0	0
7:59	30	30	3.07	0.00	0.00	0.00	0.00
8:29	30	60	3.08	0.01	0.01	0.24	0.12

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:29	0	0	2.99	0.00	0	0	0
8:59	30	30	3	0.01	0.01	0.24	0.24
9:29	30	60	3.01	0.01	0.02	0.24	0.24

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:29	0	0	3.01	0.00	0	0	0
9:59	30	30	3.02	0.01	0.01	0.24	0.24
10:29	30	60	3.03	0.01	0.02	0.24	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:29	0	0	3.01	0.00	0	0	0
10:59	30	30	3.01	0.00	0.00	0.00	0.00
11:29	30	60	3.02	0.01	0.01	0.24	0.12

Test conducted in fine sandy silt (Fill) (elev. 433.75)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-12
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:27	0	0	2.91	0.00	0	0	0
7:57	30	30	3.1	0.19	0.19	4.56	4.56
8:27	30	60	3.3	0.20	0.39	4.80	4.68

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:27	0	0	3.01	0.00	0	0	0
8:57	30	30	3.18	0.17	0.17	4.08	4.08
9:27	30	60	3.33	0.15	0.32	3.60	3.84

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:27	0	0	3.03	0.00	0	0	0
9:57	30	30	3.17	0.14	0.14	3.36	3.36
10:27	30	60	3.35	0.18	0.32	4.32	3.84

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:27	0	0	3.03	0.00	0	0	0
10:57	30	30	3.2	0.17	0.17	4.08	4.08
11:27	30	60	3.35	0.15	0.32	3.60	3.84

Test conducted in clayey silt (Fill) (elev. 432.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-13

September 26, 2014

Trial No. 1

Time	ti	T	Depth	hi	H	li	I
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
7:25	0	0	2.33	0.00	0	0	0
7:55	30	30	2.34	0.01	0.01	0.24	0.24
8:25	30	60	2.36	0.02	0.03	0.48	0.36

Trial No. 2

Time	ti	T	Depth	hi	H	li	I
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
8:25	0	0	2.36	0.00	0	0	0
8:55	30	30	2.36	0.00	0.00	0.00	0.00
9:25	30	60	2.38	0.02	0.02	0.48	0.24

Trial No. 3

Time	ti	T	Depth	hi	H	li	I
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
9:25	0	0	2.38	0.00	0	0	0
9:55	30	30	2.39	0.01	0.01	0.24	0.24
10:25	30	60	2.4	0.01	0.02	0.24	0.24

Trial No. 4

Time	ti	T	Depth	hi	H	li	I
	(min)	(min)	(ft)	(ft)	(ft)	(in/hr)	(in/hr)
10:25	0	0	2.4	0.00	0	0	0
10:55	30	30	2.41	0.01	0.01	0.24	0.24
11:25	30	60	2.42	0.01	0.02	0.24	0.24

Test conducted in coarse to fine sand and gravel (Fill) (elev. 430.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS
TP-14
September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:35	0	0	3.07	0.00	0	0	0
1:05	30	30	3.11	0.04	0.04	0.96	0.96
1:35	30	60	3.15	0.04	0.08	0.96	0.96

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:35	0	0	2.99	0.00	0	0	0
2:05	30	30	3.02	0.03	0.03	0.72	0.72
2:35	30	60	3.06	0.04	0.07	0.96	0.84

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
2:35	0	0	3.03	0.00	0	0	0
3:05	30	30	3.07	0.04	0.04	0.96	0.96
3:35	30	60	3.11	0.04	0.08	0.96	0.96

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
3:35	0	0	2.95	0.00	0	0	0
4:05	30	30	2.97	0.02	0.02	0.48	0.48
4:35	30	60	3.02	0.05	0.07	1.20	0.84

Test conducted in silty fine sand (elev. 428.50)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-15
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
	0	0	2.8	0.00	0	0	0
12:38	0	0	2.8	0.00	0	0	0
1:08	30	30	3.45	0.65	0.65	15.60	15.60
1:38	30	60	3.87	0.42	1.07	10.08	12.84

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
	0	0	2.93	0.00	0	0	0
1:38	0	0	2.93	0.00	0	0	0
2:08	30	30	3.53	0.60	0.60	14.40	14.40
2:38	30	60	3.89	0.36	0.96	8.64	11.52

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
	0	0	2.94	0.00	0	0	0
2:38	0	0	2.94	0.00	0	0	0
3:08	30	30	3.51	0.57	0.57	13.68	13.68
3:38	30	60	3.91	0.40	0.97	9.60	11.64

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
	0	0	3.04	0.00	0	0	0
3:38	0	0	3.04	0.00	0	0	0
4:08	30	30	3.55	0.51	0.51	12.24	12.24
4:38	30	60	3.94	0.39	0.90	9.36	10.80

Test conducted in silty coarse to fine sand and gravel (Fill) (elev. 427.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS
TP-16

September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
	0	0	2.57	0.00	0	0	0
12:40	0	0	2.57	0.00	0.00	0.00	0.00
1:10	30	30	2.57	0.00	0.00	0.00	0.00
1:40	30	60	2.57	0.00	0.00	0.00	0.00

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
	0	0	2.57	0.00	0	0	0
1:40	0	0	2.57	0.00	0.00	0.00	0.00
2:10	30	30	2.57	0.00	0.00	0.00	0.00
2:40	30	60	2.57	0.00	0.00	0.00	0.00

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
	0	0	2.57	0.00	0	0	0
2:40	0	0	2.57	0.00	0.01	0.24	0.24
3:10	30	30	2.58	0.01	0.01	0.00	0.12
3:40	30	60	2.58	0.00	0.01	0.00	0.12

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
	0	0	2.58	0.00	0	0	0
3:40	0	0	2.58	0.00	0.00	0.00	0.00
4:10	30	30	2.58	0.00	0.00	0.00	0.00
4:40	30	60	2.58	0.00	0.00	0.00	0.00

Test conducted in silty coarse to fine sand (Fill) (elev. 426)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-17

September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:42	0	0	2.89	0.00	0	0	0
1:12	30	30	3.84	0.95	0.95	22.80	22.80
1:42	30	60	4.1	0.26	1.21	6.24	14.52

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:42	0	0	3.07	0.00	0	0	0
2:12	30	30	3.64	0.57	0.57	13.68	13.68
2:42	30	60	3.93	0.29	0.86	6.96	10.32

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
2:42	0	0	3.04	0.00	0	0	0
3:12	30	30	3.72	0.68	0.68	16.32	16.32
3:42	30	60	4.09	0.37	1.05	8.88	12.60

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
3:42	0	0	3.02	0.00	0	0	0
4:12	30	30	3.78	0.76	0.76	18.24	18.24
4:42	30	60	4.18	0.40	1.16	9.60	13.92

Test conducted in silty coarse to fine sand and gravel (Fill) (elev. 424.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-18
September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:45	0	0	3.03	0.00	0	0	0
1:15	30	30	3.08	0.05	0.05	1.20	1.20
1:45	30	60	3.15	0.07	0.12	1.68	1.44

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:45	0	0	2.89	0.00	0	0	0
2:15	30	30	2.94	0.05	0.05	1.20	1.20
2:45	30	60	3.01	0.07	0.12	1.68	1.44

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
2:45	0	0	3.01	0.00	0	0	0
3:15	30	30	3.05	0.04	0.04	0.96	0.96
3:45	30	60	3.09	0.04	0.08	0.96	0.96

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
3:45	0	0	3.01	0.00	0	0	0
4:15	30	30	3.06	0.05	0.05	1.20	1.20
4:45	30	60	3.1	0.04	0.09	0.96	1.08

Test conducted in silty coarse to fine sand and gravel (Fill) (elev. 424.25)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-19
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:22	0	0	3.01	0.00	0	0	0
7:52	30	30	3.03	0.02	0.02	0.48	0.48
8:22	30	60	3.05	0.02	0.04	0.48	0.48

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:22	0	0	3	0.00	0	0	0
8:52	30	30	3.02	0.02	0.02	0.48	0.48
9:22	30	60	3.04	0.02	0.04	0.48	0.48

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:22	0	0	3	0.00	0	0	0
9:52	30	30	3.02	0.02	0.02	0.48	0.48
10:22	30	60	3.04	0.02	0.04	0.48	0.48

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:22	0	0	3.01	0.00	0	0	0
10:52	30	30	3.03	0.02	0.02	0.48	0.48
11:22	30	60	3.05	0.02	0.04	0.48	0.48

Test conducted in coarse to fine sand and gravel (Fill) (elev. 428.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-20
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:31	0	0	3.03	0.00	0	0	0
8:01	30	30	3.82	0.79	0.79	18.96	18.96
8:31	30	60	4.34	0.52	1.31	12.48	15.72

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:31	0	0	3.01	0.00	0	0	0
9:01	30	30	3.92	0.91	0.91	21.84	21.84
9:31	30	60	4.32	0.40	1.31	9.60	15.72

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:31	0	0	3.02	0.00	0	0	0
10:01	30	30	3.92	0.90	0.90	21.60	21.60
10:31	30	60	4.38	0.46	1.36	11.04	16.32

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:31	0	0	3.45	0.00	0	0	0
11:01	30	30	4.04	0.59	0.59	14.16	14.16
11:31	30	60	4.3	0.26	0.85	6.24	10.20

Test conducted in clayey silt (Fill) (elev. 423.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-21
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:20	0	0	2.94	0.00	0	0	0
7:50	30	30	3.75	0.81	0.81	19.44	19.44
8:20	30	60	4.29	0.54	1.35	12.96	16.20

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:20	0	0	3.03	0.00	0	0	0
8:50	30	30	4.18	1.15	1.15	27.60	27.60
9:20	30	60	4.51	0.33	1.48	7.92	17.76

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:20	0	0	3.04	0.00	0	0	0
9:50	30	30	4.05	1.01	1.01	24.24	24.24
10:20	30	60	4.38	0.33	1.34	7.92	16.08

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:20	0	0	3.07	0.00	0	0	0
10:50	30	30	4.08	1.01	1.01	24.24	24.24
11:20	30	60	4.38	0.30	1.31	7.20	15.72

Test conducted in coarse to fine sand and gravel (Fill) (elev. 428.25)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS
TP-22
September 26, 2014

Trial No. 1

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	I (in/hr)
7:18	0	0	3.01	0.00	0	0	0
7:48	30	30	3.02	0.01	0.01	0.24	0.24
8:18	30	60	3.03	0.01	0.02	0.24	0.24

Trial No. 2

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	I (in/hr)
8:18	0	0	3.03	0.00	0	0	0
8:48	30	30	3.04	0.01	0.01	0.24	0.24
9:18	30	60	3.06	0.02	0.03	0.48	0.36

Trial No. 3

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	I (in/hr)
9:18	0	0	3.01	0.00	0	0	0
9:48	30	30	3.02	0.01	0.01	0.24	0.24
10:18	30	60	3.03	0.01	0.02	0.24	0.24

Trial No. 4

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	I (in/hr)
10:18	0	0	3	0.00	0	0	0
10:48	30	30	3.02	0.02	0.02	0.48	0.48
11:18	30	60	3.03	0.01	0.03	0.24	0.36

Test conducted in silty fine sand (elev. 430.25)

t_i = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
h_i = change in depth during interval
H = cumulative change in depth
l_i = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-23
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
7:17	0	0	2.99	0.00	0	0	0
7:47	30	30	3.01	0.02	0.02	0.48	0.48
8:17	30	60	3.02	0.01	0.03	0.24	0.36

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
8:17	0	0	3.02	0.00	0	0	0
8:47	30	30	3.03	0.01	0.01	0.24	0.24
9:17	30	60	3.04	0.01	0.02	0.24	0.24

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
9:17	0	0	3.01	0.00	0	0	0
9:47	30	30	3.01	0.00	0.00	0.00	0.00
10:17	30	60	3.03	0.02	0.02	0.48	0.24

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
10:17	0	0	2.98	0.00	0	0	0
10:47	30	30	3.01	0.03	0.03	0.72	0.72
11:17	30	60	3.02	0.01	0.04	0.24	0.48

Test conducted in silty coarse to fine sand (Fill) (elev. 430.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-24
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
11:56	0	0	2.76	0.00	0	0	0
12:26	30	30	3.02	0.26	0.26	6.24	6.24
12:56	30	60	3.2	0.18	0.44	4.32	5.28

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:56	0	0	2.97	0.00	0	0	0
1:26	30	30	3.13	0.16	0.16	3.84	3.84
1:56	30	60	3.25	0.12	0.28	2.88	3.36

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:56	0	0	3.03	0.00	0	0	0
2:26	30	30	3.17	0.14	0.14	3.36	3.36
2:56	30	60	3.28	0.11	0.25	2.64	3.00

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
2:56	0	0	2.91	0.00	0	0	0
3:26	30	30	3.06	0.15	0.15	3.60	3.60
3:56	30	60	3.16	0.10	0.25	2.40	3.00

Test conducted in clayey silt (elev. 423.25)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-25
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
11:58	0	0	3	0.00	0	0	0
12:28	30	30	3.04	0.04	0.04	0.96	0.96
12:58	30	60	3.07	0.03	0.07	0.72	0.84

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:58	0	0	2.98	0.00	0	0	0
1:28	30	30	3.01	0.03	0.03	0.72	0.72
1:58	30	60	3.04	0.03	0.06	0.72	0.72

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:58	0	0	2.95	0.00	0	0	0
2:28	30	30	2.98	0.03	0.03	0.72	0.72
2:58	30	60	3.01	0.03	0.06	0.72	0.72

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
2:58	0	0	3.01	0.00	0	0	0
3:28	30	30	3.04	0.03	0.03	0.72	0.72
3:58	30	60	3.07	0.03	0.06	0.72	0.72

Test conducted in silty coarse to fine sand and gravel (Fill) (elev. 422.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-28
 September 23, 2014

Trial No. 1

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
10:06	0	0	3.06	0.00	0	0	0
10:36	30	30	3.08	0.02	0.02	0.48	0.48
11:06	30	60	3.1	0.02	0.04	0.48	0.48

Trial No. 2

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
11:06	0	0	3.01	0.00	0	0	0
11:36	30	30	3.02	0.01	0.01	0.24	0.24
12:06	30	60	3.03	0.01	0.02	0.24	0.24

Trial No. 3

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
12:06	0	0	3	0.00	0	0	0
12:36	30	30	3.02	0.02	0.02	0.48	0.48
1:06	30	60	3.03	0.01	0.03	0.24	0.36

Trial No. 4

Time	t _i (min)	T (min)	Depth (ft)	h _i (ft)	H (ft)	l _i (in/hr)	l (in/hr)
1:06	0	0	3.01	0.00	0	0	0
1:36	30	30	3.02	0.01	0.01	0.24	0.24
2:06	30	60	3.03	0.01	0.02	0.24	0.24

Test conducted in fine sandy silt with clay (elev. 397.5)

- t_i = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- h_i = change in depth during interval
- H = cumulative change in depth
- l_i = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-29
September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:07	0	0	2.64	0.00	0	0	0
10:37	30	30	2.64	0.00	0.00	0.00	0.00
11:07	30	60	2.65	0.01	0.01	0.24	0.12

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:07	0	0	2.65	0.00	0	0	0
11:37	30	30	2.65	0.00	0.00	0.00	0.00
12:07	30	60	2.66	0.01	0.01	0.24	0.12

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:07	0	0	2.66	0.00	0	0	0
12:37	30	30	2.66	0.00	0.00	0.00	0.00
1:07	30	60	2.66	0.00	0.00	0.00	0.00

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:07	0	0	2.66	0.00	0	0	0
1:37	30	30	2.66	0.00	0.00	0.00	0.00
2:07	30	60	2.67	0.01	0.01	0.24	0.12

Test conducted in silty fine sand (elev. 401.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS
TP-30
September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
10:10	0	0	3.05	0.00	0	0	0
10:40	30	30	3.07	0.02	0.02	0.48	0.48
11:10	30	60	3.1	0.03	0.05	0.72	0.60

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
11:10	0	0	2.97	0.00	0	0	0
11:40	30	30	3	0.03	0.03	0.72	0.72
12:10	30	60	3.03	0.03	0.06	0.72	0.72

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
12:10	0	0	3	0.00	0	0	0
12:40	30	30	3.03	0.03	0.03	0.72	0.72
1:10	30	60	3.05	0.02	0.05	0.48	0.60

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
1:10	0	0	2.99	0.00	0	0	0
1:40	30	30	3.01	0.02	0.02	0.48	0.48
2:10	30	60	3.03	0.02	0.04	0.48	0.48

Test conducted in silty fine sand (elev. 414)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-31
 September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:13	0	0	3.04	0.00	0	0	0
10:43	30	30	3.07	0.03	0.03	0.72	0.72
11:13	30	60	3.1	0.03	0.06	0.72	0.72

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:13	0	0	3.01	0.00	0	0	0
11:43	30	30	3.05	0.04	0.04	0.96	0.96
12:13	30	60	3.07	0.02	0.06	0.48	0.72

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:13	0	0	3.01	0.00	0	0	0
12:43	30	30	3.04	0.03	0.03	0.72	0.72
1:13	30	60	3.07	0.03	0.06	0.72	0.72

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:13	0	0	3	0.00	0	0	0
1:43	30	30	3.03	0.03	0.03	0.72	0.72
2:13	30	60	3.06	0.03	0.06	0.72	0.72

Test conducted in silty coarse to fine sand (elev. 417)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-32
 September 23, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:14	0	0	3.03	0.00	0	0	0
10:44	30	30	3.07	0.04	0.04	0.96	0.96
11:14	30	60	3.1	0.03	0.07	0.72	0.84

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:14	0	0	3.02	0.00	0	0	0
11:44	30	30	3.05	0.03	0.03	0.72	0.72
12:14	30	60	3.07	0.02	0.05	0.48	0.60

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:14	0	0	3	0.00	0	0	0
12:44	30	30	3.04	0.04	0.04	0.96	0.96
1:14	30	60	3.06	0.02	0.06	0.48	0.72

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:14	0	0	3	0.00	0	0	0
1:44	30	30	3.03	0.03	0.03	0.72	0.72
2:14	30	60	3.05	0.02	0.05	0.48	0.60

Test conducted in silty coarse to fine sand (elev. 422)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-33
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
7:26	0	0	3	0.00	0	0	0
7:56	30	30	3.04	0.04	0.04	0.96	0.96
8:26	30	60	3.08	0.04	0.08	0.96	0.96

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
8:26	0	0	3.03	0.00	0	0	0
8:56	30	30	3.06	0.03	0.03	0.72	0.72
9:26	30	60	3.1	0.04	0.07	0.96	0.84

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
9:26	0	0	3	0.00	0	0	0
9:56	30	30	3.03	0.03	0.03	0.72	0.72
10:26	30	60	3.07	0.04	0.07	0.96	0.84

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
10:26	0	0	3	0.00	0	0	0
10:56	30	30	3.05	0.05	0.05	1.20	1.20
11:26	30	60	3.08	0.03	0.08	0.72	0.96

Test conducted in silty fine sand (elev. 424.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-34
 September 24, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
7:27	0	0	3.03	0.00	0	0	0
7:57	30	30	3.07	0.04	0.04	0.96	0.96
8:27	30	60	3.1	0.03	0.07	0.72	0.84

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
8:27	0	0	3.01	0.00	0	0	0
8:57	30	30	3.05	0.04	0.04	0.96	0.96
9:27	30	60	3.08	0.03	0.07	0.72	0.84

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
9:27	0	0	2.97	0.00	0	0	0
9:57	30	30	3	0.03	0.03	0.72	0.72
10:27	30	60	3.02	0.02	0.05	0.48	0.60

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	l (in/hr)
10:27	0	0	3	0.00	0	0	0
10:57	30	30	3.04	0.04	0.04	0.96	0.96
11:27	30	60	3.07	0.03	0.07	0.72	0.84

Test conducted in silty fine sand (elev. 425.5)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- l = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-35
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:08	0	0	2.95	0.00	0	0	0
7:38	30	30	3.59	0.64	0.64	15.36	15.36
8:08	30	60	3.81	0.22	0.86	5.28	10.32

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:08	0	0	3.05	0.00	0	0	0
8:38	30	30	3.53	0.48	0.48	11.52	11.52
9:08	30	60	3.76	0.23	0.71	5.52	8.52

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:08	0	0	3.03	0.00	0	0	0
9:38	30	30	3.51	0.48	0.48	11.52	11.52
10:08	30	60	3.77	0.26	0.74	6.24	8.88

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:08	0	0	3.08	0.00	0	0	0
10:38	30	30	3.54	0.46	0.46	11.04	11.04
11:08	30	60	3.79	0.25	0.71	6.00	8.52

Test conducted in clayey silt w/concrete fragments (Fill) (elev. 431.5)

ti = duration of interval
T = cumulative time
Depth = distance from top of pipe to top of water level in pipe
hi = change in depth during interval
H = cumulative change in depth
li = infiltration rate for interval
I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-36
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:10	0	0	2.74	0.00	0	0	0
7:40	30	30	2.85	0.11	0.11	2.64	2.64
8:10	30	60	2.94	0.09	0.20	2.16	2.40

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:10	0	0	2.94	0.00	0	0	0
8:40	30	30	3.02	0.08	0.08	1.92	1.92
9:10	30	60	3.09	0.07	0.15	1.68	1.80

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:10	0	0	3	0.00	0	0	0
9:40	30	30	3.06	0.06	0.06	1.44	1.44
10:10	30	60	3.13	0.07	0.13	1.68	1.56

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:10	0	0	3.05	0.00	0	0	0
10:40	30	30	3.13	0.08	0.08	1.92	1.92
11:10	30	60	3.19	0.06	0.14	1.44	1.68

Test conducted in clayey silt (elev. 431)

ti = duration of interval
 T = cumulative time
 Depth = distance from top of pipe to top of water level in pipe
 hi = change in depth during interval
 H = cumulative change in depth
 li = infiltration rate for interval
 I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS

TP-37

September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:11	0	0	3.05	0.00	0	0	0
7:41	30	30	3.1	0.05	0.05	1.20	1.20
8:11	30	60	3.14	0.04	0.09	0.96	1.08

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:11	0	0	2.99	0.00	0	0	0
8:41	30	30	3.05	0.06	0.06	1.44	1.44
9:11	30	60	3.11	0.06	0.12	1.44	1.44

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:11	0	0	3	0.00	0	0	0
9:41	30	30	3.06	0.06	0.06	1.44	1.44
10:11	30	60	3.11	0.05	0.11	1.20	1.32

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:11	0	0	3.01	0.00	0	0	0
10:41	30	30	3.07	0.06	0.06	1.44	1.44
11:11	30	60	3.12	0.05	0.11	1.20	1.32

Test conducted in sand gravel and cobbles (Fill) (elev. 430)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-38
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
7:13	0	0	3.06	0.00	0	0	0
7:43	30	30	3.1	0.04	0.04	0.96	0.96
8:13	30	60	3.13	0.03	0.07	0.72	0.84

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
8:13	0	0	2.99	0.00	0	0	0
8:43	30	30	3.01	0.02	0.02	0.48	0.48
9:13	30	60	3.04	0.03	0.05	0.72	0.60

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
9:13	0	0	2.93	0.00	0	0	0
9:43	30	30	2.96	0.03	0.03	0.72	0.72
10:13	30	60	2.97	0.01	0.04	0.24	0.48

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
10:13	0	0	2.97	0.00	0	0	0
10:43	30	30	3.02	0.05	0.05	1.20	1.20
11:13	30	60	3.02	0.00	0.05	0.00	0.60

Test conducted in silty fine sand (elev. 430)

ti = duration of interval
 T = cumulative time
 Depth = distance from top of pipe to top of water level in pipe
 hi = change in depth during interval
 H = cumulative change in depth
 li = infiltration rate for interval
 I = cumulative infiltration rate

Villanova University LAH Development
 INFILTRATION TESTING RESULTS
 TP-39
 September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:53	0	0	2.95	0.00	0	0	0
12:23	30	30	3.01	0.06	0.06	1.44	1.44
12:53	30	60	3.06	0.05	0.11	1.20	1.32

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:53	0	0	3.02	0.00	0	0	0
1:23	30	30	3.07	0.05	0.05	1.20	1.20
1:53	30	60	3.13	0.06	0.11	1.44	1.32

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:53	0	0	2.99	0.00	0	0	0
2:23	30	30	3.04	0.05	0.05	1.20	1.20
2:53	30	60	3.1	0.06	0.11	1.44	1.32

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
2:53	0	0	2.98	0.00	0	0	0
3:23	30	30	3.04	0.06	0.06	1.44	1.44
3:53	30	60	3.09	0.05	0.11	1.20	1.32

Test conducted in silty coarse to fine sand and gravel (elev. 429)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University LAH Development
INFILTRATION TESTING RESULTS
TP-40
September 26, 2014

Trial No. 1

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
11:54	0	0	2.99	0.00	0	0	0
12:24	30	30	3.07	0.08	0.08	1.92	1.92
12:54	30	60	3.13	0.06	0.14	1.44	1.68

Trial No. 2

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
12:54	0	0	3.02	0.00	0	0	0
1:24	30	30	3.08	0.06	0.06	1.44	1.44
1:54	30	60	3.14	0.06	0.12	1.44	1.44

Trial No. 3

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
1:54	0	0	3.02	0.00	0	0	0
2:24	30	30	3.08	0.06	0.06	1.44	1.44
2:54	30	60	3.14	0.06	0.12	1.44	1.44

Trial No. 4

Time	ti (min)	T (min)	Depth (ft)	hi (ft)	H (ft)	li (in/hr)	I (in/hr)
2:54	0	0	2.97	0.00	0	0	0
3:24	30	30	3.02	0.05	0.05	1.20	1.20
3:54	30	60	3.07	0.05	0.10	1.20	1.20

Test conducted in silty sand and gravel (elev. 429)

- ti = duration of interval
- T = cumulative time
- Depth = distance from top of pipe to top of water level in pipe
- hi = change in depth during interval
- H = cumulative change in depth
- li = infiltration rate for interval
- I = cumulative infiltration rate

Villanova University
 CIDC Development
 1000 East Main Avenue
 Villanova, PA 19382

**VMA
 RAMSA**

ARCHITECT OF RECORD
 300 N. Market Street, Suite 200
 Philadelphia, PA 19106
 Phone: 215-644-4444
 www.vma-ramsa.com

DESIGN ARCHITECT
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

CIVIL ENGINEER
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

STRUCTURAL ENGINEER
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

MECHANICAL ENGINEER
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

ELECTRICAL ENGINEER
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

LANDSCAPE ARCHITECT
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu


ADDRESS CONSULTANT
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu

PERMITS CONSULTANT
 1000 East Main Avenue, Suite 200
 Villanova, PA 19382
 Phone: 610-853-1100
 www.villanova.edu


CONDITIONAL USE PLAN
 NOT FOR CONSTRUCTION
 Revision August 15, 2014
 Date May 2, 2014
 Title Conditional Use Plan
 Scale 1" = 4'-0"
 Drawn By HRF/JDW

CU4.02

Copyright © 2014 by Villanova University



GRAPHIC SCALE
 1" = 40' 0"



CU4.02_ConditionalUsePlan_R14a.dwg (2014.08.15.15:56:10)

Villanova University
 CICO Development
 Lancaster and Ithaca Avenues
 Villanova, PA 19385

**VMA
 RAMSA**

ARCHITECT OF RECORD
 1471 York Road, 1st Fl., Villanova
 Villanova, PA 19385
 Phone: 610-855-1100
 Fax: 610-855-1339
 www.villanova.edu/vma

DESIGN ARCHITECT
 450 York Road, 1st Fl.
 Villanova, PA 19385
 Phone: 610-855-1100
 Fax: 610-855-1339
 www.villanova.edu

CIVIL ENGINEER
 220 West 12th Street, Rm. 1109
 York, PA 17403
 Phone: 717-760-1234
 Fax: 717-760-1234
 www.pennstate.edu

STRUCTURAL ENGINEER
 One East Lincoln Avenue, Bldg. 403
 Goshen, PA 19330
 Phone: 610-271-4322
 Fax: 610-271-4322
 www.pennstate.edu

MECHANICAL ENGINEER
 411 E. 10th Street, 2nd Fl.
 York, PA 17403
 Phone: 717-494-7121
 Fax: 717-494-7121
 www.pennstate.edu



LANDSCAPE ARCHITECT
 200 West 12th Street, Rm. 1109
 York, PA 17403
 Phone: 717-760-1234
 Fax: 717-760-1234
 www.pennstate.edu

ACQUISITION CONSULTANT
 Architects Inc.
 200 West 12th Street, Rm. 1109
 York, PA 17403
 Phone: 717-760-1234
 Fax: 717-760-1234
 www.pennstate.edu

GENERAL CONTRACTOR
 200 West 12th Street, Rm. 1109
 York, PA 17403
 Phone: 717-760-1234
 Fax: 717-760-1234
 www.pennstate.edu

DATE: August 2, 2014
 TITLE: Conceptual Site Plan
 SCALE: 1" = 40'

CU4.03




APPENDIX A

LOG OF TEST BORING

TEST BORING TP-1

DATE: 9/22/14
 PROJECT: Villanova University LAH Project
 BORING LOCATION: See Drawings
 DRILLING METHOD: Hollow Stem Auger
 DRILLING COMPANY: Earth Core Services
 WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
 SURFACE ELEVATION: 405.0 ft.
 CHECKED BY: PFM
 DRILLER: J. Swope
 INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
405 — 0 400 — 5 395 — 10 390 — 15 385 — 20 380 — 25 375 — 30 370 — 35		Topsoil with root mat. Medium dense moist gray-brown silty fine SAND, trace clay.	405 0.2 404.8		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	7.0 398		

LOG OF TEST BORING

TEST BORING TP-2

DATE: 9/22/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRAWING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 407.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Topsoil with grass root mat.	407.5		
		Medium dense moist orange-brown silty fine SAND.	0.3 407.2		
		Medium dense moist gray-brown silty coarse to fine SAND, trace gravel.	4.0 403.5		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	7.0 400.5		

LOG OF TEST BORING

TEST BORING TP-3

DATE: 9/22/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 414.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Topsoil with grass root mat. 414.5 0.2 Medium dense moist brown silty coarse to fine SAND, trace gravel. 414.3 2.0 (FILL) 412.5 Medium dense moist brown silty coarse to fine SAND. 7.0			
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT. 407.5			

LOG OF TEST BORING

TEST BORING TP-4

DATE: 9/22/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: None Encountered


PROJECT NO.: 2014-3198-01

SURFACE ELEVATION: 419.3 ft.

CHECKED BY: PFM

DRILLER: J. Swope

INSPECTOR: M. Simonds



ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
0		Aggregate SAND and GRAVEL.	419.3		
5		Medium dense moist brown silty fine SAND, trace gravel.	418.8		
10		Medium dense to dense moist gray-brown silty coarse to fine SAND.	7.0		
15		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	412.3		
20					
25					
30					
35					

LOG OF TEST BORING

TEST BORING TP-5

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 423.3 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Topsoil with grass root mat. 423.3 Medium dense to dense moist brown silty coarse to fine SAND. 423.1 Completion Depth = 7 feet 7.0 END OF TEST BORING @ 7.0 FT. 416.3			

LOG OF TEST BORING

TEST BORING TP-6

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
D. BORING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 435.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>435</p> <p>0</p> <p>5</p> <p>10</p> <p>15</p> <p>20</p> <p>25</p> <p>30</p> <p>35</p> <p>400</p> </div>  </div>		Topsoil with root mat. Medium dense moist brown silty fine SAND.	<p>435.5</p> <p>0.2</p> <p>435.3</p>		
		Dense moist brown silty coarse to fine SAND with gravel. Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	<p>6.0</p> <p>429.5</p> <p>7.0</p> <p>428.5</p>		

LOG OF TEST BORING

TEST BORING TP-7

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: None Encountered

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 436.3 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds



ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Topsoil root mat. 436.3 Medium dense to dense moist brown silty fine SAND. 0.2 436.1			
		Completion Depth = 5 feet 5.0 END OF TEST BORING @ 5.0 FT. 431.3			

LOG OF TEST BORING

TEST BORING TP-8

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 436.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Topsoil with grass root mat. Medium dense to dense moist brown silty fine SAND.	436.5 0.3 436.2		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	7.0 429.5		

LOG OF TEST BORING

TEST BORING TP-11

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 438.8 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. 438.8 Aggregate base course. 0.4 438.4 Medium dense moist brown fine sandy SILT. 0.7 (FILL) 438.1 3.0 Medium dense moist gray-brown fine sandy SILT, 435.8 trace metal debris. (FILL) 7.0 431.8			
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-12

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 437.5 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds



ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">0</div> <div style="margin-top: 10px;">435</div> <div style="margin-top: 10px;">5</div> <div style="margin-top: 10px;">430</div> <div style="margin-top: 10px;">10</div> <div style="margin-top: 10px;">425</div> <div style="margin-top: 10px;">15</div> <div style="margin-top: 10px;">420</div> <div style="margin-top: 10px;">20</div> <div style="margin-top: 10px;">415</div> <div style="margin-top: 10px;">25</div> <div style="margin-top: 10px;">410</div> <div style="margin-top: 10px;">30</div> <div style="margin-top: 10px;">405</div> <div style="margin-top: 10px;">35</div> <div style="margin-top: 10px;">400</div> </div>		Asphalt. 437.5 Aggregate base course. 0.4 437.1 Medium dense moist brown silty coarse to fine SAND. 0.9 436.6 (FILL) 4.0 Soft gray clayey SILT with wood, brick, and metal debris. 433.5 5.5 (FILL) 432 Soft dark gray black organic SILT. 7.0 430.5 Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-13

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 435.5 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
435 0 430 5 425 10 420 15 415 20 410 25 405 30 400 35	 	Asphalt. Aggregate base course. Medium dense moist gray coarse to fine SAND and GRAVEL, trace cobbles. (FILL) Medium dense moist gray micaceous silty coarse to fine SAND. (FILL) Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	435.5 0.4 435.1 0.8 434.7 5.0 430.5 7.0 428.5		

LOG OF TEST BORING

TEST BORING TP-14

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 433.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. 433.5 Aggregate base course. 432.8 Medium dense moist gray-brown micaceous silty fine SAND. 432.6	433.5 0.7 432.8 0.9 432.6 7.0 426.5		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-15

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 432.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1;"> <p>0</p> <p>430</p> <p>5</p> <p>425</p> <p>10</p> <p>420</p> <p>15</p> <p>415</p> <p>20</p> <p>410</p> <p>25</p> <p>405</p> <p>30</p> <p>400</p> <p>35</p> <p>395</p> </div> </div>		<p>Asphalt. 432.5</p> <p>Aggregate base course. 0.5</p> <p>Loose gray-brown silty coarse to fine SAND and GRAVEL, trace concrete fragments. (FILL) 432, 0.9, 431.6</p> <p>Completion Depth = 7 feet 7.0</p> <p>END OF TEST BORING @ 7.0 FT. 425.5</p>			

LOG OF TEST BORING

TEST BORING TP-16

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 431.0 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
0 430 5 425 10 420 15 415 20 410 25 405 30 400 35 395		Asphalt. Aggregate base course. Medium dense moist brown silty coarse to fine SAND, trace gravel. (FILL) Concrete rubble. Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	431 0.4 430.6 0.8 430.2 5.0 426 7.0 424		

LOG OF TEST BORING

TEST BORING TP-17

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 429.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt Aggregate base course. Loose moist brown silty coarse to fine SAND and GRAVEL, trace glass fragments. (FILL)	429.5 0.3 429.2 0.6 428.9 7.0 422.5		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-18

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 429.3 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. 429.3 Aggregate base course. 429.1 Loose, very moist silty coarse to fine SAND and GRAVEL, trace metal debris and batteries. (FILL) 428.5 Completion Depth = 7 feet 7.0 END OF TEST BORING @ 7.0 FT. 422.3			

LOG OF TEST BORING

TEST BORING TP-19

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 433.5 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;">  <div style="margin-left: 10px;"> <p>0</p> <p>430</p> <p>5</p> <p>425</p> <p>10</p> <p>420</p> <p>15</p> <p>415</p> <p>20</p> <p>410</p> <p>25</p> <p>405</p> <p>30</p> <p>400</p> <p>35</p> </div> </div>		Asphalt. 433.5 0.5 Aggregate base course. 433 Loose to medium dense moist brown silty coarse to fine SAND. 432.6 (FILL) 4.0 Brown coarse to fine SAND and GRAVEL with concrete rubble. 429.5 6.0 Medium dense brown silty fine SAND. 427.5 7.0 Completion Depth = 7 feet 426.5 END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-20

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 428.5 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. Aggregate base course. Medium dense moist brown silty SAND. (FILL) Soft very moist gray clayey SILT, trace wood debris and ash. (FILL) Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	428.5 0.5 428 1.0 427.5 4.0 424.5 7.0 421.5		

LOG OF TEST BORING

TEST BORING TP-21

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services



WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 433.3 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		<p>Asphalt. 433.3</p> <p>Aggregate base course. 0.3</p> <p>Medium dense moist brown coarse to fine SAND and aggregate GRAVEL. 433</p> <p>(FILL) 0.6</p> <p>432.7</p> <p>5.0</p> <p>Soft very moist gray clayey SILT. 428.3</p> <p>(FILL)</p> <p>7.0</p> <p>Completion Depth = 7 feet 426.3</p> <p>END OF TEST BORING @ 7.0 FT.</p>			

LOG OF TEST BORING

TEST BORING TP-22

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services


WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 435.3 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>435</p><p>0</p><p>430</p><p>5</p><p>425</p><p>10</p><p>415</p><p>20</p><p>410</p><p>25</p><p>405</p><p>30</p><p>400</p><p>35</p> </div>  </div>		<p>Asphalt. 435.3</p> <p>Aggregate base course. 0.4</p> <p>Medium dense moist brown silty fine SAND. 434.9</p> <p style="text-align: right;">0.7</p> <p style="text-align: right;">434.6</p>			
		<p style="text-align: right;">7.0</p> <p>Completion Depth = 7 feet 428.3</p> <p>END OF TEST BORING @ 7.0 FT.</p>			

LOG OF TEST BORING

TEST BORING TP-23

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 435.5 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
435 		Asphalt. Medium dense moist brown silty coarse to fine SAND, trace cobbles. (FILL)	435.5 0.3 435.2 7.0 428.5		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.			

LOG OF TEST BORING

TEST BORING TP-24

DATE: 9/25/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 428.3 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">0</div> <div style="margin-bottom: 10px;">425</div> <div style="margin-bottom: 10px;">5</div> <div style="margin-bottom: 10px;">420</div> <div style="margin-bottom: 10px;">10</div> <div style="margin-bottom: 10px;">415</div> <div style="margin-bottom: 10px;">15</div> <div style="margin-bottom: 10px;">410</div> <div style="margin-bottom: 10px;">20</div> <div style="margin-bottom: 10px;">405</div> <div style="margin-bottom: 10px;">25</div> <div style="margin-bottom: 10px;">400</div> <div style="margin-bottom: 10px;">30</div> <div style="margin-bottom: 10px;">395</div> <div style="margin-bottom: 10px;">35</div> </div>		<p>Asphalt. 428.3</p> <p>Aggregate base course. 0.4 427.9</p> <p>Dense moist brown-gray silty SAND and GRAVEL with cobbles. 0.8 427.5</p> <p style="text-align: center;">(FILL)</p> <p>Stiff moist light brown clayey SILT. 4.5 423.8</p> <p style="text-align: right;">7.0 421.3</p> <p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>			

LOG OF TEST BORING

TEST BORING TP-25

DATE: 9/25/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 427.5 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds



ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. Aggregate base course. Dense moist brown silty coarse to fine SAND and GRAVEL, trace cobbles. (FILL)	427.5 0.4 427.1 0.8 426.7		
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	7.0 420.5		

LOG OF TEST BORING

TEST BORING TP-28

DATE: 9/23/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 402.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		<p>Grass root mat.</p> <p>Medium dense moist light brown silty fine SAND, trace gravel.</p> <p style="text-align: center;">(FILL)</p> <p>Medium dense moist fine sandy SILT with clay.</p> <p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>	<p>402.5</p> <p>0.1</p> <p>402.4</p> <p>4.0</p> <p>398.5</p> <p>7.0</p> <p>395.5</p>		

LOG OF TEST BORING

TEST BORING TP-29

DATE: 9/22/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 406.5 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		<p>Topsoil with root mat.</p> <p>Aggregate GRAVEL and COBBLES.</p> <p style="text-align: center;">(FILL)</p> <p>Medium dense moist brown silty SAND, trace gravel.</p>	<p>406.5</p> <p>0.1</p> <p>406.4</p> <p>0.8</p> <p>405.7</p>		
		<p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>	<p>7.0</p> <p>399.5</p>		

LOG OF TEST BORING

TEST BORING TP-30

DATE: 9/22/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 419.0 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1;"> </div> </div>		Grass root mat. 419 Medium dense moist brown silty fine SAND. 0.2 418.8			
		Completion Depth = 7 feet 7.0 END OF TEST BORING @ 7.0 FT. 412			

LOG OF TEST BORING

TEST BORING TP-31

DATE: 9/22/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 422.0 ft.
CHECKED BY: PFM
DRILLER: J. Swope
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1; padding-left: 10px;"> <p>Topsoil with grass root mat. 422 0.3</p> <p>Medium dense moist brown silty coarse to fine SAND. 421.7</p> </div> </div>	<div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1; padding-left: 10px;"> <p>422</p> <p>0.3</p> <p>421.7</p> </div> </div>	<p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>	<p>7.0</p> <p>415</p>		

LOG OF TEST BORING

TEST BORING TP-32

DATE: 9/22/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 427.0 ft.

CHECKED BY: PFM

DRILLER: J. Swope

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		<p>Topsoil with grass root mat. 427</p> <p>Medium dense moist brown silty coarse to fine SAND. 426.7</p>	<p>427</p> <p>0.3</p> <p>426.7</p>		
		<p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>	<p>7.0</p> <p>420</p>		

LOG OF TEST BORING

TEST BORING TP-33

DATE: 9/23/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01

SURFACE ELEVATION: 429.5 ft.

CHECKED BY: PFM

DRILLER: J. Swope

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		<p>Topsoil with grass root mat. 429.5</p> <p>Medium dense moist brown silty SAND. (FILL) 429.3</p> <p>Medium dense to dense silty fine SAND. 426.5</p> <p>Completion Depth = 7 feet 7.0</p> <p>END OF TEST BORING @ 7.0 FT. 422.5</p>			

LOG OF TEST BORING

TEST BORING TP-34

DATE: 9/23/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services


WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 430.5 ft.

CHECKED BY: PFM

DRILLER: J. Swope

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">430</div> <div style="margin-bottom: 10px;">0</div> <div style="margin-bottom: 10px;">425</div> <div style="margin-bottom: 10px;">5</div> <div style="margin-bottom: 10px;">420</div> <div style="margin-bottom: 10px;">10</div> <div style="margin-bottom: 10px;">410</div> <div style="margin-bottom: 10px;">20</div> <div style="margin-bottom: 10px;">405</div> <div style="margin-bottom: 10px;">25</div> <div style="margin-bottom: 10px;">400</div> <div style="margin-bottom: 10px;">30</div> <div style="margin-bottom: 10px;">395</div> <div style="margin-bottom: 10px;">35</div> </div> 		Topsoil with grass root mat. 430.5 Medium dense moist brown silty fine SAND. 430.3			
		Dense moist brown silty coarse to fine SAND, trace gravel. 5.5 425 7.0 Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT. 423.5			

LOG OF TEST BORING

TEST BORING TP-35

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion


PROJECT NO.: 2014-3198-01

SURFACE ELEVATION: 436.5 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>0</p> <p>435</p> <p>5</p> <p>430</p> <p>10</p> <p>425</p> <p>15</p> <p>420</p> <p>20</p> <p>415</p> <p>25</p> <p>410</p> <p>30</p> <p>405</p> <p>35</p> <p>1</p> </div>  </div>		<p>Asphalt. 436.5</p> <p>Aggregate base course. 436.2</p> <p>Medium dense moist brown silty coarse to fine SAND. 435.9</p> <p>(FILL) 434</p> <p>Soft moist gray to black clayey SILT, trace concrete fragments and metal debris. (FILL) 7.0</p> <p>Completion Depth = 7 feet 429.5</p> <p>END OF TEST BORING @ 7.0 FT.</p>			

LOG OF TEST BORING

TEST BORING TP-36

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 436.0 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds


ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; flex-direction: column; align-items: center;"> <div style="margin-bottom: 10px;">0</div> <div style="margin-bottom: 10px;">435</div> <div style="margin-bottom: 10px;">5</div> <div style="margin-bottom: 10px;">430</div> <div style="margin-bottom: 10px;">10</div> <div style="margin-bottom: 10px;">425</div> <div style="margin-bottom: 10px;">15</div> <div style="margin-bottom: 10px;">420</div> <div style="margin-bottom: 10px;">20</div> <div style="margin-bottom: 10px;">415</div> <div style="margin-bottom: 10px;">25</div> <div style="margin-bottom: 10px;">410</div> <div style="margin-bottom: 10px;">30</div> <div style="margin-bottom: 10px;">405</div> <div style="margin-bottom: 10px;">35</div> <div style="margin-bottom: 10px;">400</div> </div>		<p>Asphalt. 436 0.4</p> <p>Aggregate base course. 435.6 0.7</p> <p>Medium dense brown silty SAND and GRAVEL. (FILL) 435.3 2.0</p> <p>Firm very moist brown gray clayey SILT. 434</p>	<p>7.0</p>	<p>429</p>	<p>Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.</p>

LOG OF TEST BORING

TEST BORING TP-37

DATE: 9/24/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 435.0 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
435 0		Asphalt. 435			
		Aggregate base course. 434.6			
		Medium dense moist brown silty coarse to fine SAND. 434.3			
		(FILL) 433			
430 5		Dense moist brown SAND, GRAVEL and COBBLES. 5.0			
		(FILL) 430			
		Firm moist gray brown clayey SILT. 7.0			
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	428		
425 10					
415 20					
410 25					
405 30					
400 35					

LOG OF TEST BORING

TEST BORING TP-38

DATE: 9/24/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRAWING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01

SURFACE ELEVATION: 435.0 ft.

CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
435 0		Asphalt	435		
		Aggregate base course.	0.5		
		Medium dense moist gray brown silty SAND.	434.5		
		(FILL)	1.0		
		Soft to firm very moist gray clayey SILT.	434		
		Medium dense moist brown silty fine SAND.	2.0		
430 5		Completion Depth = 7 feet	433		
		END OF TEST BORING @ 7.0 FT.	4.0		
425 10			431		
415 20			7.0		
410 25		428			
405 30					
400 35					

LOG OF TEST BORING

TEST BORING TP-39

DATE: 9/25/14
PROJECT: Villanova University LAH Project
BORING LOCATION: See Drawings
DRILLING METHOD: Hollow Stem Auger
DRILLING COMPANY: Earth Core Services
WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01
SURFACE ELEVATION: 434.0 ft.
CHECKED BY: PFM
DRILLER: T. Fryberger
INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
<div style="display: flex; align-items: center;"> <div style="flex: 1;"> </div> <div style="flex: 1; padding-left: 10px;"> <p>Asphalt. 434 0.3</p> <p>Aggregate base course. 433.7 0.7</p> <p>Medium dense moist brown silty coarse to fine SAND and GRAVEL. 433.3</p> </div> </div>					
		Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	7.0 427		

LOG OF TEST BORING

TEST BORING TP-40

DATE: 9/25/14

PROJECT: Villanova University LAH Project

BORING LOCATION: See Drawings

DRILLING METHOD: Hollow Stem Auger

DRILLING COMPANY: Earth Core Services

WATER ENCOUNTERED AT: Dry at Completion

PROJECT NO.: 2014-3198-01

SURFACE ELEVATION: 434.0 ft.



CHECKED BY: PFM

DRILLER: T. Fryberger

INSPECTOR: M. Simonds

ELEVATION / DEPTH	SOIL SYMBOLS SAMPLER SYMBOLS BLOWS PER 6 INCHES	Soil Description	SPT (N)	Moisture (%)	Other Tests
		Asphalt. Aggregate base course. Medium dense moist brown silty fine SAND. Medium dense moist brown silty SAND and GRAVEL. Completion Depth = 7 feet END OF TEST BORING @ 7.0 FT.	434 0.3 433.7 0.7 433.3 4.0 430 7.0 427		

Appendix



Villanova University
 Lancaster Avenue Housing
 Lancaster and Ithan Avenues
 Villanova PA 19085

**VMA
 RAMSA**

ARCHITECT-OF-RECORD
 Voith & Mactavish Architects LLP
 2401 Walnut Street, 6th Floor
 Philadelphia, PA 19103
 phone: 215-545-4544
 fax: 215-545-3299
 www.voithandmactavish.com

DESIGN ARCHITECT
 Robert A.M. Stern Architects LLP
 450 West 34th Street
 New York, New York 10001
 phone: 212-967-5100
 fax: 212-967-5588
 www.ramsa.com

CIVIL ENGINEER
 Nave Newell Inc.
 900 West Valley Road, Suite 1100
 Wayne, PA 19087
 phone: 610-265-8323
 fax: 610-265-4299
 www.navenewell.com

STRUCTURAL ENGINEER
 Macintosh Engineering
 One East Uwchlan Avenue, Ste. 403
 Exton, PA 19341
 phone: 484-475-2180
 fax: 484-475-2181
 www.macintosheng.com


MEP&FP ENGINEER
 Bala Consulting Engineers, Inc.
 443 South Gulph Road
 King of Prussia, PA 19406
 phone: 610-649-8000
 fax: 910-649-8475

LANDSCAPE ARCHITECT
 Sikora Wells Appel
 8 Kings Highway West, Suite A
 Haddonfield, NJ 08033
 phone: 856-433-6381
 www.sikora-wa.com

ACOUSTIC CONSULTANT
 Acentech Inc.
 8 Interplex Drive, Suite 218
 Treviso, PA 19053
 phone: 215-245-8244
 fax: 215-245-1796
 www.acentech.com

ELEVATOR CONSULTANT
 Zipf Associates Inc.
 25 Bala Avenue, Suite 201
 Bala Cynwyd, PA 19004
 phone: 610-667-1717
 fax: 610-667-0216

Gregory C. Newell



PRELIM. LAND DEVELOPMENT
 SUBMISSION


Revision	Date	Title	Scale	Drawn By
	December 5, 2014	Pre Development Drainage Plan	1" = 60'	MMB

1 OF 4

Sheet No. 1 of 4

Contractor to verify all dimensions in field and inform Architect of any discrepancies before starting work.

20112071855
 20112071860
 20112071907
 20112071927
 20112071972
 PROJECT SERIAL AND
 CALL BEFORE YOU DIGI
 PENNSYLVANIA LAW REQUIRES
 3 WORKING DAYS NOTICE FOR
 CONSTRUCTION PHASE AND 10 WORKING
 DAYS IN DESIGN STAGE - STOP CALL
 Pennsylvania One Call System, Inc.
 1-800-242-1776



**VMA
RAMSA**

ARCHITECT-OF-RECORD
Voith & Mactavish Architects LLP
2401 Walnut Street, 6th Floor
Philadelphia, PA 19103
phone: 215-545-4544
fax: 215-545-3299
www.voithandmactavish.com

DESIGN ARCHITECT
Robert A.M. Stern Architects LLP
450 West 34th Street
New York, New York 10001
phone: 212-967-5100
fax: 212-967-5588
www.ramsa.com

CIVIL ENGINEER
Nave Newell Inc.
900 West Valley Road, Suite 1100
Wayne, PA 19087
phone: 610-265-8323
fax: 610-265-4299
www.navenewell.com


STRUCTURAL ENGINEER
MacIntosh Engineering
One East Uchlan Avenue, Ste. 403
Exton, PA 19341
phone: 484-475-2180
fax: 484-475-2181
www.macintosheng.com

MEP&FP ENGINEER
Bala Consulting Engineers, Inc.
443 South Gulph Road
King of Prussia, PA 19406
phone: 610-649-8000
fax: 910-649-8475

LANDSCAPE ARCHITECT
Silkora Wells Appel
8 Kings Highway West, Suite A
Haddonfield, NJ 08033
phone: 856-433-6381
www.silkora-wa.com

ACOUSTIC CONSULTANT
Accentech Inc.
8 Interplex Drive, Suite 218
Trevose, PA 19053
phone: 215-245-8244
fax: 215-245-1796
www.accentech.com

ELEVATOR CONSULTANT
Zipf Associates Inc.
25 Bala Avenue, Suite 201
Bala Cynwyd, PA 19004
phone: 610-667-1717
fax: 610-667-0216



PEAK RATE

INFILTRATION 1	CN = 85	Tc = 10 MIN	A = 1.518 AC	CN = 74	Tc = 38.4 MIN	A = 1.612 AC	TOTAL
							AREA = 3.139 AC

INFILTRATION 2	CN = 93	Tc = 10 MIN	A = 0.681 AC	CN = 75	Tc = 14.9 MIN	A = 1.083 AC	CN = 98	Tc = 10 MIN	A = 1.281 AC	TOTAL
										AREA = 3.045 AC

INFILTRATION 3	CN = 83	Tc = 10 MIN	A = 0.291 AC
----------------	---------	-------------	--------------

DETENTION BASIN 1	CN = 77	Tc = 23.7 MIN	A = 0.702 AC
-------------------	---------	---------------	--------------

UNCAPTURED	CN = 77	Tc = 10 MIN	A = 1.916 AC	CN = 96	Tc = 10 MIN	A = 0.181 AC	CN = 98	Tc = 10 MIN	A = 0.204 AC	TOTAL
										AREA = 2.301 AC

LANCASTER AVENUE WIDENING
NOTE: 3000 S.F. FOR PROPOSED WIDENING IS OFFSET BY ADDING 3000 S.F. TO AREA 2A. THEREFORE, THERE IS NO IMPACT TO POI 2B.

20112071855
20112071869
20112071907
20112071937
20112071957
20112071977
20112071997
20112082372
PROJECT SERIAL AND
CALL BEFORE YOU DIG!
PENNSYLVANIA LAW REQUIRES
3 WORKING DAYS NOTICE FOR
CONSTRUCTION PHASE AND 10 WORKING
DAYS IN DESIGN STAGE - STOP CALL
Pennsylvania One Call System, Inc.
1-800-242-1776

Gregory C. Newell

PRELIM. LAND DEVELOPMENT
SUBMISSION

Revision

Date	December 5, 2014
Title	Post Development Drainage Plan
Scale	1" = 60'
Drawn By	MMB

Sheet No. 2 of 4
Contractor to verify all dimensions in field and inform Architect of any discrepancies before starting work.

VMA
 RAMSA

ARCHITECT-OF-RECORD
 Voith & Mactavish Architects LLP
 2401 Walnut Street, 6th Floor
 Philadelphia, PA 19103
 phone: 215-545-4544
 fax: 215-545-3299
 www.voithandmactavish.com

DESIGN ARCHITECT
 Robert A.M. Stern Architects LLP
 460 West 34th Street
 New York, New York 10001
 phone: 212-967-5100
 fax: 212-967-5588
 www.ramsa.com

CIVIL ENGINEER
 Nave Newell Inc.
 900 West Valley Road, Suite 1100
 Wayne, PA 19087
 phone: 610-265-8323
 fax: 610-265-4999
 www.navenewell.com

STRUCTURAL ENGINEER
 Macintosh Engineering
 One East Uwchlan Avenue, Ste. 403
 Exton, PA 19341
 phone: 484-475-2180
 fax: 484-475-2181
 www.macintosheng.com


MEP&FP ENGINEER
 Bala Consulting Engineers, Inc.
 443 South Gulph Road
 King of Prussia, PA 19406
 phone: 610-649-8000
 fax: 910-649-8475

LANDSCAPE ARCHITECT
 Sikora Wells Appel
 8 Kings Highway West, Suite A
 Haddonfield, NJ 08033
 phone: 856-433-6381
 www.sikora-wa.com

ACOUSTIC CONSULTANT
 Acentech Inc.
 8 Interplex Drive, Suite 218
 Trevas, PA 19053
 phone: 215-245-8244
 fax: 215-245-1796
 www.acentech.com

ELEVATOR CONSULTANT
 Zipf Associates Inc.
 25 Bala Avenue, Suite 201
 Bala Cynwyd, PA 19004
 phone: 610-667-1717
 fax: 610-667-0216

Gregory C. Newell





PRELIM. LAND DEVELOPMENT
 SUBMISSION

Revision	
Date	December 5, 2014
Title	Post Development Drainage Plan (Volume Management)
Scale	1" = 60'
Drawn By	MMB

3 OF 4

Sheet No. 3 of 4

Contractor to verify all dimensions in field and inform Architect of any discrepancies before starting work.




LANCASTER AVENUE WIDENING
 NOTE: 3000 S.F. FOR PROPOSED
 WIDENING IS OFFSET BY ADDING
 3000 S.F. TO AREA 2A. THEREFORE,
 THERE IS NO IMPACT TO POI 2B.


IMPERVIOUS SURFACE TO BMPs	
RG-1	9247 SF
RG-2	3307 SF
RG-3	8867 SF
RG-4	5065 SF
RG-5	7319 SF
RG-6	6626 SF
RG-7	3047 SF
RG-8	7183 SF
RG-9	4385 SF
RG-10	9215 SF
CIS-1	153918 SF
CIS-2	28839 SF
INF-1	42610 SF
INF-2	25785 SF
INF-3	7411 SF

DRAINAGE AREA TO
 CISTERN No. 1 & 2

DEDICATED OPEN SPACE
 GROSS AREA: 3.88 ACRES
 NET UNPROTECTED AREA: 2.00 ACRES

20112071855
 20112071869
 20112071909
 20112071937
 20112071972
 PROJECT SERIAL NO.
 CALL BEFORE YOU DIG!
 PENNSYLVANIA LAW REQUIRES
 3 WORKING DAYS NOTICE FOR
 CONSTRUCTION PHASE AND 10 WORKING
 DAYS IN DESIGN STAGE - STOP CALL
 Pennsylvania One Call System, Inc.
 1-800-242-1776





Villanova University
 Lancaster Avenue Housing
 Lancaster and Ithan Avenues
 Villanova PA 19085

VMA RAMSA

ARCHITECT-OF-RECORD
 Voith & Mactavish Architects LLP
 2401 Walnut Street, 6th Floor
 Philadelphia, PA 19103
 phone: 215-545-4544
 fax: 215-545-3299
 www.voithandmactavish.com

DESIGN ARCHITECT
 Robert A.M. Stern Architects LLP
 460 West 34th Street
 New York, New York 10001
 phone: 212-967-5100
 fax: 212-967-5588
 www.ramsa.com

CIVIL ENGINEER
 Nave Newell Inc.
 900 West Valley Road, Suite 1100
 Wayne, PA 19087
 phone: 610-265-8323
 fax: 610-265-4299
 www.navenewell.com

STRUCTURAL ENGINEER
 MacIntosh Engineering
 One East Uchlan Avenue, Ste. 403
 Exton, PA 19341
 phone: 484-475-2180
 fax: 484-475-2181
 www.macintosheng.com


MEP&FP ENGINEER
 Bala Consulting Engineers, Inc.
 443 South Gulph Road
 King of Prussia, PA 19406
 phone: 610-649-8000
 fax: 910-649-8475

LANDSCAPE ARCHITECT
 Sikora Wells Appel
 8 Kings Highway West, Suite A
 Haddonfield, NJ 08033
 phone: 856-433-6381
 www.sikora-wa.com

ACOUSTIC CONSULTANT
 Acentech Inc.
 8 Interplex Drive, Suite 218
 Trevose, PA 19053
 phone: 215-245-8244
 fax: 215-245-1796
 www.acentech.com

ELEVATOR CONSULTANT
 Zipf Associates Inc.
 25 Bala Avenue, Suite 201
 Bala Cynwyd, PA 19004
 phone: 610-667-1717
 fax: 610-667-0216

Gregory C. Newell



PRELIM. LAND DEVELOPMENT
 SUBMISSION

Revision
 Date December 5, 2014
 Title Inlet Area
 Drainage Plan
 Scale 1" = 60'
 Drawn By MMB

4 OF 4

Sheet No. 4 of 4

Contractor to verify all dimensions in field and inform
 Architect of any discrepancies before starting work.

20112071855
 20112071869
 20112071907
 20112071927
 20112071972
 PROJECT SERIAL NO.
 CALL BEFORE YOU DIG!
 PENNSYLVANIA LAW REQUIRES
 3 WORKING DAYS NOTICE FOR
 CONSTRUCTION PHASE AND 10 WORKING
 DAYS IN DESIGN STAGE - STOP CALL
 Pennsylvania One Call System, Inc.
 1-800-242-1776